

Package ‘besthr’

April 14, 2023

Type Package

Title Generating Bootstrap Estimation Distributions of HR Data

Version 0.3.2

Description Creates plots showing scored HR experiments and plots of distribution of means of ranks of HR score from bootstrapping. Authors (2019) <[doi:10.5281/zenodo.3374507](https://doi.org/10.5281/zenodo.3374507)>.

License MIT + file LICENSE

Encoding UTF-8

Imports dplyr, ggplot2, ggridges, magrittr, patchwork, rlang, stringr, tibble

RoxygenNote 7.1.2

Suggests knitr, rmarkdown, readr

VignetteBuilder knitr

NeedsCompilation no

Author Dan MacLean [aut, cre]

Maintainer Dan MacLean <dan.maclean@tsl.ac.uk>

Repository CRAN

Date/Publication 2023-04-14 08:50:08 UTC

R topics documented:

estimate	2
make_data	3
make_data2	3
make_data3	4
plot.hrest	4
print.hrest	5

Index

6

estimate	<i>Perform bootstrap estimation of confidence intervals of ranked HR scores</i>
----------	---

Description

estimate carries out estimation of bootstrap confidence intervals on ranked score data. Returns a hrest object of the result Proceeds by calculating score ranks, then bootstrapping ranks in non-control groups retaining the mean for each bootstrap iteration. Calculates low and high quantiles of bootstrap mean distributions for each group. If technical replicates are provided in a second grouping column these will be averaged before proceeding.

Usage

```
estimate(df, ..., control = "A", nits = 100, low = 0.025, high = 0.975)
```

Arguments

df	data frame of score and group data. Contains minimally a score and group column
...	bare names of columns to use, minimally the score column and the group column in that order. Optionally a third technical replicate column can be provided
control	the value of the grouping column taken to be the control group
nits	the number of bootstrap iterations to be done
low	the low probability value of the quantile
high	the high probability value of the quantile

Value

a list object of class "hrest"

Examples

```
d1 <- make_data()
estimate(d1, score, group)

d2 <- make_data2()
estimate(d2, score_column_name, sample_column_name, rep_column_name )

d3 <- make_data3()
estimate(d3, score, sample, rep, nits = 1000)
```

make_data

return a sample data set of random values for two groups

Description

return a sample data set of random values for two groups

Usage

```
make_data()
```

Value

tibble of random values for two groups

Examples

```
d1 <- make_data()
```

make_data2

return a sample data set of random values for two groups with three technical reps per group

Description

return a sample data set of random values for two groups with three technical reps per group

Usage

```
make_data2()
```

Value

tibble of random values for two groups with three technical reps per group

Examples

```
d2 <- make_data2()
```

<code>make_data3</code>	<i>return a sample data set of random values for three groups with three technical reps per group</i>
-------------------------	---

Description

@examples

Usage

```
make_data3()
```

Details

```
d3 <- make_data3()
```

Value

tibble of random values for three groups with three technical reps per group

<code>plot.hrest</code>	<i>plots the hrest object</i>
-------------------------	-------------------------------

Description

returns a ggplot object representing the hrest object from `estimate`. The content of left panel varies according to the value of the `which` parameter. If `which = "rank_simulation"` is used a plot of rank score values will be plotted in the left panel. In this case technical replicates will be averaged if provided. If `which = "just_data"` a plot of scores only is created and technical replicates are displayed as is. In each case, the right hand panel shows the rank bootstrap distribution and confidence interval boundaries for all non-control groups.

Usage

```
## S3 method for class 'hrest'
plot(x, ..., which = "rank_simulation")
```

Arguments

<code>x</code>	the hrest object from <code>estimate</code>
<code>...</code>	Other parameters
<code>which</code>	the type of left hand panel to create. Either "rank_simulation" or "just_data"

Value

ggplot object

Examples

```
d1 <- make_data()  
hr_est <- estimate(d1, score, group)  
plot(hr_est)
```

<code>print.hrest</code>	<i>print a summary of the hrest object</i>
--------------------------	--

Description

print a summary of the hrest object

Usage

```
## S3 method for class 'hrest'  
print(x, ...)
```

Arguments

<code>x</code>	hrest object
<code>...</code>	other parameters

Value

`null`

Examples

```
d1 <- make_data()  
hr_est <- estimate(d1, score, group)  
print(hr_est)
```

Index

estimate, [2](#), [4](#)

make_data, [3](#)

make_data2, [3](#)

make_data3, [4](#)

plot.hrest, [4](#)

print.hrest, [5](#)