

Package ‘bodenmiller’

October 12, 2022

Type Package

Title Profiling of Peripheral Blood Mononuclear Cells using CyTOF

Version 0.1.1

Depends R (>= 3.1.0)

Suggests ggplot2, cytofan, dplyr, reshape2, RColorBrewer, knitr,
rmarkdown

Description

This data package contains a subset of the Bodenmiller et al, Nat Biotech 2012 dataset for testing single cell, high dimensional analysis and visualization methods.

License CC0

Encoding UTF-8

LazyData TRUE

LazyDataCompression xz

URL <https://github.com/yannabraham/bodenmiller>

BugReports <https://github.com/yannabraham/bodenmiller/issues>

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Yann Abraham [aut, cre],
Bernd Bodenmiller [aut]

Maintainer Yann Abraham <yann.abraham@gmail.com>

Repository CRAN

Date/Publication 2021-04-11 15:20:06 UTC

R topics documented:

refAnnots	2
refFuncMat	2
refPhenoMat	3

untreatedAnnots	4
untreatedFuncMat	5
untreatedPhenoMat	6

refAnnots	<i>Reference Annotation</i>
------------------	-----------------------------

Description

A `data.frame` containing the source file and cell type for every cell in `refPhenoMat` and `refFuncMat`. See [Bodenmiller et al 2012](#) for details.

Usage

```
refAnnots
```

Format

a `data.frame` with 15792 rows and 2 variables:

- `Source`the name of the source (fcs) file
- `Cell`the cell type for the corresponding row in `refPhenoMat` or `refFuncMat`

Source

<https://reports.cytobank.org/105/v2/>

refFuncMat	<i>Reference Matrix (Functional)</i>
-------------------	--------------------------------------

Description

a `matrix` containing the signal intensity for functional markers measured using CyTOF on different cell types. See [Bodenmiller et al 2012](#) for details.

Usage

```
refFuncMat
```

Format

a matrix with 15792 rows and 14 variables:

- pStat1
- pSlp76
- pBtk
- pPlcg2
- pErk
- pLat
- pS6
- pNFkB
- pp38
- pStat5
- pAkt
- pSHP2
- pZap70
- pStat3

Source

<https://reports.cytobank.org/105/v2/>

refPhenoMat

Reference Matrix (Phenotypic)

Description

a matrix containing the signal intensity for phenotypic markers measured using CyTOF on different cell types. See [Bodenmiller et al 2012](#) for details.

Usage

refPhenoMat

Format

a matrix with 15792 rows and 9 variables:

- CD20
- IgM
- CD4
- CD33

- HLA-DR
- CD14
- CD7
- CD3
- CD123

Source

<https://reports.cytobank.org/105/v2/>

untreatedAnnots

Untreated Samples with 4 Different Treatments (Annotation)

Description

A data.frame containing the source file, cell type and stimulation for every cell in `refPhenoMat` and `refFuncMat`. Stimulations include BCR/FcR-XL, PMA/Ionomycin and vanadate. See [Bodenmiller et al 2012](#) for details.

Usage

`untreatedAnnots`

Format

a data.frame with 15792 rows and 2 variables:

- Source the name of the source (fcs) file
- Treatment the treatment for the corresponding row in `refPhenoMat` or `refFuncMat`
- Cell the cell type for the corresponding row in `refPhenoMat` or `refFuncMat`

Source

<https://reports.cytobank.org/105/v2/>

untreatedFuncMat

Untreated Samples with 4 Different Treatments (Functional)

Description

a matrix containing the signal intensity for functional markers measured using CyTOF on different cell types, after stimulation with BCR/FcR-XL, PMA/Ionomycin and vanadate. See [Bodenmiller et al 2012](#) for details.

Usage

```
untreatedFuncMat
```

Format

a matrix with 15792 rows and 14 variables:

- pStat1
- pSlp76
- pBtk
- pPlcg2
- pErk
- pLat
- pS6
- pNFkB
- pp38
- pStat5
- pAkt
- pSHP2
- pZap70
- pStat3

Source

<https://reports.cytobank.org/105/v2/>

untreatedPhenoMat *Untreated Samples with 4 Different Treatments (Phenotypic)*

Description

a matrix containing the signal intensity for phenotypic markers measured using CyTOF on different cell types, after stimulation with BCR/FcR-XL, PMA/Ionomycin and vanadate. See [Bodenmiller et al 2012](#) for details.

Usage

untreatedPhenoMat

Format

a matrix with 15792 rows and 9 variables:

- CD20
- IgM
- CD4
- CD33
- HLA-DR
- CD14
- CD7
- CD3
- CD123

Source

<https://reports.cytobank.org/105/v2/>

Index

* datasets

refAnnots, [2](#)
refFuncMat, [2](#)
refPhenoMat, [3](#)
untreatedAnnots, [4](#)
untreatedFuncMat, [5](#)
untreatedPhenoMat, [6](#)

refAnnots, [2](#)
refFuncMat, [2, 2, 4](#)
refPhenoMat, [2, 3, 4](#)

untreatedAnnots, [4](#)
untreatedFuncMat, [5](#)
untreatedPhenoMat, [6](#)