

Package ‘WeibullR.learnr’

January 20, 2025

Type Package

Title An Interactive Introduction to Life Data Analysis

Version 0.2

URL <https://paulgovan.github.io/WeibullR.learnr/>,
<https://github.com/paulgovan/WeibullR.learnr>

BugReports <https://github.com/paulgovan/WeibullR.learnr/issues>

Description An interactive introduction to Life Data Analysis that depends on 'WeibullR' by David Silkworth and Jurgen Symynck (2022) <<https://CRAN.R-project.org/package=WeibullR>>, a R package for Weibull Analysis, and 'learnr' by Garrick Aden-Buie et al. (2023) <<https://CRAN.R-project.org/package=learnr>>, a framework for building interactive learning modules in R.

Imports learnr, ReliaGrowR, WeibullR, WeibullR.ALT

Suggests WeibullR.plotly, WeibullR.shiny

License CC BY 4.0

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Paul Govan [aut, cre, cph] (<<https://orcid.org/0000-0002-1821-8492>>)

Maintainer Paul Govan <paul.govan2@gmail.com>

Repository CRAN

Date/Publication 2024-11-04 17:20:02 UTC

Contents

avail	2
fr	2
mtbf	3
mttf	4

RAMR.learnr	4
rel	5
serv	5
TestR.learnr	6

Index	7
--------------	----------

avail	<i>Availability.</i>
-------	----------------------

Description

Availability.

Usage

```
avail(unavailTime, totalTime)
```

Arguments

unavailTime	Unavailable Time. A numeric value representing the unavailable time or a numeric vector of unavailable times.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the availability for a given period.

Examples

```
unavail <- 100
total <- 1000
avail(unavail, total)
```

fr	<i>Failure Rate (lambda).</i>
----	-------------------------------

Description

Failure Rate (lambda).

Usage

```
fr(failures, totalTime)
```

Arguments

failures	Failures. A numeric value representing the number of failures for a given period.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the failure rate (λ) for a given period.

Examples

```
fail <- 75
total <- 5000
fr(fail, total)
```

mtbf

Mean Time Between Failures (MTBF).

Description

Mean Time Between Failures (MTBF).

Usage

```
mtbf(failures, totalTime)
```

Arguments

failures	Failures. A numeric value representing the number of failures for a given period.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the MTBF for a given period.

Examples

```
fail <- 5
total <- 1000
mtbf(fail, total)
```

mttf *Mean Time To Failure (MTTF).*

Description

Mean Time To Failure (MTTF).

Usage

```
mttf(failures, totalTime)
```

Arguments

failures	Failures. A numeric value representing the number of failures for a given period.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the MTTF for a given period.

Examples

```
fail <- 5
total <- 1000
mttf(fail, total)
```

RAMR.learnr *Reliability, Availability, and Maintainability*

Description

RAMR.learnr is an interactive introduction to RAM analysis.

Usage

```
RAMR.learnr()
```

Value

This function does not return a value.

See Also

<https://paulgovan.github.io/WeibullR.learnr/>

Examples

```
if (interactive()) {  
  RAMR.learnr()  
}
```

rel	<i>Reliability.</i>
-----	---------------------

Description

Reliability.

Usage

```
rel(outageTime, totalTime)
```

Arguments

outageTime	Forced Outage Time. A numeric value representing the forced outage time or a numeric vector of outage times.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the reliability for a given period.

Examples

```
outage <- 100  
total <- 1000  
rel(outage, total)
```

serv	<i>Serviceability.</i>
------	------------------------

Description

Serviceability.

Usage

```
serv(serviceTime, totalTime)
```

Arguments

serviceTime	Service Time. A numeric value representing the service time or a numeric vector of service times.
totalTime	Total Time. A numeric value representing the total time for a given period or a numeric vector of time periods

Value

The function returns a numeric value representing the serviceability factor for a given period.

Examples

```
service <- 900
total <- 1000
serv(service, total)
```

TestR.learnr

An Interactive Introduction to Reliability Testing

Description

TestR.learnr is an interactive introduction to Reliability Testing.

Usage

```
TestR.learnr()
```

Value

This function does not return a value.

See Also

<https://paulgovan.github.io/WeibullR.learnr/>

Examples

```
if (interactive()) {
  TestR.learnr()
}
```

Index

avail, 2

fr, 2

mtbf, 3

mttf, 4

RAMR.learnr, 4

rel, 5

serv, 5

TestR.learnr, 6