

Package ‘BOJ’

January 21, 2025

Type Package

Title Interface to Bank of Japan Statistics

Version 0.3.4

Description Provides an interface to Bank of Japan <<https://www.boj.or.jp>> statistics.

License MIT + file LICENSE

URL <https://github.com/stefanangrick/BOJ>

BugReports <https://github.com/stefanangrick/BOJ/issues>

Suggests knitr, rmarkdown, ggplot2, zoo

Imports dplyr, readr, tidyr, tidyselect, rvest, xml2

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Stefan Angrick [aut, cre, cph]

Maintainer Stefan Angrick <contact@stefanangrick.net>

Repository CRAN

Date/Publication 2025-01-19 11:10:02 UTC

Contents

get_boj	2
get_boj_datasets	2
pivot_longer_boj	3
Index	4

get_boj	<i>Download and parse a BOJ data set</i>
---------	--

Description

Download and parse a BOJ data set

Usage

```
get_boj(item_url, auto_pivot = TRUE, ...)
```

Arguments

item_url	Character. URL of the data set to be imported (usually obtained via <code>get_boj_datasets()</code>).
auto_pivot	Logical. Controls whether source data set is converted to long format. Set this to FALSE to disable conversion (default: TRUE).
...	Arguments passed to <code>download.file()</code> (e.g. <code>quiet = TRUE</code>).

Value

A tibble data frame, or a list of tibble data frames in cases where the source zip file contains multiple csv files.

Examples

```
ds <- get_boj_datasets()
df <- get_boj(ds$url[(ds$name == "sppi_q_en")])
```

get_boj_datasets	<i>Retrieve a list of available BOJ data sets</i>
------------------	---

Description

Retrieve a list of available BOJ data sets

Usage

```
get_boj_datasets(
  base_url = "https://www.stat-search.boj.or.jp/info/dload_en.html"
)
```

Arguments

base_url	Character. URL of the BOJ's Time-Series Data portal flat files page (optional).
----------	---

Value

A tibble data frame.

Examples

```
ds <- get_boj_datasets()
```

`pivot_longer_boj` *Convert a BOJ data set to long format*

Description

Convert a BOJ data set to long format

Usage

```
pivot_longer_boj(tbl)
```

Arguments

`tbl` Tibble. A tibble data frame containing a BOJ data set (usually obtained via `get_boj(item_url, auto_pivot = FALSE)`).

Value

A tibble data frame in long format.

Examples

```
ds <- get_boj_datasets()
sppi <- get_boj(ds$url[(ds$name == "sppi_q_en")], auto_pivot = FALSE)
sppi <- subset(sppi, code == "PRCS15_52S0000000_CQ")
sppi <- pivot_longer_boj(sppi)
```

Index

`get_boj`, [2](#)
`get_boj_datasets`, [2](#)
`pivot_longer_boj`, [3](#)