

Package ‘admiralophtha’

January 16, 2025

Type Package

Title ADaM in R Asset Library - Ophthalmology

Version 1.2.0

Description Aids the programming of Clinical Data Standards Interchange Consortium (CDISC) compliant Ophthalmology Analysis Data Model (ADaM) datasets in R. ADaM datasets are a mandatory part of any New Drug or Biologics License Application submitted to the United States Food and Drug Administration (FDA). Analysis derivations are implemented in accordance with the “Analysis Data Model Implementation Guide” (CDISC Analysis Data Model Team, 2021, <https://www.cdisc.org/standards/foundational/adam/adamig-v1-3-release-package>).

License Apache License (>= 2)

URL <https://pharmaverse.github.io/admiralophtha/>,
<https://github.com/pharmaverse/admiralophtha/>

BugReports <https://github.com/pharmaverse/admiralophtha/issues/>

Depends R (>= 4.1)

Imports admiral (>= 1.1.1), admiraldev (>= 1.1.0), cli (>= 3.6.2),
dplyr (>= 1.0.5), hms (>= 0.5.3), lifecycle (>= 0.1.0),
lubridate (>= 1.7.4), magrittr (>= 1.5), purrr (>= 0.3.3),
rlang (>= 0.4.4), stringr (>= 1.4.0), tidyr (>= 1.0.2),
tidyselect (>= 1.1.0)

Suggests devtools, diffdf, knitr, lintr, methods, miniUI,
pharmaversesdtm (>= 1.0.0), pkgdown, rmarkdown, roxygen2,
spelling, testthat (>= 3.0.0), tibble, usethis

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData true

RoxygenNote 7.3.2

NeedsCompilation no

Author Edoardo Mancini [aut, cre] (<<https://orcid.org/0009-0006-4899-8641>>),
 Ritika Aggarwal [aut],
 Jane Gao [aut],
 William Holmes [aut],
 Josie Jackson [aut],
 Sonali Jain [aut],
 Yuki Matsunaga [aut],
 Gordon Miller [aut],
 Rachel Linacre [aut],
 Lucy Palmen [aut],
 Nandini R Thampi [aut],
 Aldrich Salva [aut],
 Steven Ting [aut]

Maintainer Edoardo Mancini <edoardo.mancini@roche.com>

Repository CRAN

Date/Publication 2025-01-16 10:30:09 UTC

Contents

admiralophtha_adbcva	2
admiralophtha_adoe	3
admiralophtha_advfq	3
convert_etdrs_to_logmar	4
convert_logmar_to_etdrs	5
derive_var_afeye	6
derive_var_bcvacritxfl	7
derive_var_studyeye	10

Index 12

admiralophtha_adbcva *Best Corrected Visual Acuity Analysis Dataset*

Description

An example Best Corrected Visual Acuity (BCVA) analysis dataset

Usage

```
admiralophtha_adbcva
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 7672 rows and 116 columns.

Source

Derived from the OE and ADSL datasets using {admiral}, {admiralophtha} and (https://github.com/pharmaverse/admiralophtha/blob/main/inst/templates/ad_adbcva.R)

See Also

Other datasets: [admiralophtha_adoe](#), [admiralophtha_advfq](#)

admiralophtha_adoe	<i>Ophthalmology Exam Analysis Dataset</i>
--------------------	--

Description

An example Ophthalmology Exam Analysis dataset

Usage

```
admiralophtha_adoe
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 7672 rows and 98 columns.

Source

Derived from the OE and ADSL datasets using {admiral}, {admiralophtha} and (https://github.com/pharmaverse/admiralophtha/blob/main/inst/templates/ad_adoe.R)

See Also

Other datasets: [admiralophtha_adbcva](#), [admiralophtha_advfq](#)

admiralophtha_advfq	<i>Visual Function Questionnaire Analysis Dataset</i>
---------------------	---

Description

An example Visual Function Questionnaire (VFQ) analysis dataset

Usage

```
admiralophtha_advfq
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 28798 rows and 41 columns.

Source

Derived from the ADSL and QS datasets using {admiral}, {admiralophtha} and (https://github.com/pharmaverse/admiralophtha/blob/main/inst/templates/ad_advfq.R)

See Also

Other datasets: [admiralophtha_adbcva](#), [admiralophtha_adoe](#)

convert_etdrs_to_logmar

ETDRS -> LogMAR conversion

Description

Convert ETDRS score to LogMAR units

Usage

```
convert_etdrs_to_logmar(value)
```

Arguments

value object containing ETDRS score to convert to logMAR

Details

ETDRS value converted to logMAR as $\text{logMAR} = -0.02 * \text{ETDRS} + 1.7$

Source for conversion formula: Beck, R.W., et al. A computerized method of visual acuity testing. American Journal of Ophthalmology, 135(2), pp.194-205. doi:[https://doi.org/10.1016/s0002-9394\(02\)01825-1](https://doi.org/10.1016/s0002-9394(02)01825-1).

Value

The input value converted converted to logMAR units

Author(s)

Rachel Linacre

Examples

```
library(tibble)
library(dplyr)
library(admiral)
library(admiraldev)

adbcva <- tribble(
  ~STUDYID, ~USUBJID, ~AVAL,
```

```

"XXX001", "P01", 5,
"XXX001", "P02", 10,
"XXX001", "P03", 15,
"XXX001", "P04", 20,
"XXX001", "P05", 25
)

adbcva <- adbcva %>% mutate(AVAL = convert_etdrs_to_logmar(AVAL))

```

```
convert_logmar_to_etdrs
```

LogMAR -> ETDRS conversion

Description

Convert LogMAR score to ETDRS units

Usage

```
convert_logmar_to_etdrs(value)
```

Arguments

value object containing logMAR score to convert to ETDRS

Details

logMAR value converted to ETDRS as $ETDRS = -(\logMAR - 1.7) / 0.02$

Source for conversion formula: Beck, R.W., et al. A computerized method of visual acuity testing. American Journal of Ophthalmology, 135(2), pp.194-205. doi:[https://doi.org/10.1016/s0002-9394\(02\)01825-1](https://doi.org/10.1016/s0002-9394(02)01825-1).

Value

The input value converted to ETDRS units

Author(s)

Nandini R Thampi

Examples

```

library(tibble)
library(dplyr)
library(admiral)

oe <- tribble(
  ~STUDYID, ~USUBJID, ~OETESTCD, ~OEMETHOD, ~OESTRESN,
  "XXX001", "P01", "VACSCORE", "logMAR EYE CHART", 1.08,

```

```

"XXX001", "P02", "VACSCORE", "logMAR EYE CHART", 1.66,
"XXX001", "P03", "VACSCORE", "logMAR EYE CHART", 1.60,
"XXX001", "P04", "VACSCORE", "ETDRS EYE CHART", 57,
"XXX001", "P05", "VACSCORE", "ETDRS EYE CHART", 1
)

adbcva <- oe %>%
  filter(OETESTCD == "VACSCORE" & toupper(OEMETHOD) == "LOGMAR EYE CHART") %>%
  mutate(OESTRESN = convert_logmar_to_etdrs(OESTRESN))

```

derive_var_afeye *Derive Affected Eye*

Description

Derive Affected Eye (AFEYE) in occurrence datasets

Usage

```
derive_var_afeye(dataset, loc_var, lat_var, loc_vals = "EYE")
```

Arguments

dataset	Input dataset [Deprecated] Please use dataset instead.
loc_var	Location variable
lat_var	Laterality variable
loc_vals	xxLOC values for which AFEYE is derived [Deprecated] Please simply ensure xxLAT values are contained in c("LEFT", "RIGHT", "BILATERAL").

Details

Affected Eye is derived in the occurrence dataset using laterality and Study Eye. This assumes Study Eye has already been added from ADSL.

Value

The input occurrence dataset with Affected Eye (AFEYE) added.

Author(s)

Lucy Palmen

Examples

```

library(tibble)
library(admiral)

adae1 <- tribble(
  ~STUDYID, ~USUBJID, ~STUDYEYE, ~AELOC, ~AELAT,
  "XXX001", "P01", "RIGHT", "EYE", "RIGHT",
  "XXX001", "P01", "RIGHT", "EYE", "LEFT",
  "XXX001", "P01", "RIGHT", "EYE", "",
  "XXX001", "P01", "RIGHT", "", "RIGHT",
  "XXX001", "P02", "LEFT", "", "",
  "XXX001", "P02", "LEFT", "EYE", "LEFT",
  "XXX001", "P04", "BILATERAL", "EYE", "RIGHT",
  "XXX001", "P05", "RIGHT", "EYE", "RIGHT",
  "XXX001", "P05", "RIGHT", "EYE", "BILATERAL",
  "XXX001", "P06", "BILATERAL", "", "",
  "XXX001", "P06", "BILATERAL", "", "RIGHT",
  "XXX001", "P07", "BILATERAL", "EYE", "BILATERAL",
  "XXX001", "P08", "", "EYE", "BILATERAL",
  "XXX001", "P09", "NONSENSE", "EYE", "BILATERAL",
  "XXX001", "P09", "BILATERAL", "EYE", "NONSENSE",
  "XXX001", "P09", "BILATERAL", "NONSENSE", "BILATERAL",
  "XXX001", "P10", "RIGHT", "EYE", "BOTH"
)

derive_var_afeye(adae1, loc_var = AELOC, lat_var = AELAT)

adae2 <- tribble(
  ~STUDYID, ~USUBJID, ~STUDYEYE, ~AELOC, ~AELAT,
  "XXX001", "P01", "RIGHT", "EYES", "RIGHT",
  "XXX001", "P02", "RIGHT", "RETINA", "LEFT",
  "XXX001", "P03", "LEFT", "", ""
)

derive_var_afeye(adae2, loc_var = AELOC, lat_var = AELAT, loc_vals = c("EYES", "RETINA"))

```

```
derive_var_bcvacritxfl
```

Adds CRITx/CRITxFL pairs to BCVA dataset

Description

[Superseded] The `derive_var_bcvacritxfl()` function has been superseded in favor of `admiral::derive_vars_crit_fl`

Adds a criterion variables CRITx and their corresponding flags CRITxFL to a dataset containing BCVA records

Usage

```

derive_var_bcvacritxfl(
  dataset,
  crit_var,
  bcva_ranges = NULL,
  bcva_uplims = NULL,
  bcva_lowlims = NULL,
  additional_text = "",
  critxfl_index = NULL
)

```

Arguments

<code>dataset</code>	Input dataset containing BCVA data (usually ADBCVA).
<code>crit_var</code>	Variable with respect to which CRITx/CRITxFL are derived (usually CHG or AVAL).
<code>bcva_ranges</code>	List containing one or more numeric vectors of length 2. For each vector $c(a, b)$ in <code>bcva_ranges</code> , a pair of variables CRITx, CRITxFL is created with the condition: $a \leq \text{crit_var} \leq b$. If criterion flags of that type are not required, then leave as NULL.
<code>bcva_uplims</code>	List containing one or more numeric elements. For each element a in <code>bcva_uplims</code> , a pair of variables CRITx, CRITxFL is created with the condition: $\text{crit_var} \leq a$. If criterion flags of that type are not required, then leave as NULL.
<code>bcva_lowlims</code>	List containing one or more numeric elements. For each element b in <code>bcva_lowlims</code> , a pair of variables CRITx, CRITxFL is created with the condition: $\text{crit_var} \geq b$. If criterion flags of that type are not required, then leave as NULL.
<code>additional_text</code>	string containing additional text to append to CRITx
<code>critxfl_index</code>	positive integer detailing the first value of x to use in CRITxFL. If not supplied, the function takes the first available value of x , counting up from $x = 1$.

Details

This function works by calling `derive_var_bcvacritxfl()` once for each of the elements in `bcva_ranges`, `bcva_uplims` and `bcva_lowlims`. NOTE: if `crit_var` is equal to NA, then the resulting criterion flag is also marked as NA.

Value

The input BCVA dataset with additional column pairs CRITx, CRITxFL.

Author(s)

Edoardo Mancini

Examples

```

library(tibble)
library(admiral)
library(admiraldev)

adbcva1 <- tribble(
  ~STUDYID, ~USUBJID, ~AVISIT, ~BASETYPE, ~PARAMCD, ~CHG,
  "XXX001", "P01", "BASELINE", "LAST", "SBCVA", 0,
  "XXX001", "P01", "WEEK 2", "LAST", "FBCVA", 2,
  "XXX001", "P02", "BASELINE", "LAST", "SBCVA", -13,
  "XXX001", "P02", "WEEK 2", "LAST", "FBCVA", 5,
  "XXX001", "P03", "BASELINE", "LAST", "SBCVA", NA,
  "XXX001", "P03", "WEEK 2", "LAST", "FBCVA", 17
)

derive_var_bcvacritxfl(
  dataset = adbcva1,
  crit_var = exprs(CHG),
  bcva_ranges = list(c(0, 5), c(-5, -1), c(10, 15)),
  bcva_uplims = list(5, 10),
  bcva_lowlims = list(8),
  additional_text = ""
)

adbcva2 <- tribble(
  ~STUDYID, ~USUBJID, ~AVISIT, ~BASETYPE, ~PARAMCD, ~AVAL, ~CHG,
  "XXX001", "P01", "BASELINE", "LAST", "SBCVA", 4, NA,
  "XXX001", "P01", "BASELINE", "LAST", "SBCVA", 6, NA,
  "XXX001", "P01", "AVERAGE BASELINE", "AVERAGE", "SBCVA", 5, NA,
  "XXX001", "P01", "WEEK 2", "LAST", "SBCVA", -3, NA,
  "XXX001", "P01", "WEEK 4", "LAST", "SBCVA", -10, NA,
  "XXX001", "P01", "WEEK 6", "LAST", "SBCVA", 12, NA,
  "XXX001", "P01", "WEEK 2", "AVERAGE", "SBCVA", -2, -7,
  "XXX001", "P01", "WEEK 4", "AVERAGE", "SBCVA", 6, 1,
  "XXX001", "P01", "WEEK 6", "AVERAGE", "SBCVA", 3, -2
)

restrict_derivation(
  adbcva2,
  derivation = derive_var_bcvacritxfl,
  args = params(
    crit_var = exprs(CHG),
    bcva_ranges = list(c(0, 5), c(-10, 0)),
    bcva_lowlims = list(5),
    additional_text = " (AVERAGE)"
  ),
  filter = PARAMCD %in% c("SBCVA", "FBCVA") & BASETYPE == "AVERAGE"
)

```

derive_var_studyeye *Derive Study Eye*

Description

Derive Study Eye (STUDYEYE) in the ADSL dataset

Usage

```
derive_var_studyeye(dataset_adsl, dataset_sc, sctestcd_value = "FOCID")
```

Arguments

dataset_adsl ADSL input dataset
dataset_sc SC input dataset
sctestcd_value SCTESTCD value flagging Study Eye selection records. Default: "FOCID".

Details

Study Eye is derived in ADSL using the "Study Eye selection" records in the SC SDTM dataset.

Value

The input ADSL dataset with an additional column named STUDYEYE

Author(s)

Edoardo Mancini

Examples

```
library(tibble)
library(admiral)

adsl <- tribble(
  ~STUDYID, ~USUBJID,
  "XXX001", "P01",
  "XXX001", "P02",
  "XXX001", "P03",
  "XXX001", "P04",
  "XXX001", "P05"
)

sc <- tribble(
  ~STUDYID, ~USUBJID, ~SCTESTCD, ~SCSTRESC,
  "XXX001", "P01", "FOCID", "OS",
  "XXX001", "P01", "ACOHORT", "COHORT1",
  "XXX001", "P02", "FOCID", "OD",
  "XXX001", "P02", "ACOHORT", "COHORT3",
```

derive_var_studyeye

11

```
    "XXX001", "P04", "FOCID", "OU",  
    "XXX001", "P05", "FOCID", "OD",  
    "XXX001", "P06", "FOCID", "OS"  
  )  
  
  derive_var_studyeye(adsl, sc)
```

Index

* **datasets**

admiralophtha_adbcva, 2
admiralophtha_adoe, 3
admiralophtha_advfq, 3

* **der_adsl**

derive_var_studyeye, 10

* **der_occds**

derive_var_afeye, 6

* **der_ophtha**

derive_var_bcvacritxfl, 7

* **superseded**

derive_var_bcvacritxfl, 7

* **utils_fmt**

convert_etdrs_to_logmar, 4
convert_logmar_to_etdrs, 5

admiralophtha_adbcva, 2, 3, 4

admiralophtha_adoe, 3, 3, 4

admiralophtha_advfq, 3, 3

convert_etdrs_to_logmar, 4

convert_logmar_to_etdrs, 5

derive_var_afeye, 6

derive_var_bcvacritxfl, 7

derive_var_studyeye, 10