

ICESat-2 Mission Orbits

This *first* vignette demonstrates how to download and process *time specific orbits*. We'll use one of the *Reference Ground Track (RGT) cycles* and merge it with other data sources with the purpose to visualize specific areas.

We'll load one of the latest which is “*RGT_cycle_14*” (from *December 22, 2021* to *March 23, 2022*). The documentation of the “*RGT_cycle_14*” data includes more details on how a user can come to the same data format for any of the RGT Cycles.

```
pkgs = c('IceSat2R', 'magrittr', 'mapview', 'sf', 'rnaturalearth',
         'data.table', 'DT', 'stargazer')
load_pkgs = lapply(pkgs, require, character.only = TRUE) # load required R packages

sf::sf_use_s2(use_s2 = FALSE) # disable 's2' in this vignette
mapview::mapviewOptions(leafletHeight = '600px',
                        leafletWidth = '700px') # applies to all leaflet maps

#.....
# load the 'RGT_cycle_14' data
#.....

data(RGT_cycle_14)

res_rgt_many = sf::st_as_sf(x = RGT_cycle_14, coords = c('longitude', 'latitude'), crs = 4326)
res_rgt_many

## Simple feature collection with 131765 features and 6 fields
## Geometry type: POINT
## Dimension: XY
## Bounding box: xmin: -179.9986 ymin: -87.66742 xmax: 179.9984 ymax: 87.3305
## Geodetic CRS: WGS 84
## First 10 features:
##   day_of_year   Date hour minute second RGT geometry
## 1         356 2021-12-22    7     57    49 1 POINT (-0.1318472 0.02795893)
## 2         356 2021-12-22    7     58    49 1 POINT (-0.5162124 3.868758)
## 3         356 2021-12-22    7     59    49 1 POINT (-0.901809 7.709809)
## 4         356 2021-12-22    8      0    49 1 POINT (-1.289879 11.55065)
## 5         356 2021-12-22    8      1    49 1 POINT (-1.681755 15.39082)
## 6         356 2021-12-22    8      2    49 1 POINT (-2.078916 19.2299)
## 7         356 2021-12-22    8      3    49 1 POINT (-2.483051 23.06748)
## 8         356 2021-12-22    8      4    49 1 POINT (-2.896146 26.90316)
## 9         356 2021-12-22    8      5    49 1 POINT (-3.3206 30.73662)
## 10        356 2021-12-22    8      6    49 1 POINT (-3.759374 34.56754)
```

ICESat-2 and Countries intersection

We'll proceed to merge the orbit geometry points with the countries data of the *rnaturalearth* R package (1:110 million scales) and for this purpose, we keep only the “*sovereight*” and “*sov_a3*” columns,

```

cntr = rnaturalearth::ne_countries(scale = 110, type = 'countries', returnclass = 'sf')
cntr = cntr[, c('sovereight', 'sov_a3')]
cntr

```

```

## Simple feature collection with 177 features and 2 fields
## Geometry type: MULTIPOLYGON
## Dimension: XY
## Bounding box: xmin: -180 ymin: -90 xmax: 180 ymax: 83.64513
## Geodetic CRS: WGS 84
## First 10 features:
##      sovereignty sov_a3 geometry
## 1          Fiji    FJI MULTIPOLYGON (((180 -16.067...
## 2 United Republic of Tanzania TZA MULTIPOLYGON (((33.90371 -0...
## 3      Western Sahara    SAH MULTIPOLYGON (((-8.66559 27...
## 4           Canada    CAN MULTIPOLYGON (((-122.84 49,...
## 5 United States of America    US1 MULTIPOLYGON (((-122.84 49,...
## 6      Kazakhstan    KA1 MULTIPOLYGON (((87.35997 49...
## 7      Uzbekistan    UZB MULTIPOLYGON (((55.96819 41...
## 8 Papua New Guinea    PNG MULTIPOLYGON (((141.0002 -2...
## 9      Indonesia    IDN MULTIPOLYGON (((141.0002 -2...
## 10     Argentina    ARG MULTIPOLYGON (((-68.63401 -...

```

We then merge the orbit points with the country geometries and specify also “*left = TRUE*” to keep also observations that do not intersect with the *rnaturalearth* countries data,

```

dat_both = suppressMessages(sf::st_join(x = res_rgt_many,
                                       y = cntr,
                                       join = sf::st_intersects,
                                       left = TRUE))
dat_both

```

```

## Simple feature collection with 131765 features and 8 fields
## Geometry type: POINT
## Dimension: XY
## Bounding box: xmin: -179.9986 ymin: -87.66742 xmax: 179.9984 ymax: 87.3305
## Geodetic CRS: WGS 84
## First 10 features:
##   day_of_year      Date hour minute second RGT  sovereignty sov_a3
## 1         356 2021-12-22    7     57    49    1      <NA>    <NA>
## 2         356 2021-12-22    7     58    49    1      <NA>    <NA>
## 3         356 2021-12-22    7     59    49    1      Ghana    GHA
## 4         356 2021-12-22    8      0    49    1 Burkina Faso BFA
## 5         356 2021-12-22    8      1    49    1      Mali    MLI
## 6         356 2021-12-22    8      2    49    1      Mali    MLI
## 7         356 2021-12-22    8      3    49    1      Mali    MLI
## 8         356 2021-12-22    8      4    49    1      Algeria DZA
## 9         356 2021-12-22    8      5    49    1      Algeria DZA
## 10        356 2021-12-22    8      6    49    1      Morocco MAR
##           geometry
## 1 POINT (-0.1318472 0.02795893)
## 2 POINT (-0.5162124 3.868758)
## 3 POINT (-0.901809 7.709809)
## 4 POINT (-1.289879 11.55065)
## 5 POINT (-1.681755 15.39082)
## 6 POINT (-2.078916 19.2299)

```

```
## 7 POINT (-2.483051 23.06748)
## 8 POINT (-2.896146 26.90316)
## 9 POINT (-3.3206 30.73662)
## 10 POINT (-3.759374 34.56754)
```

The unique number of RGT's for “*RGT_cycle_14*” are

```
length(unique(dat_both$RGT))
```

```
## [1] 1387
```

We observe that from *December 22, 2021* to *March 23, 2022*,

```
df_tbl = data.frame(table(dat_both$sovereignt), stringsAsFactors = F)
colnames(df_tbl) = c('country', 'Num_IceSat2_points')
```

```
df_subs = dat_both[, c('RGT', 'sovereignt')]
df_subs$geometry = NULL
df_subs = data.table::data.table(df_subs, stringsAsFactors = F)
colnames(df_subs) = c('RGT', 'country')
df_subs = split(df_subs, by = 'country')
df_subs = lapply(df_subs, function(x) {
  unq_rgt = sort(unique(x$RGT))
  items = ifelse(length(unq_rgt) < 5, length(unq_rgt), 5)
  concat = paste(unq_rgt[1:items], collapse = '-')
  iter_dat = data.table::setDT(list(country = unique(x$country),
                                   Num_RGTs = length(unq_rgt),
                                   first_5_RGTs = concat))

  iter_dat
})
```

```
df_subs = data.table::rbindlist(df_subs)
```

```
df_tbl = merge(df_tbl, df_subs, by = 'country')
df_tbl = df_tbl[order(df_tbl$Num_IceSat2_points, decreasing = T), ]
```

```
DT_dtbl = DT::datatable(df_tbl, rownames = FALSE)
```

all RGT's (1387 in number) intersect with “*Antarctica*” and almost all with “*Russia*”.

‘Onshore’ and ‘Offshore’ Points ICESat-2 coverage

The **onshore** and **offshore** number of ICESat-2 points and percentages for the “*RGT_cycle_14*” equal to

```
num_sea = sum(is.na(dat_both$sovereignt))
num_land = sum(!is.na(dat_both$sovereignt))
```

```
perc_sea = round(num_sea / nrow(dat_both), digits = 4) * 100.0
perc_land = round(num_land / nrow(dat_both), digits = 4) * 100.0
```

```
dtbl_land_sea = data.frame(list(percentage = c(perc_sea, perc_land),
                               Num_Icesat2_points = c(num_sea, num_land)))
```

```
row.names(dtbl_land_sea) = c('sea', 'land')
```

```
stargazer::stargazer(dtbl_land_sea,
                     summary = FALSE,
                     rownames = TRUE,
```

```
header = FALSE,
float = FALSE,
table.placement = '!h',
title = 'Land and Sea Proportions')
```

	percentage	Num_Icesat2_points
sea	67.070	88,369
land	32.930	43,396

Global glaciated areas and ICESat-2 coverage

We can also observe the ICESat-2 “*RGT_cycle_14*” coverage based on the 1 to 10 million large scale [Natural Earth Glaciated Areas](#) data,

```
data(ne_10m_glaciated_areas)
```

We’ll restrict the processing to the major polar glaciers (that have a name included),

```
ne_obj_subs = subset(ne_10m_glaciated_areas, !is.na(name))
ne_obj_subs = sf::st_make_valid(x = ne_obj_subs) # check validity of geometries
ne_obj_subs
```

```
## Simple feature collection with 68 features and 5 fields
## Geometry type: POLYGON
## Dimension: XY
## Bounding box: xmin: -180 ymin: -89.99993 xmax: 180 ymax: 82.96573
## Geodetic CRS: WGS 84
## First 10 features:
##   recnum scalerank   featurecla      name min_zoom
## 143     143         3 Glaciated areas  Mount Brown Icefield      2.1
## 148     148         5 Glaciated areas  Braithwaite Icefield      5.0
## 152     152         3 Glaciated areas    Hooker Icefield      2.1
## 206     206         5 Glaciated areas  Homathko Icefield      5.0
## 214     214         6 Glaciated areas Clachnacudainn Icefield  5.7
## 215     215         6 Glaciated areas    Albert Icefield      5.7
## 228     228         3 Glaciated areas    Plateau Icefield      2.1
## 230     230         5 Glaciated areas  Pemberton Icefield      5.0
## 256     256         3 Glaciated areas    Cambria Icefield      2.1
## 273         0         3 Glaciated areas    Lyell Icefield      2.1
##           geometry
## 143 POLYGON ((-118.4066 52.7965...
## 148 POLYGON ((-119.9303 52.6144...
## 152 POLYGON ((-117.8572 52.5404...
## 206 POLYGON ((-124.6489 51.3257...
## 214 POLYGON ((-118.0284 51.1342...
## 215 POLYGON ((-117.6752 51.0917...
## 228 POLYGON ((-123.8453 50.5810...
## 230 POLYGON ((-123.3869 50.5279...
## 256 POLYGON ((-129.661 56.09113...
## 273 POLYGON ((-117.2649 52.0351...
##           geometry
```

and we’ll visualize the subset using the *mapview* package,

```
mpv = mapview::mapview(ne_obj_subs,
                        color = 'cyan',
```

```

col.regions = 'blue',
alpha.regions = 0.5,
legend = FALSE)
mpv

```

We will see which orbits of the ICESat-2 “RGT_cycle_14” intersect with these major polar glaciers,

```

res_rgt_many$id_rgt = 1:nrow(res_rgt_many)      # include 'id' for fast subsetting

dat_glac_sf = suppressMessages(sf::st_join(x = ne_obj_subs,
                                           y = res_rgt_many,
                                           join = sf::st_intersects))

dat_glac = data.table::data.table(sf::st_drop_geometry(dat_glac_sf), stringsAsFactors = F)
dat_glac = dat_glac[complete.cases(dat_glac), ] # keep non-NA observations
dat_glac

```

```

##      recnum scalerank   featurecla      name min_zoom day_of_year
##      <num>   <num>      <char>      <char>   <num>   <int>
##  1:    952         4 Glaciated areas Jostedalbreen     3.0     40
##  2:   1696         3 Glaciated areas Agassiz Ice Cap     2.1    357
##  3:   1696         3 Glaciated areas Agassiz Ice Cap     2.1    358
##  4:   1696         3 Glaciated areas Agassiz Ice Cap     2.1    361
##  5:   1696         3 Glaciated areas Agassiz Ice Cap     2.1    362
##  ---
## 13245:     0         3 Glaciated areas Kluane Ice Cap     2.1     42
## 13246:     0         3 Glaciated areas Kluane Ice Cap     2.1     44
## 13247:     0         3 Glaciated areas Kluane Ice Cap     2.1     48
## 13248:     0         3 Glaciated areas Kluane Ice Cap     2.1     71
## 13249:     0         3 Glaciated areas Kluane Ice Cap     2.1     73
##
##      Date hour minute second  RGT id_rgt
##      <Date> <int> <int> <num> <int> <int>
##  1: 2022-02-09  17    23    15   755  71662
##  2: 2021-12-23   1    41     0    12  1072
##  3: 2021-12-24  12    10    22   34  3157
##  4: 2021-12-27   1    32    40   73  6867
##  5: 2021-12-28  12     2     3   95  8952
##  ---
## 13245: 2022-02-11  14    42    39   784  74402
## 13246: 2022-02-13   3     6    19   807  76602
## 13247: 2022-02-17   2    57    59   868  82397
## 13248: 2022-03-12  13    18    42  1226 116392
## 13249: 2022-03-14   1    42    22  1249 118592

```

We’ll split the merged data by the ‘name’ of the glacier,

```

dat_glac_name = split(x = dat_glac, by = 'name')

sum_stats_glac = lapply(dat_glac_name, function(x) {

  dtbl_glac = x[, .(name_glacier = unique(name),
                  Num_unique_Dates = length(unique(Date)),
                  Num_unique_RGTs = length(unique(RGT)))]

  dtbl_glac
})

```

```
sum_stats_glac = data.table::rbindlist(sum_stats_glac)
sum_stats_glac = sum_stats_glac[order(sum_stats_glac$Num_unique_RGTs, decreasing = T), ]
```

The next table shows the total number of days and RGTs for each one of the major polar glaciers,

```
stargazer::stargazer(sum_stats_glac,
  summary = FALSE,
  rownames = FALSE,
  header = FALSE,
  float = FALSE,
  table.placement = 'h',
  title = 'Days and RGTs')
```

name_glacier	Num_unique_Dates	Num_unique_RGTs
Antarctic Ice Sheet	92	1,387
Greenland Ice Sheet	91	352
Agassiz Ice Cap	56	58
Academy of Sciences Ice Cap	34	34
Manson Icefield	14	19
Müller Ice Cap	16	16
Kluane Ice Cap	12	12
Sydkap Ice Cap	6	7
Southern Patagonian Ice Field	5	5
Stikine Icecap	4	4
Vestfonna	3	3
Brasvellbreen	3	3
Northern Patagonian Ice Field	2	2
Jostedalsbreen	1	1

We can restrict to one of the glaciers to visualize the ICESat-2 “RGT_cycle_14” coverage over this specific area (*Southern Patagonian Ice Field*),

```
sample_glacier = 'Southern Patagonian Ice Field'
dat_glac_smpl = dat_glac_name[[sample_glacier]]
```

```
cols_display = c('name', 'day_of_year', 'Date', 'hour', 'minute', 'second', 'RGT')
```

```
stargazer::stargazer(dat_glac_smpl[, ..cols_display],
  summary = FALSE,
  rownames = FALSE,
  header = FALSE,
  float = FALSE,
  table.placement = 'h',
  title = 'Southern Patagonian Ice Field')
```

name	day_of_year	Date	hour	minute	second	RGT
Southern Patagonian Ice Field	357	2021-12-23	0	40	43	11
Southern Patagonian Ice Field	2	2022-01-02	12	28	4	171
Southern Patagonian Ice Field	20	2022-01-20	23	16	46	453
Southern Patagonian Ice Field	49	2022-02-18	21	52	48	895
Southern Patagonian Ice Field	64	2022-03-05	9	31	50	1,116

and we gather the intersected RGT coordinates points with the selected glacier,

```

subs_rgts = subset(res_rgt_many, id_rgt %in% dat_glac_smpl$id_rgt)

set.seed(1)
samp_colrs = sample(x = grDevices::colors(distinct = TRUE),
                    size = nrow(subs_rgts))
subs_rgts$color = samp_colrs

ne_obj_subs_smpl = subset(ne_obj_subs, name == sample_glacier)

mpv_glacier = mapview::mapview(ne_obj_subs_smpl,
                               color = 'cyan',
                               col.regions = 'blue',
                               alpha.regions = 0.5,
                               legend = FALSE)

mpv_RGTs = mapview::mapview(subs_rgts,
                             color = subs_rgts$color,
                             alpha.regions = 0.0,
                             lwd = 6,
                             legend = FALSE)

```

and visualize both the glacier and the subset of the intersected RGT coordinate points (of the different Days) in the same map. The clickable map and point popups include more information,

```

lft = mpv_glacier + mpv_RGTs
lft

```