

# Package ‘MandalaR’

November 2, 2022

**Type** Package

**Title** Building Mandalas from Parametric Equations of Classical Curves

**Version** 0.1.0

**Author** Luciane Ferreira Alcoforado

**Maintainer** Luciane Ferreira Alcoforado <luciana@id.uff.br>

**Description** Provides an algorithm for creating mandalas. From the perspective of classic mathematical curves and rigid movements on the plane, the package allows you to select curves and produce mandalas from the curve. The algorithm was developed based on the book by Alcoforado et. al. entitled “Art, Geometry and Mandalas with R” (2022) in press by the USP Open Books Portal.

**Depends** R (>= 3.2)

**Imports** ggplot2

**License** GPL-3

**URL** <https://lucianealcoforado.shinyapps.io/Mandala/>

**Encoding** UTF-8

**RoxygenNote** 7.2.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-11-02 19:42:41 UTC

## R topics documented:

f_factor	2
f_rotacao	3
f_trans	3
f_transxy	4
mandalar_basic	5
pastroide	6
pcardioide	7
pcircle	7
pdeltoide	8

pelipse . . . . .	9
pespiral1 . . . . .	10
pespiral2 . . . . .	10
plemniscata . . . . .	11
plimacon . . . . .	12
plot_mandala . . . . .	13

<b>Index</b>	<b>14</b>
--------------	-----------

---

f_factor	<i>Mandalar: package for building mandalas from parametric equations of classical curves</i>
----------	--

---

### Description

Function to reduce points

### Usage

```
f_factor(x, y, k)
```

### Arguments

x	is a vector length n with coordinate x of point
y	is a vector length n with coordinate y of point
k	is a vector with factor of decrease or increase points

### Value

Returns a dataframe with the original points plus the respective changed points.

### Examples

```
x=c(1,1)
y=c(0,1)
k=c(0.5)
f_factor(x,y,k)
```

---

f_rotacao	<i>Mandalas: package for building mandalas from parametric equations of classical curves</i>
-----------	--

---

**Description**

Function to rotate points by one or more angles

**Usage**

```
f_rotacao(x, y, rotacao)
```

**Arguments**

x	is a vector length n with coordinate x of point
y	is a vector length n with coordinate y of point
rotacao	is a vector of length k with angles in radians to rotate the point (x,y)

**Details**

If x and y dimension is n and rotation dimension is k, then function f\_rotacao will return a dataframe with two columns and (n+1)k rows

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Examples**

```
x=c(1,1)
y=c(0,1)
rotacao=c(pi/3, pi/2, pi)
f_rotacao(x,y,rotacao)
```

---

f_trans	<i>creates a dataframe containing the points for the espiral hiperbolica mandala</i>
---------	--

---

**Description**

Function to translation points by shifts on the x-axis or y-axis

**Usage**

```
f_trans(x, y, t, d)
```

**Arguments**

x	is a vector length n with coordinate x of point
y	is a vector length n with coordinate y of point
t	is a vector with shifts on the x or y-axis
d	is a direction translation, 1)x or 2)y

**Value**

Returns a dataframe with the original points plus the respective translation of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
x=c(1,1)
y=c(0,1)
t=c(-3, 3)
d=1
f_trans(x,y,t,d)
```

---

f_transxy	<i>creates a dataframe containing the points for the espiral hiperbolica mandala</i>
-----------	--

---

**Description**

Function to translation points by shifts on the x-axis or y-axis or both

**Usage**

```
f_transxy(x, y, tx, ty)
```

**Arguments**

x	is a vector length n with coordinate x of point
y	is a vector length n with coordinate y of point
tx	is a vector with with shifts on the x-axis
ty	is a vector with with shifts on the y-axis

**Value**

Returns a dataframe with the original points plus the respective translation of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
x=c(1,1)
y=c(0,1)
tx=c(-1,-2)
ty=c(0,0)
f_transxy(x,y,tx,ty)
```

---

mandalar\_basic

*Create a mandala with algorithm basic*

---

**Description**

Function to create a mandala with the basic method

**Usage**

```
mandalar_basic(curve, theta, k, n, raio, a, b)
```

**Arguments**

curve	Either a character string or a function returning curve equation evaluated at its first argument. Curves "circle", "elipse", "cardioide", "limacon", "espiral1", "espiral2", "lemniscata", "deltoide" and "astroide" are recognised, case being ignored.
theta	is a vector length 2 with start angle and end angle
k	is a angle of rotations, k in (0,360) graus
n	is a number of points
raio	is a positive number for the radius of circle
a	is one of the parameters of the curves; for the ellipse is the radius on the x axis
b	is one of the parameters of the curves; for the ellipse is the radius on the y axis

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
require(ggplot2)
mandalar_basic("circle", theta = c(0,2*pi), raio=1, k = 45, n=500)
mandalar_basic("cardioide", theta = c(0,2*pi), raio=1, k = 60, n=500)
mandalar_basic("elipse", theta = c(0,2*pi), a=1, b=2, k = 30, n=500)
```

---

pastroide	<i>creates a dataframe containing the points for the astroide mandala</i>
-----------	---

---

**Description**

Function to build a astroide

**Usage**

```
pastroide(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value. For astroide we do r=3.
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi)
k=45
raio = 1
n=20
pastroide(theta, raio, k, n)
```

---

pcardioide                      *creates a dataframe containing the points for the cardioide mandala*

---

**Description**

Function to build a cardioide

**Usage**

```
pcardioide(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi)
k=45
raio = 1
n=20
pcardioide(theta, raio, k, n)
```

---

pcircle                      *creates a dataframe containing the points for the circle mandala*

---

**Description**

Function to build point for the circle base

**Usage**

```
pcircle(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi) #half turn angle
raio = 1
k = 45
n=20
pcircle(theta, raio, k, n)
```

---

pdeltoide

*creates a dataframe containing the points for the deltoide mandala*

---

**Description**

Function to build a deltoide

**Usage**

```
pdeltoide(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value. For deltoide we do r=2.
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.



**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi)
k=45
raio = 1
n=20
pdeltoide(theta, raio, k, n)
```

---

pelipse *creates a dataframe containing the points for the ellipse mandala*

---

**Description**

Function to build point for the ellipse base

**Usage**

```
pelipse(theta, a, b, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
a	is one of the parameters of the curves; for the ellipse is the radius on the x axis
b	is one of the parameters of the curves; for the ellipse is the radius on the y axis
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi) #half turn angle
a = 1
b=2
k = 90
n=20
pelipse(theta, a, b, k, n)
```

---

pespiral1	<i>creates a dataframe containing the points for the Fermat spiral mandala</i>
-----------	--

---

**Description**

Function to build a espiral de Fermat

**Usage**

```
pespiral1(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,6*pi)
k=45
raio = 1
n=20
pespiral1(theta, raio, k, n)
```

---

pespiral2	<i>creates a dataframe containing the points for the espiral hiperbolica mandala</i>
-----------	--

---

**Description**

Function to build a espiral hiperbolica

**Usage**

```
pespiral2(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,6*pi)
k=45
raio = 1
n=20
pespiral2(theta, raio, k, n)
```

---

plemniscata                      *creates a dataframe containing the points for the lemniscata mandala*

---

**Description**

Function to build a lemniscata

**Usage**

```
plemniscata(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi)
k=45
raio = 1
n=20
pllemniscata(theta, raio, k, n)
```

---

plimacon

*creates a dataframe containing the points for the limacon mandala*

---

**Description**

Function to build a limacon

**Usage**

```
plimacon(theta, raio, k, n)
```

**Arguments**

theta	is a vector length 2 with start angle and end angle
raio	is a vector length 1 with radius value
k	is a vector of length 1 with angles in degree to rotate the point (x,y)
n	is a number of points

**Value**

Returns a dataframe with the original points plus the respective rotations of these points.

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
theta = c(0,2*pi)
k=45
raio = 1
n=20
plimacon(theta, raio, k, n)
```

---

plot_mandala	<i>creates a mandala visualization</i>
--------------	--

---

**Description**

Function to plot a mandala with points in dataframe

**Arguments**

dt                      dataframe with points x and y

**Value**

Returns a plot

**Author(s)**

Luciane Ferreira Alcoforado

**Examples**

```
require(ggplot2)
n=500; raio=1; t=seq(0,2*pi, length.out = n)
x1=raio*cos(t)
y1=raio*sin(t)
#pontos para os 3 círculos: translação dos pontos iniciais (x1,x=c(x1,x1-raio,x1-2*raio)
x=c(x1,x1-raio,x1-2*raio)
y=c(y1,y1,y1)
dt=data.frame(x,y,z="circulo")
rotacao = (pi/8)*(1:16); n=length(x); xt1=x; yt1=y
dt=f_rotacao(x=dt$x, y=dt$y, rotacao)
plot_mandala(dt)
```

# Index

f\_factor, 2  
f\_rotacao, 3  
f\_trans, 3  
f\_transxy, 4  
  
mandalar\_basic, 5  
  
pastroide, 6  
pcardioide, 7  
pcircle, 7  
pdeltoide, 8  
pelipse, 9  
pespiral1, 10  
pespiral2, 10  
plemniscata, 11  
plimacon, 12  
plot\_mandala, 13