

Package ‘go2bigq’

August 29, 2023

Type Package

Title Convert Large Numbers to Bigq Format

Version 2.0.1

Date 2023-08-28

Description This function converts mfpr, numeric, or character strings representing numbers to bigq format without loss of precision.

License LGPL-3

Imports Rmpfr, gmp, methods

NeedsCompilation no

Author Carl Witthoft [aut, cre]

Maintainer Carl Witthoft <cellocgw@gmail.com>

Repository CRAN

Date/Publication 2023-08-29 18:10:11 UTC

R topics documented:

go2bigq-package	1
go2bigq	2

Index	4
--------------	----------

go2bigq-package	<i>Convert Large Numbers to Bigq Format</i>
-----------------	---

Description

This function converts mfpr, numeric, or character strings representing numbers to bigq format without loss of precision.

Details

Package: go2bigq
 Type: Package
 Version: 2.0
 Date: 2022-06-02
 License: GPL-3

Author(s)

Carl Witthoft

Maintainer: Carl Witthoft carl@witthoft.com

go2bigq

Function to convert various numerics to bigq with full precision.

Description

Convert a numeric, a character string representing a numeric, or various mpfr classes to a bigq fraction. The output has the same precision as the input.

Usage

```
go2bigq(x, ...)
```

Arguments

x	A value of class numeric, mpfr, mpfr1, or character. A list containing any one of these classes is allowed. See Details for various limitations
...	Parameters which could be used to modify the default behavior of formatMpfr. See Details for more information.

Details

The input `x`, if a list, must contain only one of the allowed classes. Character strings which represent numbers must be of the form `[+,-]X[.]Y[e,E[+,-]Z]`, where `X`, `Y`, and `Z` are strictly limited to the numerals `[0:9]`. None of the other character options listed are required (except of course `"[+,-]Z"` is disallowed unless `"[e,E]"` exists.) The function `formatMpfr` accepts several arguments to adjust the output character string (number of digits precision, e.g.). `go2bigq` passes the `...` objects to `formatMpfr`.

Value

A bigq object containing a vector of bigq fractions .

Author(s)

Carl Witthoft, <carl@witthoft.com>

See Also

[.bigq2mpfr](#), [.bigz2mpfr](#), [as.bigq](#)

Examples

```
library(Rmpfr)
(go2bigq(0.17 + 1:5))
(go2bigq(as.character(0.17 + 1:5)))
(go2bigq(mpfr(0.17 + 1:5, 100)))
as.numeric(go2bigq('017.3200e-10')[1] - go2bigq(0017.3200e-10)[1])
```

Index

`.bigq2mpfr`, [3](#)

`.bigz2mpfr`, [3](#)

`as.bigq`, [3](#)

`formatMpfr`, [2](#)

`go2bigq`, [2](#)

`go2bigq-package`, [1](#)