The **ddphonism** package[*]

Celia Rubio Madrigal[†]

September 1, 2019

Abstract

This is a music-related package focused on notation from the Twelve-Tone System, also called Dodecaphonism. It provides LaTeX algorithms that produce typical dodecaphonic diagrams based off a musical series, or row sequence, of variable length.

Keywords

twelve tone system, dodecaphonism, music, mathematics, matrix, row, series, permutation, diagram, clock diagram, notation, algorithm, schoenberg, contemporary music, 20th century

Contents

1   Introduction

There are hundreds of music tools and software online which are able to produce different music notations. However, I have never seen a LaTeX tool that can do the same. This package is not only about notation, but it also calculates mathematically how this notation should work.

It is said that a twelve-tone matrix is the only thing a twelve-tone composer should need, because it provides the whole serial spectrum with which they may work. I wanted LaTeX users to be able to generate them automatically.

But I also think that a twelve-tone matrix is not enough, that there exist several other notations with which they may understand their series and their potential. These are the diagrams that can be obtained with this package:

---

[*]This document corresponds to **ddphonism** v0.2, dated 2019/09/01.

[†]Email: `celrubio@ucm.es`

1

$$\begin{array}{ccccc}
4 & 3 & 2 & 1 & 0 \\
0 & 4 & 3 & 2 & 1 \\
1 & 0 & 4 & 3 & 2 \\
2 & 1 & 0 & 4 & 3 \\
3 & 2 & 1 & 0 & 4
\end{array}$$

$$\begin{pmatrix}
0 & 1 & 2 & 3 & 4 \\
4 & 3 & 2 & 1 & 0
\end{pmatrix}$$

2   Using the **ddphonism** package

These are the commands provided by ddphonism. The main parameter in every command is the row sequence.

\dmatrix   produces a twelve-tone matrix of arbitrary length, as shown in this website. For example, `\dmatrix{0,2,1,4,3,6,5}` produces the matrix

$$\begin{array}{ccccccc}
0 & 2 & 1 & 4 & 3 & 6 & 5 \\
5 & 0 & 6 & 2 & 1 & 4 & 3 \\
6 & 1 & 0 & 3 & 2 & 5 & 4 \\
3 & 5 & 4 & 0 & 6 & 2 & 1 \\
4 & 6 & 5 & 1 & 0 & 3 & 2 \\
1 & 3 & 2 & 5 & 4 & 0 & 6 \\
2 & 4 & 3 & 6 & 5 & 1 & 0
\end{array}$$

|	
sep	scales the matrix.
vsep	scales the matrix vertically.
hsep	scales the matrix horizontally.
lines	draws lines between rows and columns.
outside lines	only draws the outside lines.

| inside lines | only draws the inside lines. |

| vlines | only draws the vertical lines. |

| hlines | only draws the horizontal lines. |

`\dmatrix[lines,sep=0.75]{0,2,1,4,3,6,5}` produces the matrix

| 0	2	1	4	3	6	5
5	0	6	2	1	4	3
6	1	0	3	2	5	4
3	5	4	0	6	2	1
4	6	5	1	0	3	2
1	3	2	5	4	0	6
2	4	3	6	5	1	0

| no tikz | deletes the tikz environment and lets the user write it instead. |

`\ddiagram`   produces a twelve tone clock diagram of arbitrary length, as shown in this website. For example, `\ddiagram{0,2,1,4,3,6,5}` produces the diagram

| name | writes a name at the center of the diagram. |

| up | lets the user choose which number is up north. The default value is the first number in the row. |

| arrow shift | lets the user choose where the arrow should fall on the line. The values range from 0 to 10. The default value is 2.5. |

`\ddiagram[name=P, up=5, arrow shift=5]{0,2,1,4,3,6,5}` produces the diagram

| no numbers | deletes the numbers around the diagram. |

| no arrow | deletes the arrow inside the diagram. |

`\ddiagram[no numbers, no arrow]{0,2,1,4,3,6,5}` produces the diagram

Figure: diagram produced by the command (geometric line drawing)

xshift   shifts the figure horizontally.

yshift   shifts the figure vertically.

no tikz   deletes the tikz environment and lets the user write it instead. The option up does not work anymore and the up position becomes 0. It is recommended that the user passes the option ddiagram to the environment:

```
\begin{tikzpicture}[ddiagram]
\ddiagram[no tikz]{0,2,1,4,3,6,5}
\end{tikzpicture}
```

produces the same diagram as `\ddiagram{0,2,1,4,3,6,5}`.

`\ddihedral`   produces a dihedral representation of a series of arbitrary length. For example, `\ddihedral{0,2,1,4,3,6,5}` produces the diagram

Figure: dihedral diagram with nodes 0, 1, 2, 3, 4, 5, 6 and T^0

t   applies the transformation *transposition* to the diagram.

s   applies the transformation *inversion* to the diagram.

c   applies the transformation *cyclic shift* to the diagram.

v   applies the transformation *retrograde* to the diagram.

The transformations are applied in that exact order.

`\ddihedral[s=1, c=4]{0,2,1,4,3,6,5}` produces the diagram

no italics	removes the italics from the diagram name.
new t	renames the transformation *transposition*.
new s	renames the transformation *inversion*.
new c	renames the transformation *cyclic shift*.
new v	renames the transformation *retrograde*.

`\ddihedral[no italics, new v=R, v=1]{0,2,1,4,3,6,5}` produces the diagram

no tikz   deletes the tikz environment and lets the user write it instead. It is recommended that the user passes the option ddihedral to the environment:

```
\begin{tikzpicture}[ddihedral]
\ddihedral[no tikz]{0,2,1,4,3,6,5}
\end{tikzpicture}
```

produces the same diagram as `\ddihedral{0,2,1,4,3,6,5}`.

`\darrows`   produces the arrows from the `\ddihedral` diagram. For example, `\darrows{0,2,1,4,3,6,5}` produces the arrows

     no tikz   deletes the tikz environment and lets the user write it instead.

`\drow`   produces a twelve-tone row sequence as a permutation in its matrix form. For example, `\drow{0,2,1,4,3,6,5}` produces the row

$$\begin{pmatrix} 0 & 1 & 2 & 3 & 4 & 5 & 6 \\ 0 & 2 & 1 & 4 & 3 & 6 & 5 \end{pmatrix}$$

     sep   lets the user choose the column separation.

`\drow[sep=10pt]{0,2,1,4,3,6,5}` produces the row

$$\begin{pmatrix} 0 & 1 & 2 & 3 & 4 & 5 & 6 \\ 0 & 2 & 1 & 4 & 3 & 6 & 5 \end{pmatrix}$$

3   The package code

```
1    % ddphonism
     %
3    % (c) Celia  Rubio Madrigal
     %
5    %% This program can be redistributed and/or modified  under the  terms
     %% of the LaTeX Project Public License  Distributed  from CTAN archives
7    %% in directory macros/latex/base/lppl . txt .

9    \NeedsTeXFormat{LaTeX2e}
     \ProvidesPackage{ddphonism}
11   [2019/09/01 v0.2 Dodecaphonic diagrams: twelve−tone matrices, clock  diagrams,  etc .]

13   \RequirePackage{etoolbox}
     \RequirePackage{xparse}
15   \RequirePackage{tikz}
     \RequirePackage{xstring}
17   \RequirePackage{pgfkeys}

19
```

```latex
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Matrices

\ usetikzlibrary {matrix}

\ExplSyntaxOn
\DeclareExpandableDocumentCommand{\Evaluation}{m}{\int_eval:n {#1}}
\ExplSyntaxOff

\newcounter{Dsize}
\newcommand{\DsizeMake}[1]{%
    \setcounter{Dsize}{0}%
    \foreach \n in {#1}{%
        \stepcounter{Dsize}%
    }%
}

% Only with numbers.
\newcounter{Dfirst}
\newcommand{\DheadMake}[1]{%
    \setcounter{ Dfirst }{−1}%
    \foreach \n in {#1}{%
        \ifnum\theDfirst=−1%
        \setcounter{ Dfirst }{\n}%
        \ fi %
    }%
}

% Only when DsizeMake is already done.
\newcounter{Dmod}
\newcommand{\Modulo}[1]{%
    \setcounter{Dmod}{#1}%
    \loop%
    \ifnum\theDmod>\Evaluation{\theDsize−1}%
    \setcounter{Dmod}{\Evaluation{\theDmod−\theDsize}}%
    \repeat%
    \ifnum\theDmod<0%
    \setcounter{Dmod}{\Evaluation{\theDmod+\theDsize}}%
    \repeat%
    \theDmod%
}

\newif\ ifdmatrixLines
\newif\ ifdmatrixOutside
\newif\ ifdmatrixInside
\newif\ifdmatrixV
\newif\ifdmatrixH
\newif\ ifdmatrixTikz
\pgfkeys{
    /dmatrix/. is  family
    , /dmatrix
    , default /. style  =
    {  lines  = false
        , outside  lines  = false
        ,  inside  lines  = false
        , sep = 1
        , vsep = 1
```

```
77            , hsep = 1
              , no tikz  = false
79        }
          , no tikz /. is  if =dmatrixTikz
81        , lines /. is  if =dmatrixLines
          , outside  lines /. is  if =dmatrixOutside
83        , inside  lines /. is  if =dmatrixInside
          , vlines /. is  if =dmatrixV
85        , hlines /. is  if =dmatrixH
          , sep/. estore  in=\dmatrixSep
87        , vsep/. estore  in=\dmatrixVsep
          , hsep/. estore  in=\dmatrixHsep
89    }

91    \newcommand{\DLOH}{%
          \draw (0.05*\dmatrixSep*\dmatrixHsep,0) −−%
93        (\theDsize*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,0);%
          \draw (0.05*\dmatrixSep*\dmatrixHsep,−\theDsize*0.5*\dmatrixSep*\dmatrixVsep) −− %
95        (\theDsize*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,−\theDsize*0.5*\dmatrixSep*\dmatrixVsep);%
      }
97
      \newcommand{\DLOV}{%
99        \draw (0.05*\dmatrixSep*\dmatrixHsep,0) −− %
          (0.05*\dmatrixSep*\dmatrixHsep,−\theDsize*0.5*\dmatrixSep*\dmatrixVsep);%
101       \draw (\theDsize*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,0) −− %
          (\theDsize*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,−\theDsize*0.5*\dmatrixSep*\dmatrixVsep);
103   }

105   \newcommand{\DLIH}{%
          \draw (0.05*\dmatrixSep*\dmatrixHsep,−\xD*0.5*\dmatrixSep*\dmatrixVsep) −− %
107       (\theDsize*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,−\xD*0.5*\dmatrixSep*\dmatrixVsep);%
      }
109
      \newcommand{\DLIV}{%
111       \draw (\xD*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,0) −− %
          (\xD*\dmatrixSep*\dmatrixHsep+0.05*\dmatrixSep*\dmatrixHsep,−\theDsize*0.5*\dmatrixSep*\dmatrixVsep);%
113   }

115   \newcommand{\dmatrix}[2][]{%
          \DsizeMake{#2}%
117       \DheadMake{#2}%
          %
119       \pgfkeys{/dmatrix, default , #1}%
          %
121       \ifdmatrixTikz \ else %
          \begin{ tikzpicture }%
123       \ fi %
          \foreach  [count=\nj] \j in {#2} {%
125           \foreach  [count=\ni] \i in {#2} {%
                  \draw node at
127               ( \ni*\dmatrixSep*\dmatrixHsep−0.5*\dmatrixSep*\dmatrixHsep
                  , −\nj*\dmatrixSep*\dmatrixVsep/2+0.25*\dmatrixSep*\dmatrixVsep) {%
129                   \Modulo{\Evaluation{\i−\j+\theDfirst}}%
                  };%
131           }%
          }%
133       \foreach \xD in  {1,...,\ Evaluation{\theDsize−1}} {%
```

```
               \ifdmatrixLines
135            \DLOH\DLOV\DLIH\DLIV
               \fi
137            \ifdmatrixOutside
               \DLOH\DLOV
139            \fi
               \ifdmatrixInside
141            \DLIH\DLIV
               \fi
143            \ifdmatrixH
               \DLOH\DLIH
145            \fi
               \ifdmatrixV
147            \DLOV\DLIV
               \fi
149        }%
           %
151        \ifdmatrixTikz\else%
           \end{tikzpicture}%
153        \fi%
       }


157    %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
       % Diagrams
159
       \usetikzlibrary{shapes,arrows, decorations .markings,shapes.misc}
161
       \tikzstyle{ddiagram}=[minimum height=0pt,inner sep=0pt,outer sep=0pt,scale=0.65]
163
       \newif\ifddiagramTikz
165    \newif\ifddiagramNoNum
       \newif\ifddiagramNoArr
167    \pgfkeys{
           /ddiagram/.is family
169        , /ddiagram
           , default /. style =
171        { name =\empty%
               , up =\empty%
173            , no tikz  = false
               , no numbers = false
175            , no arrow  = false
               , xshift  = 0
177            , yshift  = 0
               , arrow  shift  = 2.5
179        }
           , no tikz /. is  if =ddiagramTikz
181        , no numbers/.is  if =ddiagramNoNum
           , no arrow/. is   if =ddiagramNoArr
183        , name/.estore  in=\ddiagramName
           , up/. estore  in=\ddiagramUp
185        , xshift /. estore  in=\ddiagramX
           , yshift /. estore  in=\ddiagramY
187        , arrow  shift /. estore  in=\ddiagramArrS
       }
189
       \newcounter{Dprev}
```

```latex
191    \newcommand{\Dvar}{}
       \newcommand{\ddiagram}[2][]{%
193        \DsizeMake{#2}%
           \DheadMake{#2}%
195        %
           \pgfkeys{/ddiagram, default, #1}%
197        %
           \ifdefequal {\ddiagramUp}{\empty}%
199        {\renewcommand{\Dvar}{\theDfirst}}% if empty
           {\renewcommand{\Dvar}{\ddiagramUp}}% if not empty
201        %
           \ifddiagramTikz\else%
203        \begin{ tikzpicture }[ddiagram,rotate=360*\Dvar/\theDsize]%
           \fi%
205        \foreach \x in  {0,...,\ Evaluation{\theDsize−1}} {%
               \ifddiagramNoNum\else
207            \node [xshift =\ddiagramX,yshift=\ddiagramY] at (90−360*\x/\theDsize:2) {\x};%
               \fi
209            \node [xshift =\ddiagramX,yshift=\ddiagramY] (\x) at (90−360*\x/\theDsize:1.6) {};%
           };%
211        %
           \setcounter{Dprev}{−1}%
213        \foreach \x in {#2}{%
               \ifnum \theDprev=\theDfirst%
215            \ifddiagramNoArr
               \draw [xshift =\ddiagramX,yshift=\ddiagramY] (\theDprev) −− (\x);%
217            \else
               \draw [xshift =\ddiagramX,yshift=\ddiagramY,
219            decoration=
               {markings,mark=at position 0.099*\ddiagramArrS with
221                {\arrow[scale=1.25,>=triangle 45]{>}}},
               postaction={decorate}
223            ] (\theDprev) −− (\x);%
               \fi
225            \else \ifnum \theDprev=−1 \else%
               \draw [xshift =\ddiagramX,yshift=\ddiagramY] (\theDprev) −− (\x);%
227            \fi \fi%
               \setcounter{Dprev}{\x}%
229        };%
           \draw [xshift =\ddiagramX,yshift=\ddiagramY] (\theDprev) −− (\theDfirst);%
231        %
           \ifdefequal {\ddiagramName}{\empty}%
233        {}% if empty
           {\node [xshift =\ddiagramX,yshift=\ddiagramY] at (0,0) [circle, fill =white] {\ddiagramName};}% if not empty
235        \ifddiagramTikz\else%
           \end{ tikzpicture }%
237        \fi%
       }
239

241    %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
       % Dihedral diagrams
243
       \ tikzstyle  ddihedralArrow=[decoration=
245    {markings,mark=at position 1 with {\arrow[scale=1.5,>=angle 60]{>}}},
       postaction={decorate}]
247
```

```
        \ tikzstyle {ddihedral}=[inner sep=0,minimum height=18pt]
249
        \newif\ ifddihedralTikz
251     \newif\  ifddihedralItalics
        \pgfkeys{
253         /ddihedral /. is  family ,  /ddihedral ,
            default /. style  =
255             { t = 0, c = 0, s = 0, v = 0
                , no  tikz =false
257             , new t = T, new c = C, new s = S, new v = V
                , no  italics  = false
259             },
            no tikz /. is  if =ddihedralTikz,
261         t /. estore  in  = \ddihedralT,
            c /. estore  in  = \ddihedralC,
263         s /. estore  in  = \ddihedralS,
            v /. estore  in  = \ddihedralV,
265         no  italics  /. is  if = ddihedralItalics ,
            new t /. estore  in  = \ddihedralNewT,
267         new c /. estore  in  = \ddihedralNewC,
            new s /. estore  in  = \ddihedralNewS,
269         new v /. estore  in  = \ddihedralNewV,
        }
271
        \newif\ ifdarrowsTikz
273     \pgfkeys{
            /darrows/. is  family ,  /darrows,
275         default /. style  = {no tikz=false },
            no  tikz /. is  if =darrowsTikz,
277     }
        \newcommand{\darrows}[2][]{%
279         \DsizeMake{#2}%
            %
281         \pgfkeys{/darrows,  default ,  #1}%
            %
283         \ifdarrowsTikz \ else %
            \begin{ tikzpicture }%
285         \ fi %
            \draw foreach \x in  {0,...,\ Evaluation{\theDsize−1}} {%
287             (90−360∗\x/\theDsize:2.5) node[circle ] (\x) {}%
            };%
289         \foreach  \x [count=\y] in {#2} {%
                \draw [ style =ddihedralArrow] (90−360∗\Evaluation{\y−1}/\theDsize:1.25) −− (\x);%
291         };%
            \ifdarrowsTikz \ else %
293         \end{ tikzpicture }%
            \ fi %
295     }
297     \newcommand\ddihedral[2][]{%
            \DsizeMake{#2}%
299         %
            \pgfkeys{/ddihedral ,  default ,  #1}%
301         %
            \ ifddihedralTikz \ else %
303         \begin{ tikzpicture }[ ddihedral ]%
            \ fi %
```

11

```latex
305        \draw foreach \x in  {0,...,\ Evaluation{\theDsize−1}} {%
               (\Evaluation{(90+\ddihedralT∗360/\theDsize)+(2∗\ddihedralS−1)∗\x∗360/\theDsize}:2.5)%
307            node[very  thin , circle ,draw] (\x)  {\x}%
           };%
309        %
           \draw foreach \x in  {0,...,\ Evaluation{\theDsize−1}} {%
311            (\Evaluation{(90−\ddihedralC∗360/\theDsize)+(2∗\ddihedralV−1)∗\x∗360/\theDsize}:1.25)%
               node[very  thin , circle ,draw]  {\x}%
313        };%
           %
315        \darrows[no  tikz]{#2}%
           %
317        \node at  (0,0)  [very  thin ,draw, circle ,    fill =white]  {%
           {\  ifddihedralItalics  \else \ it \ fi %
319            \ifodd\ddihedralV%
               \ddihedralNewV\else%
321            \ifnum\ddihedralC=0%
               \ifodd\ddihedralS\ else %
323            \ifnum\ddihedralT=0%
               \ddihedralNewT$^0$%
325            \ fi \ fi \ fi \ fi %
               \ifnum\ddihedralC=0%
327            \ else  \ddihedralNewC$^{\ddihedralC}$\fi%
               \ifodd\ddihedralS%
329            \ddihedralNewS\fi%
               \ifnum\ddihedralT=0%
331            \ else  \ddihedralNewT$^{\ddihedralT}$\fi}%
           };%
333        \ ifddihedralTikz  \else%
           \end{ tikzpicture }%
335        \ fi %
       }
337

339    %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
       % Rows
341
       \pgfkeys{
343        /drow/.is  family ,  /drow,
           default /. style  = {sep=\arraycolsep},
345        sep/. estore  in  = \drowSep,
       }
347
       \long\def\addto#1#2{\expandafter\def\expandafter#1\expandafter{#1#2}}
349    \newcounter{myDDcntr}
       \newlength{\Dvarr}
351
       \newcommand{\drow}[2][]{%
353        \DsizeMake{#2}%
           %
355        \pgfkeys{/drow, default ,  #1}%
           \setlength {\Dvarr}{\arraycolsep}
357        \setlength {\ arraycolsep }{\drowSep}
           %
359        \ifnum\theDsize=0%
           \ensuremath{\left(\ right )}%
361        \ else \ifnum\theDsize=1%
```

```latex
        \ensuremath{%
            \left(\begin{array}{*{\theDsize}c}%
                0\\%
                #2\\%
            \end{array}\right)%
        }%
        \else%
        \def\TableDDdata{}%
        \setcounter{myDDcntr}{0}%
        \loop%
        \addto\TableDDdata{\themyDDcntr\stepcounter{myDDcntr} &}%
        \stepcounter{myDDcntr}%
        \ifnum\themyDDcntr<\Evaluation{\theDsize-1}%
        \repeat%
        \addto\TableDDdata{\themyDDcntr \\}%
        \setcounter{myDDcntr}{0}%
        %
        \ensuremath{%
            \left(\begin{array}{*{\theDsize}c}%
                \TableDDdata%
                \StrSubstitute{#2}{,}{&}\\%
            \end{array}\right)%
        }%
        \fi\fi%
        \setlength{\arraycolsep}{\Dvarr}
    }

\endinput


%% End of file 'ddphonism.sty'.
```