

# Package ‘UStatBookABSC’

October 12, 2022

**Title** A Companion Package to the Book “U-Statistics, M-Estimation and Resampling”

**Version** 1.0.0

**Author** Snigdhansu Chatterjee <chatt019@umn.edu>

**Maintainer** Snigdhansu Chatterjee <chatt019@umn.edu>

**Description** A set of functions leading to multivariate response L1 regression. This includes functions on computing Euclidean inner products and norms, weighted least squares estimates on multivariate responses, function to compute fitted values and residuals. This package is a companion to the book “U-Statistics, M-estimation and Resampling”, by Arup Bose and Snigdhansu Chatterjee, to appear in 2017 as part of the “Texts and Readings in Mathematics” (TRIM) series of Hindustan Book Agency and Springer-Verlag.

**Depends** R (>= 3.2.3)

**Suggests** MASS

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 5.0.1.9000

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2016-12-27 17:50:42

## R topics documented:

CCU12_Precip	2
FitAndResiduals	2
IdentityMatrix	3
InnerProduct	4
L1Regression	4
Norm	5
WLS	6
<b>Index</b>	<b>7</b>

---

CCU12\_Precip

*Precipitation for June-September 2012 recorded in Kolkata*

---

### Description

Precipitation for June-September 2012 recorded in Kolkata

### Usage

```
data(CCU12_Precip)
```

### Format

A data frame with columns

**Date** The data in Year-Month-Day format

**Precip** Precipitation in millimeters

**TMax** Maximum temperature, in Celcius

**TMin** Minimum temperature, in Celcius

### Examples

```
Precip <-CCU12_Precip$Precip  
TMax <-CCU12_Precip$TMax  
plot(TMax, Precip)
```

---

FitAndResiduals

*Computes a linear regression fit and residuals on possibly multivariate responses*

---

### Description

Computes a linear regression fit and residuals on possibly multivariate responses

### Usage

```
FitAndResiduals(Y, X, BetaHat)
```

### Arguments

Y                    a numeric matrix, to act as response  
X                    a numeric matrix, to act as covariates  
BetaHat             a numeric matrix, to act as slope

**Value**

a list consisting of two vectors, the fitted values and residuals

**Examples**

```
## Not run:  
DataY = cbind(CCU12_Precip$Precip, CCU12_Precip$TMax);  
DataX = cbind(rep(1, length(CCU12_Precip$Precip)), CCU12_Precip$TMin)  
BetaHat.New = WLS(DataY, DataX)  
Results.New = FitAndResiduals(DataY, DataX, BetaHat.New);  
  
## End(Not run)
```

---

IdentityMatrix	<i>Obtains the identity matrix of dimension n</i>
----------------	---

---

**Description**

Obtains the identity matrix of dimension n

**Usage**

```
IdentityMatrix(n)
```

**Arguments**

n                    an integer

**Value**

an identity matrix

**Examples**

```
I.3 = IdentityMatrix(3)  
print(I.3)
```

---

InnerProduct	<i>Computes the Euclidean inner product</i>
--------------	---

---

**Description**

Computes the Euclidean inner product

**Usage**

```
InnerProduct(a, b, na.rm)
```

**Arguments**

a	a numeric vector
b	another numeric vector
na.rm	logical

**Value**

a real number

**Examples**

```
x <- c(1, 2, 3)
y <- c(3, 0, 1)
InnerProduct(x, y)
```

---

L1Regression	<i>Computes a L1 multivariate regression This is the equivalent of median regression when the response is possibly multivariate</i>
--------------	---

---

**Description**

Computes a L1 multivariate regression This is the equivalent of median regression when the response is possibly multivariate

**Usage**

```
L1Regression(Data.Y, Data.X, Weights,
  InitialValue = "WLS", MaxIteration, epsilon, lambda)
```

**Arguments**

Data.Y	a numeric matrix, to act as response
Data.X	a numeric matrix, to act as covariates
Weights	a numeric matrix, to act as weights
InitialValue	a character, to denote how the initial estimate will be computed currently the only available option is WLS
MaxIteration	an integer, for the maximum number of iterations allowed
epsilon	a positive real number, as tolerance value for convergence
lambda	a real number between 0 and 1, to control the amount of update allowed in each iteration

**Value**

a list consisting of the iteration value at the last step, the difference in norms between the last two iterations, and the estimate of slope

**Examples**

```
## Not run:
DataY = cbind(CCU12_Precip$Precip, CCU12_Precip$TMax);
DataX = cbind(rep(1, length(CCU12_Precip$Precip)), CCU12_Precip$TMin)
A2 = L1Regression(DataY, DataX)

## End(Not run)
```

---

Norm	<i>Computes the Euclidean norm</i>
------	------------------------------------

---

**Description**

Computes the Euclidean norm

**Usage**

```
Norm(a, na.rm)
```

**Arguments**

a	a numeric vector
na.rm	logical

**Value**

a real number

**Examples**

```
x <- c(1, 2)
Norm(x)
```

---

WLS	<i>Computes a weighted least squares linear regression on possibly multivariate responses</i>
-----	---

---

**Description**

Computes a weighted least squares linear regression on possibly multivariate responses

**Usage**

```
WLS(Y, X, W)
```

**Arguments**

Y	a numeric matrix, to act as response
X	a numeric matrix, to act as covariates
W	a numeric matrix, to act as weights

**Value**

a vector of regression coefficients

**Examples**

```
## Not run:
DataY = cbind(CCU12_Precip$Precip, CCU12_Precip$TMax);
DataX = cbind(rep(1, length(CCU12_Precip$Precip)), CCU12_Precip$TMin)
BetaHat.New = WLS(DataY, DataX)

## End(Not run)
```

# Index

## \* datasets

CCU12\_Precip, 2

CCU12\_Precip, 2

FitAndResiduals, 2

IdentityMatrix, 3

InnerProduct, 4

L1Regression, 4

Norm, 5

WLS, 6