

Package ‘Waypoint’

March 19, 2025

Type Package

Title Convert, Validate, Format and Print Geographic Coordinates and Waypoints

Version 1.1.0

Date 2025-03-17

Description Convert, validate, format and elegantly print geographic coordinates and waypoints (paired latitude and longitude values) in decimal degrees, degrees and minutes, and degrees, minutes and seconds using high performance C++ code to enable rapid conversion and formatting of large coordinate and waypoint datasets.

License MIT + file LICENSE

Imports methods, Rcpp (>= 1.0.13)

LinkingTo Rcpp

RoxxygenNote 7.3.1

Encoding UTF-8

URL <https://mark-eis.github.io/Waypoint/>

NeedsCompilation yes

Author Mark Eisler [aut, cre, cph] (<<https://orcid.org/0000-0001-6843-3345>>)

Maintainer Mark Eisler <mark.eisler@bristol.ac.uk>

Depends R (>= 4.1.0)

Repository CRAN

Date/Publication 2025-03-19 13:00:01 UTC

Contents

Waypoint-package	2
convert	2
coords	4
format	6
op-zero-length	8
review	9
validate	10
waypoints	12

Waypoint-package	<i>Convert, Validate, Format and Print Geographic Coordinates and Waypoints</i>
------------------	---------------------------------------------------------------------------------

Description

Convert, validate, format and elegantly print geographic coordinates and waypoints (paired latitude and longitude values) in decimal degrees, degrees and minutes, and degrees, minutes and seconds using high performance C++ code to enable rapid conversion and formatting of large coordinate and waypoint datasets.

Package Content

Index of help topics:

convert	Convert the Format of "coords" and "waypoints" Objects
coords	Geographic Coordinate Class
format	Format and Print Coords or Waypoints
op-zero-length	Operator Providing Alternative to Zero-Length Object
review	Review Coordinates and Waypoints Validity
validate	Validate Coords or Waypoints
Waypoint-package	Convert, Validate, Format and Print Geographic Coordinates and Waypoints
waypoints	Geographic Waypoint Class

Maintainer

Mark Eisler <mark.eisler@bristol.ac.uk>

Author(s)

Mark Eisler [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0001-6843-3345>>)

convert	<i>Convert the Format of "coords" and "waypoints" Objects</i>
---------	---------------------------------------------------------------

Description

Convert the format of objects of class "coords" or "waypoints" between (i) decimal degrees, (ii) degrees and minutes, and (iii) degrees, minutes and seconds.

Usage

```
convert(x, ...)

## S3 method for class 'coords'
convert(x, fmt, ...)

## S3 method for class 'waypoints'
convert(x, fmt, ...)
```

Arguments

x	object of class " coords " created by function as_coords() , or class " waypoints " created by function as_waypoints() .
...	further arguments passed to or from other methods.
fmt	integer, 1L, 2L or 3L, specifying the required coordinate format.

Details

The `fmt` argument should be 1L to convert to *decimal degrees*, 2L, to convert to *degrees and minutes*, and 3L to convert to *degrees, minutes and seconds*. On conversion of a "coords" object, the original argument `x` is modified to have a decimal point after the number of whole degrees in the case of decimal degrees, after the number of whole minutes in the case of degrees and minutes, and after the number of whole seconds in the case of degrees, minutes and seconds.

Prior to conversion, the "coords" or "waypoints" object to be converted is checked to ensure its values represent valid geographic locations as described under [validate\(\)](#).

Value

The original argument `x`, an object of class "coords" or "waypoints" with values converted as described under *details* and a revised "`fmt`" attribute reflecting the new format.

See Also

["coords"](#), ["waypoints"](#) and [validate\(\)](#).

Other coordsandway: [coords](#), [waypoints](#)

Examples

```
## Continuing example from `as_coords()`...

## Named "coords" object in degrees and minutes with
## eight values each of latitude and longitude
dm

## Convert to degrees, minutes and seconds (fmt = 3)
convert(dm, 3)

## Convert to decimal degrees (fmt = 1)
```

```

convert(dm, 1)

## Show converted values as an ordinary R numeric vector
as.numeric(dm)

###  

### Continuing example from `as_waypoints()`...

## "waypoints" object in degrees, minutes and seconds
wp

## Convert to degrees and minutes (fmt = 2)
convert(wp, 2)

## Convert to decimal degrees (fmt = 1)
convert(wp, 1)

## Show converted values as an ordinary R data frame
as.data.frame(wp)

rm(dm, wp)

```

Description

`as_coords()` creates an object of class "coords", a robust representation of a series of geographic or GPS coordinate values.

`latlon()<-` adds information to objects of class "coords" specifying whether individual coordinate values represent latitude or longitude.

Usage

```

as_coords(object, ...)

## Default S3 method:
as_coords(object, ..., fmt = 1L)

latlon(cd) <- value

## S3 method for class 'waypoints'
as_coords(object, which, ...)

```

Arguments

object	a numeric vector of coordinate values, optionally named, or an object of class "waypoints".
...	further arguments passed to or from other methods.
fmt	integer, 1L, 2L or 3L, specifying the required coordinate format.
cd	object of class "coords" created by function as_coords() .
value	a logical vector of length 1 or length(x).
which	logical, indicating whether the as_coords() method for class "waypoints" extracts the latitude component of argument object (if TRUE), or the longitude (if FALSE).

Details

Individual values provided in a numeric vector argument object should have a decimal point after the number of whole degrees in the case of *decimal degrees*, after the number of whole minutes in the case of *degrees and minutes*, and after the number of whole seconds in the case of *degrees, minutes and seconds*.

The fmt argument should be 1L to represent decimal degrees, 2L for degrees and minutes, and 3L for degrees, minutes and seconds and is used to provide the format of values in the numeric vector argument object to be converted to class "coords".

The values of a newly created "coords" object are checked to ensure they are valid geographic locations as described under [validate\(\)](#).

Individual coordinate values in a Coords object may be specified as representing latitude or longitude using [latlon\(\)](#). The value argument may either be a single value, TRUE signifying that all values are latitude, FALSE signifying that all values are longitude, or a logical vector of the same length as the Coords object signifying whether individual values are latitude or longitude.

Value

[as_coords\(\)](#) returns an object of class "coords", comprising a numeric vector argument with additional attributes: –

"class"	the character string "coords".
"fmt"	an integer representing the coordinate format.
"valid"	a logical vector indicating whether individual coordinate values are valid geographic locations.

The [as_coords\(\)](#) method for class "coords" returns its numeric vector argument object modified in place, whereas the method for class 'waypoints' returns a new numeric vector.

[latlon\(\)](#) returns its "coords" argument cd with a logical vector attribute "latlon" added or updated to reflect argument value.

See Also

[attr\(\)](#), [attributes](#), and [validate\(\)](#).

Other coordsandway: [convert\(\)](#), [waypoints](#)

Examples

```

## Numeric vector representing degrees and minutes, with
## the decimal point after the number of whole minutes
dm <- c(5130.4659, 4932.7726, 4806.4339, 3853.3696, 0.0000, -3706.7044, -5306.2869, -2514.4093,
       -007.6754, 1823.9137, -12246.7203, -7702.1145, 0.0000, -1217.3178, 7331.0370, -5731.1536)

## Create an unnamed "coords" object of degrees and minutes (fmt = 2)
## (Latitude and longitude unspecified)
as_coords(dm, fmt = 2)

## Name the "coords" object
names(dm) <- rep(c("Nelson's Column", "Ostravice", "Tally Ho", "Washington Monument", "Null Island",
                     "Tristan da Cunha", "Mawson Peak", "Silvio Pettirossi International Airport"), 2)
dm

## Set all values to represent longitude
## ("latlon" attribute set to FALSE, length 1)
latlon(dm) <- FALSE
dm

## Set eight values each of latitude and longitude
## ("latlon" attribute set to TRUE, n=8, and FALSE, n=8)
latlon(dm) <- rep(c(TRUE, FALSE), each = 8)
dm

## Show as an ordinary R numeric vector
as.numeric(dm)

rm(dm)

```

Description

Format and print objects of class "coords" or "waypoints".

Usage

```

## S3 method for class 'coords'
print(x, ..., max = NULL)

## S3 method for class 'waypoints'
print(x, ..., max = NULL)

## S3 method for class 'coords'
format(x, ..., usernames = TRUE)

```

```
## S3 method for class 'waypoints'
format(x, ..., usenames = TRUE)

ll_headers(aswidth, fmt)
```

Arguments

x	object of class " coords " created by function as_coords() , or class " waypoints " created by function as_waypoints() .
...	further arguments passed to or from other methods.
max	numeric or NULL, specifying the maximal number of entries to be printed. By default, when NULL, getOption("max.print") used.
usenames	logical, whether or not to include names in formatted output; default TRUE.
aswidth	character vector, used to match width of headers to formatted output.
fmt	integer, 1L, 2L or 3L, specifying the required coordinate format.

Details

The `format()` methods for "[coords](#)" and "[waypoints](#)" objects output elegantly formatted character vector representations of their arguments, which are used by their respective `print()` methods.

Prior to formatting and printing, "[coords](#)" or "[waypoints](#)" objects are checked to ensure that their "`valid`" attribute (in the case of a "[coords](#)" object), or "`validlat`" and "`validlon`" attributes (in the case of a "[waypoints](#)" object) are present and all TRUE i.e., valid. If these attributes are found to contain any FALSE i.e. invalid values, a warning is issued and similarly, if these attributes are missing, a warning is issued and the objects are re-validated as described under [validate\(\)](#).

`ll_headers()` outputs the headings "Latitude ... Longitude" formatted to the same width as argument `aswidth`, adjusted for format `fmt` and is primarily intended for use by the `print()` method for class "[waypoints](#)".

Value

The `format()` methods for both classes "[coords](#)" and "[waypoints](#)" return a character vector, respectively of length `length(x)` or `nrow(x)`, and containing values formatted in decimal degrees, degrees and minutes, or degrees, minutes and seconds as appropriate.

See Also

[format\(\)](#), [print\(\)](#), "[coords](#)" and "[waypoints](#)".

Examples

```
## Continuing example from `as_coords()`...

## Print named "coords" object in degrees and minutes,
## 'silently' using S3 print() method
dm
```

```

## Format as a fixed-width character vector,
## with names...
format(dm)

## ...or without them
format(dm, usenames = FALSE)

####
## Continuing example from `as_waypoints()`...

## Print named "waypoints" object in degrees and minutes,
## 'silently' using S3 print() method
wp

## Format as a fixed-width character vector,
## with names...
format(wp)

## ...or without them
format(wp, usenames = FALSE)

rm(dm, wp)

```

Description

Infix function implementing provision of an alternative if an object has zero length.

Usage

`x %L% y`

Arguments

<code>x, y</code>	atomic vector arguments or other objects for which <code>length()</code> is defined.
-------------------	--------------------------------------------------------------------------------------

Details

The infix function `%L%` may be useful in implementing `if (length(x)) x else y` and was inspired by the null coalescing operator `%||%`.

Value

`x`, or if `length(x)` is zero, `y`.

See Also

[%| |%.](#)

Examples

```
c4 <- letters[1:4]
c0 <- character(0)
n3 <- 1:3
n0 <- numeric(0)

c4 %L% n3
c0 %L% n3

n3 %L% c4
n0 %L% c4

rm(c4, c0, n3, n0)
```

review

Review Coordinates and Waypoints Validity

Description

Review validity of elements of "coords" and "waypoints" objects.

Usage

```
review(x, ...)
## S3 method for class 'coords'
review(x, ..., show_n = 20L)

## S3 method for class 'waypoints'
review(x, ..., show_n = 20L)
```

Arguments

- x object of class "[coords](#)" created by function [as_coords\(\)](#), or class "[waypoints](#)" created by function [as_waypoints\(\)](#).
- ... further arguments passed to or from other methods.
- show_n integer, the maximum number of invalid elements of argument x to include in the output; default 20L.

Details

`review()` reveals elements of "coords" and "waypoints" objects that do not conform to the criteria checked by [validate\(\)](#), i.e. are not valid geographic locations.

Value

The `review()` method for class "coords" returns a `list` comprising the following elements: -

<code>allvalid</code>	logical, whether or not all the elements of argument <code>x</code> are valid.
<code>n_invalid</code>	integer, the number of invalid elements in argument <code>x</code> , if any.
<code>invalids</code>	numeric vector including invalid elements of argument <code>x</code> , if any.
<code>which_invalid</code>	integer vector specifying which elements of argument <code>x</code> are invalid, if any.

The method for class "waypoints" returns a list of two sub-lists, each sub-list with elements as described above for the method for class "coords", one each for latitude and longitude.

See Also

"coords" and "waypoints".

Other validate: `validate()`

Examples

```
## Continuing example from `validate()``...

## Review "coords" object in degrees and minutes, having
## an erroneous first value of more than 60 minutes
review(dm)

####
## Continuing example from `validate()``...

## Review "waypoints" object in decimal degrees, having an erroneous
## penultimate latitude absolute value greater than 90 degrees
review(wp)

rm(dm, wp)
```

Description

Validate objects of class "coords" or "waypoints" as geographic locations.

Usage

```
validate(x, ...)

## S3 method for class 'coords'
validate(x, ...)

## S3 method for class 'waypoints'
validate(x, ...)
```

Arguments

- | | |
|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | object of class " coords " created by function as_coords() , or class " waypoints " created by function as_waypoints() . |
| ... | further arguments passed to or from other methods. |

Details

Individual coordinate values within "[coords](#)" or "[waypoints](#)" objects are checked to ensure they represent valid geographic locations.

To be valid, the absolute values of coordinates in degrees must not exceed 180°, or 90° if degrees of latitude and, similarly, the absolute values of the minutes and seconds components, where given, must not exceed 60. Otherwise, a warning will be issued and the "valid" attribute in the case of a "coords" object, or "validlat" and "validlon" attributes in the case of a "waypoints" object will be set to FALSE for any non-compliant coordinate values.

Value

`validate()` returns its argument with logical vector attribute "valid", or attributes "validlat" and "validlon" updated as appropriate for "coords" and "waypoints" objects respectively.

See Also

"[coords](#)" and "[waypoints](#)".

Other validate: [review\(\)](#)

Examples

```
## Continuing example from `as_coords()``...

## Validate "coords" object in degrees and minutes
validate(dm)

## Deliberately change the first coordinate
## to a value greater than 60 minutes
dm[1] <- 5160.4659

validate(dm)
```

```

## Examine "valid" attribute of dm
attr(dm, "valid")

###  

## Continuing second example from `as_waypoints()`...

## Validate "waypoints" object in decimal degrees

validate(wp)

## Deliberately change the penultimate latitude
## to an absolute value greater than 90 degrees
wp$lat[7] <- -93.104781

validate(wp)

## Examine "validlat" attribute of wp
attr(wp, "validlat")

rm(dm, wp)

```

waypoints*Geographic Waypoint Class***Description**

`as_waypoints()` creates an object of class "waypoints", a robust representation of a series of geographic or GPS waypoints of paired latitude and longitude values.

Usage

```

as_waypoints(object, ...)

## Default S3 method:
as_waypoints(object, ..., fmt = 1L)

```

Arguments

- | | |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | a data frame with each row representing a waypoint, comprising at least two numeric columns containing values of latitude and longitude, and optionally a character column of waypoint names (see <i>Details</i>). |
| <code>...</code> | further arguments passed to or from other methods. |
| <code>fmt</code> | integer, 1L, 2L or 3L, specifying the required coordinate format. |

Details

Data frame argument object should have numeric vector latitude and longitude columns with individual values having a decimal point after the number of whole degrees in the case of *decimal degrees*, after the number of whole minutes in the case of *degrees and minutes*, and after the number of whole seconds in the case of *degrees, minutes and seconds*. These should be the first two columns of the data frame, or the second and third columns if the first column contains waypoints names (see below). Alternative columns may be specified for the latitude and longitude by setting "llcols" as a length 2 integer vector attribute of object indicating their positions in the data frame.

The `fmt` argument should be 1L to represent decimal degrees, 2L for degrees and minutes, and 3L for degrees, minutes and seconds and is used to provide the format of values in data frame argument object to be converted to class "waypoints".

If the waypoints have names, these should be included in a "Name" column of data frame argument object, by default immediately before (on the left-hand side of) the latitude and longitude columns. An alternative column for waypoint names may be specified by setting an integer `attribute` named "namescol" indicating its position in object, while setting this attribute to NA suppresses printing of waypoint names. If neither a "Name" column nor a "namescol" attribute is present in object, `row.names` are used for waypoint names.

The latitude and longitude values of a newly created "waypoints" object are checked to ensure they are valid geographic locations as described under `validate()`.

Value

An object of classes "waypoints" and "data.frame", comprising the original data frame argument object, with additional attributes: –

"class"	the character string "waypoints".
"fmt"	an integer indicating the coordinate format.
"namescol"	an integer indicating the position of a waypoint names column, if present.
"llcols"	a length 2 integer vector indicating the positions of latitude and longitude columns.
"validlat" and "validlon"	logical vectors indicating whether individual latitude and longitude values are valid geographic locations.

See Also

`attr()`, `data.frame()`, and `validate()`.

Other coordsandway: `convert()`, `coords`

Examples

```
## Dataframe representing waypoint names, and latitude and longitude values
## in degrees, minutes and seconds
wp1 <- data.frame(
  name = c("Nelson's Column", "Ostravice", "Tally Ho", "Washington Monument", "Null Island",
         "Tristan da Cunha", "Mawson Peak", "Silvio Pettirossi International Airport"),
  lat = c(513027.95, 493246.36, 480626.04, 385322.18, 0, -370642.26, -530617.21, -251424.56),
```

```

lon = c(-00740.53, 182354.82, -1224643.22, -770206.87, 0, -121719.07, 733102.22, -573109.21)
)

## Create "waypoints" object of degrees, minutes and seconds (fmt = 3)
as_waypoints(wp1, fmt = 3)

## Show as an ordinary R data frame
as.data.frame(wp1)

### 

## Dataframe representing unnamed latitude and longitude
## values in decimal degrees
wp2 <- data.frame(
  lat = c(51.507765, 49.54621, 48.107232, 38.889494, 0, -37.11174, -53.104781, -25.240156),
  lon = c(-0.127924, 18.398562, -122.778671, -77.035242, 0, -12.28863, 73.517283, -57.519227)
)

## Create unnamed "waypoints" object of decimal degrees (default fmt = 1)
as_waypoints(wp2)

## Add waypoint names as row.names
row.names(wp2) <-
  c("Nelson's Column", "Ostravice", "Tally Ho", "Washington Monument", "Null Island",
    "Tristan da Cunha", "Mawson Peak", "Silvio Pettirossi International Airport")

wp2

## Show as an ordinary R data frame
as.data.frame(wp2)

rm(wp1, wp2)

```

Index

- * **character**
 - format, 6
- * **coordsandway**
 - convert, 2
 - coords, 4
 - waypoints, 12
- * **logic**
 - op-zero-length, 8
- * **package**
 - Waypoint-package, 2
- * **print**
 - format, 6
- * **programming**
 - convert, 2
 - op-zero-length, 8
- * **utils**
 - op-zero-length, 8
- * **validate**
 - review, 9
 - validate, 10

%L% (op-zero-length), 8
%, 8, 9

- as_coords, 3, 5, 7, 9, 11
- as_coords (coords), 4
- as_waypoints, 3, 7, 9, 11
- as_waypoints (waypoints), 12
- attr, 5, 13
- attribute, 13
- attributes, 5

convert, 2, 5, 13
coords, 3, 4, 7, 9–11, 13

data.frame, 13

format, 6, 7

getOption, 7

latlon<- (coords), 4

- list, 10
- ll_headers (format), 6

op-zero-length, 8

print, 7

print.coords (format), 6

print.waypoints (format), 6

review, 9, 11

row.names, 13

validate, 3, 5, 7, 9, 10, 10, 13

Waypoint (Waypoint-package), 2

Waypoint-package, 2

waypoints, 3, 5, 7, 9–11, 12