

Package ‘paramlink2’

September 7, 2024

Type Package

Title Parametric Linkage Analysis

Version 1.0.6

Description Parametric linkage analysis of monogenic traits in medical pedigrees. Features include singlepoint analysis, multipoint analysis via 'MERLIN' (Abecasis et al. (2002) <doi:10.1038/ng786>), visualisation of log of the odds (LOD) scores and summaries of linkage peaks. Disease models may be specified to accommodate phenocopies, reduced penetrance and liability classes. 'paramlink2' is part of the 'pedsuite' package ecosystem, presented in 'Pedigree Analysis in R' (Vigeland, 2021, ISBN:9780128244302).

License GPL-3

URL <https://github.com/magnusdv/paramlink2>

BugReports <https://github.com/magnusdv/paramlink2/issues>

Depends R (>= 4.1), pedtools

Imports pedprobr

Suggests spelling, testthat

Encoding UTF-8

Language en-GB

LazyData true

RoxygenNote 7.3.2

SystemRequirements MERLIN (<https://csg.sph.umich.edu/abecasis/merlin/>)
for multipoint linkage analysis.

NeedsCompilation no

Author Magnus Dehli Vigeland [aut, cre]
(<<https://orcid.org/0000-0002-9134-4962>>)

Maintainer Magnus Dehli Vigeland <m.d.vigeland@medisin.uio.no>

Repository CRAN

Date/Publication 2024-09-07 13:50:02 UTC

Contents

diseaseModel	2
dominant1	3
linkres	4
lod	5
lodPeaks	7
merlinLod	8
Index	11

diseaseModel	<i>Disease models for linkage analysis</i>
--------------	--

Description

Create a disease model in form of a `disModel` object, for use in e.g. `lod()`.

Usage

```
diseaseModel(model = NULL, chrom = NULL, penetrances = NULL, dfreq = NULL)
```

Arguments

<code>model</code>	An existing <code>disModel</code> object (to be modified by other arguments), or one of the following two-letter keywords: <ul style="list-style-type: none"> • AD = autosomal dominant • AR = autosomal recessive • XD = X-linked dominant • XR = X-linked recessive <p>In all of the above, the disease is assumed to be fully penetrant, and with a disease allele frequency of $1e-5$.</p>
<code>chrom</code>	Either "AUTOSOMAL" or "X". Lower case versions are allowed and will be converted automatically.
<code>penetrances</code>	For autosomal models, a numeric of length 3 corresponding to (f_0, f_1, f_2) , where f_i is the probability of being affected given i disease alleles. It can also be a matrix with 3 columns, in which case each row represents a liability class. For X-linked models, a list of two vectors named <code>male</code> and <code>female</code> , of lengths 2 and 3 respectively: (f_0, f_1) for males and (f_0, f_1, f_2) for females. Alternatively, each list entry may be a matrix or data frame (with the same number of columns) where each row represents a liability class.
<code>dfreq</code>	A number in $[0, 1]$: The population frequency of the disease allele.

Value

An object of class `disModel`, which is a list with entries `chrom`, `penetrances` and `dfreq`.

See Also[lod\(\)](#)**Examples**

```
# Fully penetrant AD model:
m1 = diseaseModel(model = "AD")

# The above is equivalent to
m2 = diseaseModel(chrom = "Aut", penetrances = c(0,1,1), dfreq = 1e-5)
stopifnot(identical(m1, m2))

# X-linked recessive model:
m3 = diseaseModel(model = "XR", dfreq = 0.01)

# Long version of the above:
m4 = diseaseModel(chrom = "X", penetrances = list(male = c(0,1), female = c(0,0,1)),
                  dfreq = 0.01)
stopifnot(identical(m3, m4))
```

dominant1

Dominant linkage analysis example

Description

A dataset with SNP genotypes for 14 members of a pedigree affected with a dominant disorder.

Usage

```
dominant1
```

Format

A list with 3 elements:

- ped: A [pedtools::ped](#) object describing a pedigree with 19 individuals, including genotypes for 14 members at 248 markers on Chromosome 1.
- aff: A vector indicating the affected pedigree members.
- map: A data frame with 3 columns (chrom, marker, cm) describing the centiMorgan positions of the markers.

Examples

```

data(dominant1)
ped = dominant1$ped
aff = dominant1$aff
model = diseaseModel("AD")

# Compute singlepoint LODs
lods = lod(ped, aff = aff, model = model)

# LOD score graph
plot(lods)

```

linkres

S3 methods for class 'linkres'.

Description

Functions for printing, summarizing and plotting the results of a linkage analysis.

Usage

```

## S3 method for class 'linkres'
print(x, ...)

## S3 method for class 'linkres'
summary(object, ...)

## S3 method for class 'linkres'
plot(
  x,
  chrom = NULL,
  type = "l",
  lwd = NA,
  ylim = NULL,
  xlab = NULL,
  ylab = NULL,
  ...
)

## S3 method for class 'linkres'
points(x, chrom = NULL, type = "l", lwd = NA, ...)

```

Arguments

x, object A linkres object (normally produced by [lod\(\)](#) or [merlinLod\(\)](#)).

... further arguments.
chrom (Optional) A numeric indicating which chromosomes to be included in the plot.
lwd, type, ylim Graphical parameters passed on to plot().
xlab, ylab Axis labels.

Value

These functions are called for their side effects.

See Also

[lod\(\)](#), [merlinLod\(\)](#), [lodPeaks\(\)](#)

Examples

```
# Pedigree with 5 simulated SNP markers
x = nuclearPed(3)

x = setMarkers(x, alleleMatrix = cbind(
  m1 = c("1/1", "1/2", "1/2", "1/2", "1/2"),
  m2 = c("1/2", "1/2", "1/2", "1/2", "1/2"),
  m3 = c("1/1", "1/2", "1/2", "1/2", "1/1")), sep="/")

# Mother and all children affected
aff = c(1, 2, 2, 2, 2)

# LOD scores under autosomal dominant model
lods = lod(x, aff, model = diseaseModel(model = "AD"))

summary(lods)
as.data.frame(lods)
plot(lods)
```

lod

Singlepoint LOD score

Description

Calculates the singlepoint log of the odds (LOD) scores of a pedigree for the specified markers, assuming a fixed recombination rate between the disease and each marker locus.

Usage

```
lod(
  x,
  aff,
  model,
```

```

rho = 0,
liability = NULL,
markers = NULL,
maxOnly = NA,
loopBreakers = NULL,
peelOrder = NULL,
verbose = FALSE
)

```

Arguments

x	A ped object.
aff	A vector naming the affected pedigree members, or a numeric vector of length <code>pedsize(x)</code> with affection statuses for all pedigree members (2 = affected; 1 = unaffected; 0 = unknown). Alternatively, <code>aff</code> can be a list of vectors, named affected, unaffected and unknown. It suffices to give (any) two of these vectors.
model	A <code>disModel</code> object, typically created with <code>diseaseModel()</code> .
rho	A number between 0 and 0.5 (inclusive); the hypothesised recombination ratio between the marker and the disease locus.
liability	NULL (default) or a vector of length <code>pedsize(x)</code> indicating the liability class (a row number of <code>model\$penetrances</code>) of each individual.
markers	A vector of marker names or indices referring to markers attached to <code>x</code> . By default all markers are included.
maxOnly	a logical indicating whether only the maximum LOD score should be returned. By default this is always done if the number of markers is 1.
loopBreakers	A vector of ID labels indicating loop breakers. (Only relevant for inbred pedigrees.)
peelOrder	For internal use.
verbose	a logical: verbose output or not.

Details

The LOD score of a marker is defined as

$$LOD(\rho) = \log \frac{L(\rho)}{L(0.5)}$$

where the logarithms are base 10, and $L(\rho)$ denotes the likelihood of the observed marker genotypes given a recombination ratio ρ between the marker and the disease locus.

The likelihoods are computed with the **pedprobr** package.

Value

If the number of markers is 1, or if `maxOnly = TRUE`, a single number is returned.

Otherwise a `linkres` object, which is basically a data frame with columns CHROM, MARKER, MB and LOD.

Author(s)

Magnus Dehli Vigeland

See Also

[linkres](#), [merlinLod\(\)](#), [diseaseModel\(\)](#), [lodPeaks\(\)](#)

Examples

```
x = nuclearPed(2) |>
  addMarker(geno = c("1/2", "1/1", "1/2", "1/2"))

aff = c(2,1,2,2)
model = diseaseModel(model = "AD")

lod(x, aff, model)
```

lodPeaks	<i>LOD score peaks</i>
----------	------------------------

Description

Identify and summarise LOD score peaks.

Usage

```
lodPeaks(x, threshold, width = 1)

peakSummary(x, threshold, width = 1, physmap = NULL)
```

Arguments

x	A linkres object, or data frame with columns CHROM, MB, LOD.
threshold	A single number
width	A positive integer
physmap	A matrix or data frame with three columns: Marker name, chromosome and physical position.

Details

A peak is defined as a run of at least width consecutive markers with LOD score above or equal to threshold. If possible, one flanking marker is included on each side of the peak.

Value

A list of data frames.

See Also

[linkres](#), [lod\(\)](#), [merlinLod\(\)](#)

Examples

```
# Use built-in dataset `dominant1`
lods = lod(x = dominant1$ped,
          aff = dominant1$aff,
          model = diseaseModel("AD"))

# All peaks above LOD = 1.5
lodPeaks(lods, threshold = 1.5)
peakSummary(lods, threshold = 1.5)
```

merlinLod

Multipoint LOD scores by MERLIN

Description

This function is a wrapper for the parametric linkage functionality of the MERLIN software. For this to work, MERLIN must be installed and correctly pointed to in the PATH environment variable.

Usage

```
merlinLod(
  x,
  aff,
  model,
  map = NULL,
  markers = NULL,
  rho = 0,
  liability = NULL,
  maxOnly = NA,
  options = "",
  dir = tempdir(),
  cleanup = TRUE,
  verbose = FALSE,
  ...
)
```

Arguments

x A ped object.

aff A vector naming the affected pedigree members, or a numeric vector of length `pedsize(x)` with affection statuses for all pedigree members (2 = affected; 1 = unaffected; 0 = unknown). Alternatively, `aff` can be a list of vectors, named

	affected, unaffected and unknown. It suffices to give (any) two of these vectors.
model	A <code>disModel</code> object, typically created with <code>diseaseModel()</code> .
map	A data frame with columns according to MERLIN format for map files.
markers	A vector of marker names or indices referring to markers attached to <code>x</code> . By default all markers are included.
rho	A numeric with values between 0 and 0.5: The recombination value(s) for which the LOD score is computed. The value of <code>rho</code> is converted to centiMorgans using Haldane's map function and included in the MERLIN command using the <code>--position</code> parameter. Note: This parameter only works when <code>markers</code> has length 1.
liability	NULL (default) or a vector of length <code>pedsize(x)</code> indicating the liability class (a row number of <code>model\$penetrances</code>) of each individual.
maxOnly	a logical indicating whether only the maximum LOD score should be returned. By default this is always done if the number of markers is 1.
options	A character with additional options to the MERLIN command.
dir	Path to a directory where the MERLIN input files should be created.
cleanup	A logical indicating if MERLIN files should be removed after use. Default: TRUE.
verbose	a logical: verbose output or not.
...	Further arguments passed on to <code>pedprobr::merlin()</code> . In particular, <code>merlinpath</code> should be supplied if the merlin executables are not on the system's search path.

Details

By default the following MERLIN command is run (via a call to `system()`) after creating appropriate files in a temporary (or user specified) directory:

```
_merlin.freq --model _merlin.model --tabulate --markerNames --quiet
```

The resulting multipoint LOD scores are extracted from the output and returned in R as a `linkres` object.

Value

If the number of markers is 1, or if `maxOnly = TRUE`, a single number is returned.

Otherwise a `linkres` object similar to the output of `lod()`, but with an additional column CM.

References

<https://csg.sph.umich.edu/abecasis/merlin/>

See Also

[lod\(\)](#)

Examples

```
#-----  
# Requires MERLIN to be installed  
#-----  
  
if(pedprobr::checkMerlin()) {  
  
  # Pedigree with a single marker  
  x = nuclearPed(3, sex = c(1,2,2)) |>  
    addMarker(geno = c("1/1", "1/2", "1/2", "1/2", "1/2"))  
  
  # Simple AD model  
  merlinLod(x, aff = 2:5, model = diseaseModel("AD"))  
  
  # With liability classes  
  mod = diseaseModel("AD", penetrances = cbind(f0 = 0, f1 = 1:0, f2 = 1:0))  
  merlinLod(x, aff = 2:4, mod, liability = c(1,1,1,1,2))  
  
  # X  
  merlinLod(x, aff = 3:5, model = diseaseModel("XR"))  
  
}
```

Index

* datasets

- dominant1, 3

- diseaseModel, 2
- diseaseModel(), 6, 7, 9
- dominant1, 3

- linkres, 4, 7–9
- lod, 5
- lod(), 2–5, 8, 9
- lodPeaks, 7
- lodPeaks(), 5, 7

- merlinLod, 8
- merlinLod(), 4, 5, 7, 8

- peakSummary (lodPeaks), 7
- pedprobr::merlin(), 9
- pedtools::ped, 3
- plot.linkres (linkres), 4
- points.linkres (linkres), 4
- print.linkres (linkres), 4

- summary.linkres (linkres), 4
- system(), 9