

# Warnings and errors for the expl3 analysis tool

Vít Starý Novotný

2026-02-05

## Contents

<b>Introduction</b>	<b>4</b>
<b>1 Preprocessing</b>	<b>4</b>
No standard delimiters [W100] . . . . .	4
Unexpected delimiters [W101] . . . . .	5
Expl3 material in non-expl3 parts [E102] . . . . .	5
Line too long [S103] . . . . .	6
Multiple delimiters \ProvidesExpl* in a single file [E104] . . . . .	6
Needlessly ignored issue [S105] . . . . .	6
<b>2 Lexical analysis</b>	<b>6</b>
“Do not use” argument specifiers [W200] . . . . .	6
Unknown argument specifiers [E201] . . . . .	7
Deprecated control sequences [W202] . . . . .	7
Missing stylistic whitespaces [S204] . . . . .	7
Too many closing braces [E208] . . . . .	7
Invalid characters [E209] . . . . .	8
<b>3 Syntactic analysis</b>	<b>8</b>
Unexpected function call argument [E300] . . . . .	8
End of expl3 part within function call [E301] . . . . .	8
Unbraced n-type function call argument [W302] . . . . .	8
Braced N-type function call argument [W303] . . . . .	9
Unexpected parameter number [E304] . . . . .	9
Expanding an unexpandable variable or constant [T305] . . . . .	9
<b>4 Semantic analysis</b>	<b>10</b>
4.1 Functions and conditional functions . . . . .	10
Unused private function [W401] . . . . .	10
Unused private function variant [W402] . . . . .	10
Function variant of incompatible type [T403] . . . . .	11
Protected predicate function [E404] . . . . .	11
Function variant for an undefined function [E405] . . . . .	11

Calling an undefined function [E408] . . . . .	12
Function variant of deprecated type [W410] . . . . .	12
Indirect function definition from an undefined function [E411] . . . . .	13
Malformed function name [S412] . . . . .	14
4.2 Variables and constants . . . . .	15
Malformed variable or constant name [S413] . . . . .	15
Malformed quark or scan mark name [S414] . . . . .	16
Unused variable or constant [W415] . . . . .	16
Setting an undeclared variable [W416] . . . . .	17
Setting a variable as a constant [E417] . . . . .	17
Setting a constant [E418] . . . . .	17
Using an undeclared variable or constant [W419] . . . . .	17
Locally setting a global variable [E420] . . . . .	18
Globally setting a local variable [E421] . . . . .	18
Using a variable of an incompatible type [T422] . . . . .	18
4.3 Messages . . . . .	23
Unused message [W423] . . . . .	23
Using an undefined message [E424] . . . . .	24
Incorrect parameters in message text [E425] . . . . .	24
Incorrect number of arguments supplied to message [W426] . . . . .	24
4.4 Sorting . . . . .	25
Comparison conditional without signature :nnTF [E427] . . . . .	25
<b>5 Flow analysis</b>	<b>25</b>
5.1 Functions and conditional functions . . . . .	25
Multiply defined function [E500] . . . . .	25
Multiply defined function variant [W501] . . . . .	27
Unused private function [W502] . . . . .	28
Unused private function variant [W503] . . . . .	28
Function variant for an undefined function [E504] . . . . .	29
Calling an undefined function [E505] . . . . .	30
Indirect function definition from an undefined function [E506] . . . . .	31
Setting a function before definition [W507] . . . . .	32
Unexpandable or restricted-expandable boolean expression [E508] . . . . .	33
Expanding an unexpandable function [E509] . . . . .	33
Fully-expanding a restricted-expandable function [E510] . . . . .	34
Defined an expandable function as protected [W511] . . . . .	34
Defined an unexpandable function as unprotected [W512] . . . . .	35
Conditional function with no return value [E513] . . . . .	35
Comparison code with no return value [E514] . . . . .	36
Paragraph token in the parameter of a "nopar" function [E515] . . . . .	36
5.2 Variables and constants . . . . .	37
Unused variable or constant [W516] . . . . .	37
Setting an undeclared variable [E517] . . . . .	37
Using an undeclared variable or constant [W518] . . . . .	37
Multiply declared variable or constant [E519] . . . . .	38

5.3	Messages	38
	Unused message [W520]	38
	Using an undefined message [E521]	38
	Incorrect number of arguments supplied to message [W522]	39
	Multiply defined message [E523]	39
5.4	Input–output streams	40
	Using an unopened or closed stream [E524]	40
	Multiply opened stream [E525]	40
	Unclosed stream [W526]	40
5.5	Piecewise token list construction	41
	Building on a regular token list [T527]	41
	Using a semi-built token list [T528]	41
	Multiply started building a token list [E529]	42
	Unfinished semi-built token list [W530]	42
	<b>Caveats</b>	<b>43</b>
	<b>References</b>	<b>45</b>
	<b>Index</b>	<b>46</b>

# Introduction

In this document, I list the warnings and errors for the different processing steps of the expl3 linter [1]:

**Preprocessing** Determine which parts of the input files contain expl3 code.

**Lexical analysis** Convert expl3 parts of the input files into  $\text{\TeX}$  tokens.

**Syntactic analysis** Convert  $\text{\TeX}$  tokens into a tree of function calls.

**Semantic analysis** Determine the meaning of the different function calls.

**Flow analysis** Determine additional emergent properties of the code.

For each warning and error, I specify a unique identifier that can be used to disable the warning or error, a description of the condition for the warning or error, and a code example that demonstrates the condition and serves as a test case for the linter.

Warnings and errors have different types that decides the prefix of their identifiers:

- Warnings:  
S : Style warnings  
W : Other warnings
- Errors:  
T : Type errors  
E : Other errors

Issues that are planned but not yet implemented are grayed out.

## 1 Preprocessing

In the preprocessing step, the expl3 analysis tool determines which parts of the input files contain expl3 code. Inline  $\text{\TeX}$  comments that disable warnings and errors are also analyzed in this step.

### No standard delimiters [W100]

An input file contains no delimiters such as `\ExplSyntaxOn`, `\ExplSyntaxOff`, `\ProvidesExplPackage`, `\ProvidesExplClass`, and `\ProvidesExplFile` [2, Section 2.1]. The analysis tool should assume that the whole input file is in expl3.

```

1  % file-wide warning
2  \tl_new:N
3    \g_example_tl
4  \tl_gset:Nn
5    \g_example_tl
6    { Hello,~ }
7  \tl_gput_right:Nn
8    \g_example_tl
9    { world! }
10 \tl_use:N
11   \g_example_tl

```

## Unexpected delimiters [W101]

An input file contains extraneous \ExplSyntaxOn delimiters [2, Section 2.1] in expl3 parts or extraneous \ExplSyntaxOff delimiters in non-expl3 parts.

```

1  \input expl3-generic
2  \ExplSyntaxOff % warning on this line
3  \ExplSyntaxOn
4  \tl_new:N
5    \g_example_tl
6  \tl_gset:Nn
7    \g_example_tl
8    { Hello,~ }
9  \ExplSyntaxOn % warning on this line
10 \tl_gput_right:Nn
11   \g_example_tl
12   { world! }
13 \tl_use:N
14   \g_example_tl

```

## Expl3 material in non-expl3 parts [E102]

An input file contains what looks like expl3 material [2, Section 1.1] in non-expl3 parts.

```

1  \ProvidesExplFile{example.tex}{2024-04-09}{1.0.0}{An example
  ↳  file}
2  \tl_new:N
3    \g_example_tl
4  \tl_gset:Nn
5    \g_example_tl
6    { Hello,~ }
7  \tl_gput_right:Nn
8    \g_example_tl
9    { world! }

```

```
10  \ExplSyntaxOff
11  \tl_use:N % error on this line
12  \g_example_tl % error on this line
```

## Line too long [S103]

Some lines in expl3 parts are longer than 80 characters [3, Section 2].

- 1 This line is not very long, because it is 80 characters long, not  
→ 81 characters.
- 2 This line is overly long, because it is 81 characters long  
→ excluding the comment. % warning on this line
- 3 This line is not very long, because it is 80 characters long,  
→ comments excluded. % no warning on this line

The maximum line length can be configured using the command-line option `--max-line-length` or with the Lua option `max_line_length`.

## Multiple delimiters \ProvidesExpl\* in a single file [E104]

An input file contains multiple delimiters `\ProvidesExplPackage`, `\ProvidesExplClass`, and `\ProvidesExplFile`.

```
1 \ProvidesExplPackage
2   {example.sty}{2024-04-09}{1.0.0}{An example package}
3 \ExplSyntaxOff
4 \ProvidesExplClass % error on this line
5   {example.cls}{2024-04-09}{1.0.0}{An example class}
```

## Needlessly ignored issue [S105]

An input file contains `% noqa` comments with needlessly ignored issues.

```
1 % warning on the following line
2 There is no issue here. % noqa: e123
```

## 2 Lexical analysis

In the lexical analysis step, the expl3 analysis tool converts the expl3 parts of the input files into a list of `TeX` tokens.

## “Do not use” argument specifiers [W200]

Some control sequence tokens correspond to functions with `D` (do not use) argument specifiers.

```

1 \tex_space:D % warning on this line
2 \tex_italiccorr^3aD % warning on this line
3 \tex_hyphen^zD % warning on this line
4 \tex_let:^^44 % warning on this line

```

The above example has been taken from The L<sup>A</sup>T<sub>E</sub>X Project [2, Chapter 24].

## Unknown argument specifiers [E201]

Some control sequence tokens correspond to functions with unknown argument specifiers. [2, Section 1.1]

```

1 \cs_new:Nn
2   \example:bar % error on this line
3   { foo }
4   { bar }
5   { baz }

```

## Deprecated control sequences [W202]

Some control sequence tokens correspond to deprecated expl3 control sequences from `13obsolete.txt` [5].

```

1 \str_lower_case:n % warning on this line
2   { FOO BAR }

```

## Missing stylistic whitespaces [S204]

Some control sequences and curly braces are not surrounded by whitespaces [4, Section 6, 3, Section 3].

```

1 \cs_new:Npn \foo_bar:Nn #1#2
2 {
3   \cs_if_exist:NTF#1 % warning on this line
4   { \__foo_bar:n {#2} }
5   { \__foo_bar:nn{#2}{literal} } % warning on this line
6 }

```

## Too many closing braces [E208]

An expl3 part of the input file contains too many closing braces.

```

1 \tl_new:N
2   \g_example_tl
3 \tl_gset:Nn
4   \g_example_tl
5   { Hello,~ } } % error on this line

```

## Invalid characters [E209]

An expl3 part of the input file contains invalid characters.

```
1  ^~7f  % error on this line
2  \fo^~?o % error on this line
```

## 3 Syntactic analysis

In the syntactic analysis step, the expl3 analysis tool converts the list of TeX tokens into a tree of function calls.

## Unexpected function call argument [E300]

A function is called with an unexpected argument.

```
1  \cs_new:Nn
2  { unexpected } % error on this line
3  \l_tmpa_tl
```

Partial applications are detected by analysing closing braces (}) and do not produce an error:

```
1  \cs_new:Nn
2  \example_foo:n
3  { foo~#1 }
4  \cs_new:Nn
5  \example_bar:
6  { \example_foo:n }
7  \cs_new:Nn
8  \example_baz:
9  {
10  \example_bar:
11  { bar }
12 }
```

## End of expl3 part within function call [E301]

A function call is cut off by the end of a file or an expl3 part of a file:

```
1  \cs_new:Nn % error on this line
2  \example_foo:n
```

## Unbraced n-type function call argument [W302]

An n-type function call argument is unbraced:

```

1  \tl_set:Nn
2    \l_tmpa_tl
3    \l_tmpb_tl  % warning on this line

```

Depending on the specific function, this may or may not be an error.

## Braced N-type function call argument [W303]

An N-type function call argument is braced:

```

1  \cs_new:Nn
2    { \example_foo:n }  % warning on this line
3    { bar }

```

Depending on the specific function, this may or may not be an error.

## Unexpected parameter number [E304]

A parameter or replacement text contains parameter tokens (#) followed by unexpected numbers:

```

1  \cs_new:Npn
2    \example_foo:nnn
3    #1#2#9  % error on this line
4    { foo~#1 }

1  \cs_new:Npn
2    \example_foo:nnn
3    #1#2#3
4    { foo~#4 }  % error on this line

```

## Expanding an unexpandable variable or constant [T305]

A function with a V-type argument is called with a variable or constant that does not support V-type expansion [2, Section 1.1].

```

1  \cs_new:Nn
2    \module_foo:n
3    { #1 }
4  \cs_generate_variant:Nn
5    \module_foo:n
6    { V, v }
7  \module_foo:V
8    \c_false_bool  % error on this line
9  \module_foo:v
10   { c_false_bool }  % error on this line

```

## 4 Semantic analysis

In the semantic analysis step, the expl3 analysis tool determines the meaning of the different function calls.

### 4.1 Functions and conditional functions

#### Unused private function [W401]

A private function or conditional function is defined but unused.

```
1 \cs_new:Nn % warning on this line
2   \__module_foo:
3   { bar }

1 \prg_new_conditional:Nnn % warning on this line
2   \__module_foo:
3   { p, T, F, TF }
4   { \prg_return_true: }
```

#### Unused private function variant [W402]

A private function or conditional function variant is defined but unused.

```
1 \cs_new:Nn
2   \__module_foo:n
3   { bar~#1 }
4 \cs_generate_variant:Nn % warning on this line
5   \__module_foo:n
6   { V }
7 \__module_foo:n
8   { baz }

1 \prg_new_conditional:Nnn
2   \__module_foo:n
3   { p, T, F, TF }
4   { \prg_return_true: }
5 \prg_generate_conditional_variant:Nnn % warning on this line
6   \__module_foo:n
7   { V }
8   { TF }
9 \__module_foo:nTF
10  { foo }
11  { bar }
12  { baz }
```

### Function variant of incompatible type [T403]

A function or conditional function variant is generated from an incompatible argument type [2, Section 5.2, documentation of function `\cs_generate_variant:Nn`].

```
1  \cs_new:Nn
2    \module_foo:Nn
3    { bar }
4  \cs_generate_variant:Nn
5    \module_foo:Nn
6    { Nnn } % error on this line
```

Higher-order variants can be created from existing variants as long as only `n` and `N` arguments are changed to other types:

```
1  \cs_new:Nn
2    \module_foo:Nn
3    { bar }
4  \cs_generate_variant:Nn
5    \module_foo:Nn
6    { cn }
7  \cs_generate_variant:Nn
8    \module_foo:cn
9    { cx }
10 \cs_generate_variant:Nn
11   \module_foo:cx
12   { Ne } % error on this line
```

### Protected predicate function [E404]

A protected predicate function is defined.

```
1  \prg_new_protected_conditional:Nnn
2    \module_foo:
3    { p }
4    { \prg_return_true: }
```

### Function variant for an undefined function [E405]

A function or conditional function variant is defined for an undefined function.

```
1  \cs_new:Nn
2    \module_foo:n
3    { bar }
4  \cs_generate_variant:Nn
5    \module_bar:n % error on this line
6    { V }
```

```

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F }
4    { \prg_return_true: }
5  \prg_generate_conditional_variant:Nnn
6    \module_bar:n % error on this line
7    { V }
8    { T }
9  \prg_generate_conditional_variant:Nnn
10   \module_foo:n % error on this line
11   { V }
12   { TF }

```

### Calling an undefined function [E408]

A function or conditional function (variant) is called but undefined.

```

1  \module_foo: % error on this line

1  \cs_new:Nn
2    \module_foo:n
3    { bar~#1 }
4  \tl_set:Nn
5    \l_tmpa_tl
6    { baz }
7  \module_foo:V % error on this line
8    \l_tmpa_tl

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \prg_generate_conditional_variant:Nnn
6    \module_foo:n
7    { V }
8    { T }
9  \module_foo:VTF % error on this line
10   \l_tmpa_tl
11   { foo }
12   { bar }

```

### Function variant of deprecated type [W410]

A function or conditional function variant is generated from a deprecated argument type [2, Section 5.2, documentation of function `\cs_generate_variant:Nn`].

```
1  \cs_new:Nn
```

```

2   \module_foo:Nn
3   { bar }
4 \cs_generate_variant:Nn
5   \module_foo:Nn
6   { nn } % warning on this line
7 \cs_generate_variant:Nn
8   \module_foo:Nn
9   { NN } % warning on this line
10 \cs_generate_variant:Nn
11   \module_foo:Nn
12   { vc } % warning on this line

```

### Indirect function definition from an undefined function [E411]

A function or conditional function is indirectly defined from an undefined function.

```

1 \cs_new:Nn
2   \module_foo:n
3   { bar~#1 }
4 \cs_new_eq:NN
5   \module_bar:n
6   \module_foo:n
7 \cs_new_eq:NN
8   \module_baz:n
9   \module_bar:n
10 \module_baz:n
11   { foo }

1 \prg_new_conditional:Nnn
2   \module_foo:n
3   { p, T, F, TF }
4   { \prg_return_true: }
5 \cs_new_eq:NN
6   \module_bar:nTF
7   \module_foo:nTF
8 \cs_new_eq:NN
9   \module_baz:nTF
10  \module_bar:nTF
11 \module_baz:nTF
12   { foo }
13   { bar }
14   { baz }

1 \cs_new:Nn
2   \module_foo:n
3   { bar~#1 }
4 \cs_new_eq:NN % error on this line

```

```

5   \module_baz:n
6   \module_bar:n
7 \module_baz:n
8   { foo }

1 \prg_new_conditional:Nnn
2   \module_foo:n
3   { p, T, F, TF }
4   { \prg_return_true: }
5 \cs_new_eq:NN % error on this line
6   \module_baz:nTF
7   \module_bar:nTF
8 \module_baz:nTF
9   { foo }
10  { bar }
11  { baz }

```

### Malformed function name [S412]

Some function have names that are not in the format  $\langle module \rangle \_ \langle description \rangle : \langle arg-spec \rangle$  [4, Section 3.2].

```

1 \cs_new:Nn
2   \description: % warning on this line
3   { foo }

1 \cs_gset:Npn
2   \module__description: % warning on this line
3   { foo }

1 \cs_new:Nn
2   \example_foo:
3   { bar }
4 \cs_set_eq:NN
5   \module_description: % warning on this line
6   \example_foo:

1 \cs_generate_from_arg_count:NNnn
2   \__module_description:
3   \cs_new:Npn
4   { 0 }
5   { foo }

```

This also extends to conditional functions:

```

1 \prg_new_conditional:Nn
2   \description: % warning on this line
3   { p, T, F, TF }
4   { foo }

```

```

1  \prg_gset_conditional:Npn
2    \module__description: % warning on this line
3    { p, T, F, TF }
4    { foo }

1  \prg_new_conditional:Nnn
2    \example_foo:
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \prg_set_eq_conditional:NNn
6    \module_description: % warning on this line
7    \example_foo:
8    { p, T, F, TF }

```

Furthermore, this also extends to function variants:

```

1  \cs_new:Nn
2    \example:n % warning on this line
3    { #1 }
4  \cs_generate_variant:Nn
5    \example:n % warning on this line
6    { e, x, V }

```

## 4.2 Variables and constants

### Malformed variable or constant name [S413]

Some expl3 variables and constants have names that are not in the format `\langle scope\rangle_\langle module\rangle_\langle description\rangle_\langle type\rangle` [4, Section 3.2].

```

1  \tl_new:N
2    \g_description_tl % warning on this line
3  \box_use:N
4    \l_description_box % warning on this line
5  \int_const:Nn
6    \c_description % warning on this line
7    { 123 }

1  \regex_new:N
2    \g_module_description_regex
3  \coffin_new:N
4    \l_module_description_coffin
5  \str_const:Nn
6    \c_module_description_str
7    { foo }

1  \tl_use:N
2    \l_tmpa_tl

```

```

3  \int_gset:Nn
4    \g_tmpb_int
5    { 1 + 2 }
6  \str_show:N
7    \g_tmpa_str
8  \bool_set_true:N
9    \l_tmpa_bool

```

### Malformed quark or scan mark name [S414]

Some expl3 quarks and scan marks have names that do not start with `\q_` and `\s_`, respectively [4, Chapter 19].

```

1  \quark_new:N
2    \foo_bar  % warning on this line

1  \quark_new:N
2    \q_foo_bar

1  \scan_new:N
2    \foo_bar  % error on this line

1  \scan_new:N
2    \s_foo_bar

```

### Unused variable or constant [W415]

A variable or a constant is declared and perhaps defined but unused.

```

1  \tl_new:N
2    \g_declared_but_undefined_tl  % warning on this line

1  \tl_new:N
2    \g_defined_but_unused_tl  % warning on this line
3  \tl_gset:Nn
4    \g_defined_but_unused_tl
5    { foo }

1  \tl_new:N
2    \g_defined_and_used_tl
3  \tl_gset:Nn
4    \g_defined_and_used_tl
5    { foo }
6  \tl_use:N
7    \g_defined_and_used_tl

1  \tl_const:Nn
2    \c_defined_but_unused_tl  % warning on this line
3    { foo }

```

```
1  \tl_const:Nn
2    \c_defined_and_used_tl
3    { foo }
4  \tl_use:N
5    \c_defined_and_used_tl
```

### Setting an undeclared variable [W416]

An undeclared variable is set.

```
1  \tl_gset:Nn
2    \g_example_tl  % warning on this line
3    { bar }
```

### Setting a variable as a constant [E417]

A variable is set as though it were a constant.

```
1  \tl_const:Nn
2    \g_example_tl  % error on this line
3    { bar }
```

### Setting a constant [E418]

A constant is set.

```
1  \tl_gset:Nn
2    \c_example_tl  % error on this line
3    { bar }
```

### Using an undeclared variable or constant [W419]

A variable or constant is used but undeclared or undefined.

```
1  \tl_use:N
2    \g_undeclared_tl  % error on this line

1  \tl_new:N
2    \g_declared_but_undefined_tl
3  \tl_use:N
4    \g_declared_but_undefined_tl

1  \tl_new:N
2    \g_defined_tl
3  \tl_gset:Nn
4    \g_defined_tl
5    { foo }
6  \tl_use:N
7    \g_defined_tl
```

```

1  \tl_use:N
2    \c_undefined_tl  % error on this line

1  \tl_const:Nn
2    \c_defined_tl
3    { foo }
4  \tl_use:N
5    \c_defined_tl

```

### Locally setting a global variable [E420]

A global variable is locally set.

```

1  \tl_new:N
2    \g_example_tl
3  \tl_set:Nn  % error on this line
4    \g_example_tl
5    { foo }

```

### Globally setting a local variable [E421]

A local variable is globally set.

```

1  \tl_new:N
2    \l_example_tl
3  \tl_gset:Nn  % error on this line
4    \l_example_tl
5    { foo }

```

### Using a variable of an incompatible type [T422]

A variable of one type is used where a variable of a different type should be used.

```

1  \tl_new:N  % error on this line
2    \l_example_str
3  \str_new:N  % error on this line
4    \l_example_tl

1  \tl_new:N
2    \l_example_tl
3  \tl_count:N
4    \l_example_tl
5  \str_count:N
6    \l_example_tl
7  \seq_count:N  % error on this line
8    \l_example_tl
9  \clist_count:N
10   \l_example_tl

```

```

11  \prop_count:N % error on this line
12    \l_example_tl
13 \intarray_count:N % error on this line
14    \l_example_tl
15 \fparray_count:N % error on this line
16    \l_example_tl

1 \str_new:N
2   \l_example_str
3 \tl_count:N
4   \l_example_str
5 \str_count:N
6   \l_example_str
7 \seq_count:N % error on this line
8   \l_example_str
9 \clist_count:N % error on this line
10   \l_example_str
11 \prop_count:N % error on this line
12   \l_example_str
13 \intarray_count:N % error on this line
14   \l_example_str
15 \fparray_count:N % error on this line
16   \l_example_str

1 \int_new:N
2   \l_example_int
3 \tl_count:N % error on this line
4   \l_example_int
5 \str_count:N % error on this line
6   \l_example_int
7 \seq_count:N % error on this line
8   \l_example_int
9 \clist_count:N % error on this line
10   \l_example_int
11 \prop_count:N % error on this line
12   \l_example_int
13 \intarray_count:N % error on this line
14   \l_example_int
15 \fparray_count:N % error on this line
16   \l_example_int

1 \seq_new:N
2   \l_example_seq
3 \tl_count:N % error on this line
4   \l_example_seq
5 \str_count:N % error on this line
6   \l_example_seq

```

```

7  \seq_count:N
8    \l_example_seq
9 \clist_count:N % error on this line
10   \l_example_seq
11 \prop_count:N % error on this line
12   \l_example_seq
13 \intarray_count:N % error on this line
14   \l_example_seq
15 \fparray_count:N % error on this line
16   \l_example_seq

1 \clist_new:N
2   \l_example_clist
3 \tl_count:N
4   \l_example_clist
5 \str_count:N % error on this line
6   \l_example_clist
7 \seq_count:N % error on this line
8   \l_example_clist
9 \clist_count:N
10   \l_example_clist
11 \prop_count:N % error on this line
12   \l_example_clist
13 \intarray_count:N % error on this line
14   \l_example_clist
15 \fparray_count:N % error on this line
16   \l_example_clist

1 \clist_new:N % error on this line
2   \l_example_prop
3 \tl_count:N % error on this line
4   \l_example_prop
5 \str_count:N % error on this line
6   \l_example_prop
7 \seq_count:N % error on this line
8   \l_example_prop
9 \clist_count:N % error on this line
10   \l_example_prop
11 \prop_count:N
12   \l_example_prop
13 \intarray_count:N % error on this line
14   \l_example_prop
15 \fparray_count:N % error on this line
16   \l_example_prop

1 \intarray_new:Nn
2   \g_example_intarray

```

```

3      { 5 }
4  \tl_count:N % error on this line
5      \g_example_intarray
6  \str_count:N % error on this line
7      \g_example_intarray
8  \seq_count:N % error on this line
9      \g_example_intarray
10 \clist_count:N % error on this line
11      \g_example_intarray
12 \prop_count:N % error on this line
13      \g_example_intarray
14 \intarray_count:N
15      \g_example_intarray
16 \fpararray_count:N % error on this line
17      \g_example_intarray

1 \fpararray_new:Nn
2      \g_example_fpararray
3      { 5 }
4  \tl_count:N % error on this line
5      \g_example_fpararray
6  \str_count:N % error on this line
7      \g_example_fpararray
8  \seq_count:N % error on this line
9      \g_example_fpararray
10 \clist_count:N % error on this line
11      \g_example_fpararray
12 \prop_count:N % error on this line
13      \g_example_fpararray
14 \intarray_count:N % error on this line
15      \g_example_fpararray
16 \fpararray_count:N
17      \g_example_fpararray

1 \ior_new:N
2      \l_example_ior
3  \iow_open:Nn % error on this line
4      \l_example_ior
5      { example }

1 \clist_new:N
2      \l_example_clist
3  \tl_set:Nn
4      \l_tmpa_tl
5      { foo }
6  \clist_set_eq:NN % error on this line
7      \l_example_clist
8      \l_tmpa_tl

```

```

1  \tl_set:Nn
2    \l_tmpa_tl
3    { foo }
4  \seq_set_from_clist:NN % error on this line
5    \l_tmpa_seq
6    \l_tmpa_tl

1  \tl_set:Nn
2    \l_tmpa_tl
3    { foo }
4  \regex_set:Nn
5    \l_tmpa_regex
6    { foo }
7  \int_set:Nn
8    \l_tmpa_int
9    { 1 + 2 }
10 \regex_show:N % error on this line
11   \l_tmpa_tl
12 \regex_show:N
13   \l_tmpa_regex
14 \regex_show:N % error on this line
15   \l_tmpa_int

1  \tl_set:Nn
2    \l_tmpa_tl
3    { foo }
4  \int_set_eq:NN % error on this line
5    \l_tmpa_int
6    \l_tmpa_tl

1  \str_new:N
2    \l_example_str
3  \tl_const:Nn
4    \c_example_tl
5    { foo }
6  \str_set_eq:NN % error on this line
7    \l_example_str
8    \c_example_tl

1  \tl_new:N
2    \l_example_tl
3  \str_new:N
4    \l_example_str
5  \str_set:Nn
6    \l_example_str
7    { foo }
8  \tl_set_eq:NN
9    \l_example_tl

```

```

10      \l_example_str
11  \str_set_eq:NN
12      \l_example_tl
13      \l_example_str
14  \tl_set_eq:NN % error on this line
15      \l_example_str
16      \l_example_tl
17  \str_set_eq:NN % error on this line
18      \l_example_str
19      \l_example_tl

1  \str_set_eq:NN % error on this line
2      \l_example_tl
3      \l_example_tl
4  \tl_set_eq:NN % error on this line
5      \l_example_str
6      \l_example_str

1  \seq_set_from_clist:NN
2      \l_tmpa_seq
3      \l_tmpa_clist
4  \seq_set_from_clist:NN % error on this line
5      \l_tmpa_seq
6      \l_tmpa_tl
7  \seq_set_from_clist:NN % error on this line
8      \l_tmpa_seq
9      \l_tmpa_seq
10 \clist_set_from_seq:NN
11      \l_tmpa_clist
12      \l_tmpa_seq
13 \clist_set_from_seq:NN % error on this line
14      \l_tmpa_clist
15      \l_tmpa_int

```

### 4.3 Messages

#### Unused message [W423]

A message is defined but unused.

```

1  \msg_new:nnn % warning on this line
2      { foo }
3      { bar }
4      { baz }

1  \msg_new:nnn
2      { bar }
3      { bar }

```

```
4  { baz }
5  \msg_info:nn
6  { bar }
7  { bar }
```

### Using an undefined message [E424]

A message is used but undefined.

```
1 \msg_info:nnn % error on this line
2 { foo }
3 { bar }
4 { baz }
```

### Incorrect parameters in message text [E425]

Parameter tokens other than #1, #2, #3, and #4 are specified in a message text.

```
1 \msg_new:nnn
2 { foo }
3 { bar }
4 { #5 } % error on this line

1 \msg_new:nnnn
2 { foo }
3 { bar }
4 { #5~#6 } % two errors on this line
5 { #6~#7 } % two errors on this line

1 \msg_new:nnnn
2 { foo }
3 { bar }
4 { #1~#2 }
5 { #3~#4 }
```

### Incorrect number of arguments supplied to message [W426]

A message was supplied fewer or more arguments than there are parameters in the message text.

```
1 \msg_new:nnn
2 { foo }
3 { bar }
4 { #1~#2 }
5 \msg_info:nn % warning on this line
6 { foo }
7 { bar }
8 \msg_info:nnn % warning on this line
```

```

9   { foo }
10  { bar }
11  { foo }
12 \msg_info:nnnn
13  { foo }
14  { bar }
15  { foo }
16  { bar }
17 \msg_info:nnnnn % warning on this line
18  { foo }
19  { bar }
20  { foo }
21  { bar }
22  { baz }

```

## 4.4 Sorting

**Comparison conditional without signature :nnTF [E427]**

A sorting function is called with a conditional that has a signature different than :nnTF [2, Section 15.5.4].

```

1 \cs_new:Nn
2   \example_foo:
3   { \prg_return_true: }
4 \tl_sort:nN
5   { { foo } { bar } }
6   \example_foo:nnT % error on this line

1 \cs_new:Nn
2   \example_foo:
3   { \prg_return_true: }
4 \tl_sort:nN
5   { { foo } { bar } }
6   \example_foo:nnTF

```

## 5 Flow analysis

In the flow analysis step, the expl3 analysis tool determines compiler-theoretic properties of functions, such as expandability, and variables, such as reaching definitions.

### 5.1 Functions and conditional functions

**Multiply defined function [E500]**

A function or conditional function is defined multiple times.

```

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_new:Nn % error on this line
5    \module_foo:
6    { bar }

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_undefine:N
5    \module_foo:
6  \cs_new:Nn
7    \module_foo:
8    { bar }

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_gset:Nn
5    \module_foo:
6    { bar }

\prg_new_if:nNnn
1  \module_foo:
2  { p, T, F, TF }
3  { \prg_return_true: }
\prg_new_if:nNnn % error on this line
1  \module_foo:
2  { p, T, F, TF }
3  { \prg_return_true: }

\prg_new_if:nNnn
1  \module_foo:
2  { p, T, F, TF }
3  { \prg_return_true: }
\cs_undefine:N
1  \module_foo_p:
\cs_undefine:N
1  \module_foo:T
\cs_undefine:N
1  \module_foo:F
\cs_undefine:N
1  \module_foo:TF
\prg_new_if:nNnn
1  \module_foo:
2  { p, T, F, TF }
3  { \prg_return_true: }

```

```

1  \prg_new_conditional:Nnn
2    \module_foo:
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \prg_gset_conditional:Nnn
6    \module_foo:
7    { p, T, F, TF }
8    { \prg_return_true: }

```

### Multiply defined function variant [W501]

A function or conditional function variant is defined multiple times.

```

1  \cs_new:Nn
2    \module_foo:n
3    { bar~#1 }
4  \cs_generate_variant:Nn
5    \module_foo:n
6    { V }
7  \cs_generate_variant:Nn % warning on this line
8    \module_foo:n
9    { o, V }

1  \cs_new:Nn
2    \module_foo:n
3    { bar~#1 }
4  \cs_generate_variant:Nn
5    \module_foo:n
6    { V }
7  \cs_undefine:N
8    \module_foo:V
9  \cs_generate_variant:Nn
10   \module_foo:n
11   { o, V }

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \prg_generate_conditional_variant:Nnn
6    \module_foo:n
7    { V }
8    { TF }
9  \prg_generate_conditional_variant:Nnn % warning on this line
10   \module_foo:n
11   { o, V }
12   { TF }

```

```

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \prg_generate_conditional_variant:Nnn
6    \module_foo:n
7    { V }
8    { TF }
9  \cs_undefine:N
10   \module_foo:VTF
11 \prg_generate_conditional_variant:Nnn
12   \module_foo:n
13   { o, V }
14   { TF }

```

### Unused private function [W502]

A private function or conditional function is defined but all its calls are unreachable.<sup>1</sup>

```

1  \cs_new:Nn  % warning on this line
2    \__module_foo:
3    { bar }
4  \cs_new:Nn
5    \__module_baz:
6    { \__module_foo: }

```

This check is a stronger version of W401 and should only be emitted if W401 has not previously been emitted for this function.

### Unused private function variant [W503]

A private function or conditional function variant is defined but all its calls are unreachable.

```

1  \cs_new:Nn
2    \__module_foo:n
3    { bar~#1 }
4  \cs_new:Nn
5    \__module_baz:
6    {
7      \tl_set:Nn
8      \l_tmpa_tl
9      { baz }

```

---

<sup>1</sup>Code is unreachable if it is only reachable through private functions which are either unused or also unreachable.

```

10      \_\_module\_foo:V
11          \l_tmpa_t1
12      }
13 \cs_generate_variant:Nn % warning on this line
14     \_\_module\_foo:n
15     { V }
16 \_\_module\_foo:n
17     { baz }

```

This check is a stronger version of W402 and should only be emitted if W402 has not previously been emitted for this function variant.

#### Function variant for an undefined function [E504]

A function or conditional function variant is defined before the base function has been defined or after it has been undefined.

```

1 \cs_new:Nn
2     \module_foo:n
3     { bar }
4 \cs_generate_variant:Nn
5     \module_foo:n
6     { V }

1 \cs_generate_variant:Nn % error on this line
2     \module_foo:n
3     { V }
4 \cs_new:Nn
5     \module_foo:n
6     { bar }

1 \cs_new:Nn
2     \module_foo:n
3     { bar }
4 \cs_undefine:N
5     \module_foo:n
6 \cs_generate_variant:Nn % error on this line
7     \module_foo:n
8     { V }

1 \prg_new_conditional:Nnn
2     \module_foo:n
3     { p, T, F, TF }
4     { \prg_return_true: }
5 \prg_generate_conditional_variant:Nnn
6     \module_foo:n
7     { V }
8     { TF }

```

```

1  \prg_generate_conditional_variant:Nnn  % error on this line
2    \module_foo:n
3    { V }
4    { TF }
5  \prg_new_conditional:Nnn
6    \module_foo:n
7    { p, T, F, TF }
8    { \prg_return_true: }

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F, TF }
4    { \prg_return_true: }
5  \cs_undefine:N
6    \module_foo:nTF
7  \prg_generate_conditional_variant:Nnn  % error on this line
8    \module_foo:n
9    { V }
10   { TF }

```

This check is a stronger version of E405 and should only be emitted if E405 has not previously been emitted for this function variant.

### Calling an undefined function [E505]

A function or conditional function (variant) is called before it has been defined or after it has been undefined.

```

1  \module_foo:  % error on this line
2  \cs_new:Nn
3    \module_foo:
4    { bar }

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_undefine:N
5    \module_foo:
6  \module_foo:  % error on this line

1  \cs_new:Nn
2    \module_foo:n
3    { bar~#1 }
4  \tl_set:Nn
5    \l_tmpa_tl
6    { baz }
7  \module_foo:V  % error on this line
8    \l_tmpa_tl

```

```

9  \cs_generate_variant:Nn
10   \module_foo:n
11   { V }

```

This check is a stronger version of E408 and should only be emitted if E408 has not previously been emitted for this function.

### Indirect function definition from an undefined function [E506]

A function or conditional function is indirectly defined from a function that has yet to be defined or after it has been undefined.

```

1  \cs_new:Nn
2   \module_foo:n
3   { bar~#1 }
4  \cs_new_eq:NN  % error on this line
5   \module_baz:n
6   \module_bar:n
7  \cs_new_eq:NN
8   \module_bar:n
9   \module_foo:n
10 \module_baz:n
11 { foo }

1  \cs_new:Nn
2   \module_foo:n
3   { bar~#1 }
4  \cs_new_eq:NN
5   \module_bar:n
6   \module_foo:n
7  \cs_undefine:N
8   \module_bar:n
9  \cs_new_eq:NN  % error on this line
10  \module_baz:n
11  \module_bar:n
12 \module_baz:n
13 { foo }

1  \prg_new_conditional:Nnn
2   \module_foo:n
3   { p, T, F, TF }
4   { \prg_return_true: }
5  \cs_new_eq:NN  % error on this line
6   \module_baz:nTF
7   \module_bar:nTF
8  \cs_new_eq:NN
9   \module_bar:nTF
10  \module_foo:nTF

```

```

11  \module_baz:nTF
12    { foo }
13    { bar }
14    { baz }

1  \prg_new_conditional:Nnn
2    \module_foo:n
3    { p, T, F, TF }
4    { \prg_return_true: }

5  \cs_new_eq:NN
6    \module_bar:nTF
7    \module_foo:nTF
8  \cs_undefine:N
9    \module_bar:nTF
10 \cs_new_eq:NN % error on this line
11   \module_baz:nTF
12   \module_bar:nTF
13 \module_baz:nTF
14   { foo }
15   { bar }
16   { baz }

```

This check is a stronger version of E411 and should only be emitted if E411 has not previously been emitted for this function.

### Setting a function before definition [W507]

A function is set before it has been defined or after it has been undefined.

```

1  \cs_gset:N % warning on this line
2    \module_foo:
3    { foo }
4  \cs_new:Nn
5    \module_foo:
6    { bar }

1  \cs_new:Nn
2    \module_foo:
3    { bar }
4  \cs_undefine:N
5    \module_foo:
6  \cs_gset:N % warning on this line
7    \module_foo:
8    { foo }

```

## Unexpandable or restricted-expandable boolean expression [E508]

A boolean expression [2, Section 9.2] is not fully-expandable.

```
1  \cs_new_protected:N
2    \example_unexpandable:
3    {
4      \tl_set:Nn
5        \l_tmpa_tl
6        { bar }
7      \c_true_bool
8    }
9  \cs_new:N
10   \example_restricted_expandable:
11   {
12     \bool_do_while:Nn
13       \c_false_bool
14       { }
15     \c_true_bool
16   }
17 \cs_new_protected:N
18   \example_expandable:
19   { \c_true_bool }
20 \bool_set:Nn
21   \l_tmpa_bool
22   { \example_unexpandable: } % error on this line
23 \bool_set:Nn
24   \l_tmpa_bool
25   { \example_restricted_expandable: } % error on this line
26 \bool_set:Nn
27   \l_tmpa_bool
28   { \example_expandable: }
```

## Expanding an unexpandable function [E509]

An unexpandable function or conditional function is called within an x-type, e-type, or f-type argument.

```
1  \cs_new_protected:N
2    \example_unexpandable:
3    {
4      \tl_set:Nn
5        \l_tmpa_tl
6        { bar }
7    }
8  \cs_new:N
9    \module_foo:n
```

```

10  { #1 }
11  \cs_generate_variant:Nn
12  \module_foo:n
13  { x, e, f }
14  \module_foo:n
15  { \example_unexpandable: }
16  \module_foo:x
17  { \example_unexpandable: } % error on this line
18  \module_foo:e
19  { \example_unexpandable: } % error on this line
20  \module_foo:f
21  { \example_unexpandable: } % error on this line

```

### Fully-expanding a restricted-expandable function [E510]

An restricted-expandable function or conditional function is called within an f-type argument.

```

1  \cs_new:N
2  \example_restricted_expandable:
3  {
4  \int_to_roman:n
5  { 1 + 2 }
6  }
7  \cs_new:N
8  \module_foo:n
9  { #1 }
10 \cs_generate_variant:Nn
11 \module_foo:n
12 { x, e, f }
13 \module_foo:n
14 { \example_restricted_expandable: }
15 \module_foo:x
16 { \example_restricted_expandable: }
17 \module_foo:e
18 { \example_restricted_expandable: }
19 \module_foo:f
20 { \example_restricted_expandable: } % error on this line

```

### Defined an expandable function as protected [W511]

A fully expandable function or conditional function is defined using a creator function `\cs_new_protected:*` or `\prg_new_protected_conditional:*`. [3, Section 4]

```

1 \cs_new_protected:Nn % warning on this line

```

```

2   \example_expandable:
3   { foo }

1 \prg_new_protected_conditional:Nnn % warning on this line
2   \example_expandable:
3   { T, F, TF }
4   { \prg_return_true: }

```

### Defined an unexpandable function as unprotected [W512]

An unexpandable or restricted-expandable function or conditional function is defined using a creator function `\cs_new:*` or `\prg_new_conditional:*`. [3, Section 4]

```

1 \cs_new:Nn % warning on this line
2   \example_unexpandable:
3   {
4     \tl_set:Nn
5     \l_tmpa_tl
6     { bar }
7   }

1 \prg_new_conditional:Nnn % warning on this line
2   \example_unexpandable:
3   { p, T, F, TF }
4   {
5     \tl_set:Nn
6     \l_tmpa_tl
7     { bar }
8     \prg_return_true:
9   }

```

### Conditional function with no return value [E513]

A conditional functions has no return value.

```

1 \prg_new_conditional:Nnn % error on this line
2   \example_no_return_value:
3   { p, T, F, TF }
4   { foo }

1 \prg_new_conditional:Nnn
2   \example_has_return_value:
3   { p, T, F, TF }
4   { \example_foo: }
5 \cs_new:Nn
6   \example_foo:
7   { \prg_return_true: }

```

### Comparison code with no return value [E514]

A comparison code [2, Section 6.1] has no return value.

```
1  \clist_set:Nn
2    \l_foo_clist
3    { 3 , 01 , -2 , 5 , +1 }
4  \clist_sort:Nn % error on this line
5    \l_foo_clist
6    { foo }

1  \clist_set:Nn
2    \l_foo_clist
3    { 3 , 01 , -2 , 5 , +1 }
4  \clist_sort:Nn
5    \l_foo_clist
6    { \example_foo: }
7  \cs_new:Nn
8    \example_foo:
9    {
10      \int_compare:nNnTF { #1 } > { #2 }
11      { \sort_return_swapped: }
12      { \sort_return_same: }
13    }
```

The above example has been taken from The L<sup>A</sup>T<sub>E</sub>X Project [2, Chapter 6].

### Paragraph token in the parameter of a "nopar" function [E515]

An argument that contains \par tokens may reach a function with the "nopar" restriction.

```
1  \cs_new_nopar:Nn
2    \example_foo:n
3    { #1 }
4  \cs_new:nn
5    \example_bar:n
6    {
7      \example_foo:n
8      { #1 }
9    }
10 \example_bar:n
11 {
12   foo
13   \par % error on this line
14   bar
15 }
```

## 5.2 Variables and constants

### Unused variable or constant [W516]

A variable or a constant is declared and perhaps defined but all its uses are unreachable.

```
1  \tl_new:N % warning on this line
2    \g_defined_but_unreachable_tl
3  \tl_gset:Nn
4    \g_defined_but_unreachable_tl
5    { foo }
6  \cs_new:Nn
7    \__module_baz:
8    {
9      \tl_use:N
10     \g_defined_but_unreachable_tl
11 }
```

This check is a stronger version of W415 and should only be emitted if W415 has not previously been emitted for this variable or constant.

### Setting an undeclared variable [E517]

A variable is set before it has been declared.

```
1  \tl_gset:Nn % error on this line
2    \g_example_tl
3    { bar }
4  \tl_new:N
5    \g_example_tl
```

This check is a stronger version of W416 and should prevent W416 from being emitted for this variable.

### Using an undeclared variable or constant [W518]

A variable or constant is used before it has been declared.

```
1  \tl_use:N % error on this line
2    \g_example_tl
3  \tl_new:N
4    \g_example_tl

1  \tl_use:N % error on this line
2    \c_example_tl
3  \tl_const:N
4    \c_example_tl
5    { foo }
```

This check is a stronger version of W419 and should only be emitted if W419 has not previously been emitted for this variable or constant.

## Multiply declared variable or constant [E519]

A variable or constant is declared multiple times.

```
1  \tl_new:N
2    \g_example_tl
3  \tl_new:N % error on this line
4    \g_example_tl

1  \tl_const:Nn
2    \c_example_tl
3    { foo }
4  \tl_const:Nn % error on this line
5    \c_example_tl
6    { bar }
```

## 5.3 Messages

### Unused message [W520]

A message is defined but all its uses are unreachable.

```
1  \msg_new:nnn % warning on this line
2    { foo }
3    { bar }
4    { baz }
5  \cs_new:Nn
6    \__module_baz:
7    {
8      \msg_info:nn
9        { foo }
10       { bar }
11    }
```

This check is a stronger version of W423 and should only be emitted if W423 has not previously been emitted for this message.

### Using an undefined message [E521]

A message is used before it has been defined.

```
1  \msg_info:nn % error on this line
2    { foo }
3    { bar }
4  \msg_new:nnn
5    { foo }
6    { bar }
7    { baz }
```

This check is a stronger version of E424 and should only be emitted if E424 has not previously been emitted for this message.

### Incorrect number of arguments supplied to message [W522]

A message was supplied fewer or more arguments than there are parameters in the message text.

```
1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #1 }
5  \msg_set:nnn
6    { foo }
7    { bar }
8    { baz }
9  \msg_info:nnn % error on this line
10   { foo }
11   { bar }
12   { baz }

1  \msg_new:nnn
2    { foo }
3    { bar }
4    { #1 }
5  \msg_info:nnn
6    { foo }
7    { bar }
8    { baz }
9  \msg_set:nnn
10   { foo }
11   { bar }
12   { baz }
```

This check is a stronger version of W426 and should only be emitted if W426 has not previously been emitted for this message.

### Multiply defined message [E523]

A message is defined multiple times.

```
1  \msg_new:nnn
2    { foo }
3    { bar }
4    { baz }
5  \msg_new:nnn % error on this line
6    { foo }
7    { bar }
8    { baz }
```

## 5.4 Input–output streams

### Using an unopened or closed stream [E524]

A stream is used before it has been opened or after it has been closed.

```
1  \ior_new:N
2    \l_example_ior
3  \ior_str_get:NN % error on this line
4    \l_example_ior
5    \l_tmpa_tl
6  \ior_open:Nn
7    \l_example_ior
8    { example }

1  \ior_new:N
2    \l_example_ior
3  \ior_open:Nn
4    \l_example_ior
5    { example }
6  \ior_close:N
7    \l_example_ior
8  \ior_str_get:NN % error on this line
9    \l_example_ior
10   \l_tmpa_tl
```

### Multiply opened stream [E525]

A stream is opened a second time without closing the stream first.

```
1  \iow_new:N
2    \l_example_iow
3  \iow_open:Nn
4    \l_example_iow
5    { foo }
6  \iow_open:Nn % error on this line
7    \l_example_iow
8    { bar }
9  \iow_close:N
10   \l_example_iow
```

### Unclosed stream [W526]

A stream is opened but not closed.

```
1  % file-wide warning
2  \ior_new:N
```

```

3   \l_example_ior
4   \ior_open:Nn
5   \l_example_ior
6   { example }

```

## 5.5 Piecewise token list construction

### Building on a regular token list [T527]

A token list variable is used with `\tl_build_*` functions before a function `\tl_build_*begin:N` has been called or after a function `\tl_build_*end:N` has been called.

```

1 \tl_new:N
2   \l_example_tl
3 \tl_build_put_right:Nn % error on this line
4   \l_example_tl
5   { foo }
6 \tl_build_begin:N
7   \l_example_tl
8 \tl_build_end:N
9   \l_example_tl

1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_put_right:Nn
6   \l_example_tl
7   { foo }
8 \tl_build_end:N
9   \l_example_tl

1 \tl_new:N
2   \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_end:N
6   \l_example_tl
7 \tl_build_put_right:Nn % error on this line
8   \l_example_tl
9   { foo }

```

### Using a semi-built token list [T528]

A token list variable is used where a regular token list is expected after a function `\tl_build_*begin:N` has been called and before a function `\tl_build_*end:N` has been called.

```

1  \tl_new:N
2    \l_example_tl
3 \tl_use:N
4   \l_example_tl
5 \tl_build_begin:N
6   \l_example_tl
7 \tl_build_end:N
8   \l_example_tl

1  \tl_new:N
2    \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_use:N
6   \l_example_tl % error on this line
7 \tl_build_end:N
8   \l_example_tl

1  \tl_new:N
2    \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_end:N
6   \l_example_tl
7 \tl_use:N
8   \l_example_tl

```

### Multiply started building a token list [E529]

A function `\tl_build_*begin:N` is called on a token list variable a second time without calling a function `\tl_build_*end:N` first.

```

1  \tl_new:N
2    \l_example_tl
3 \tl_build_begin:N
4   \l_example_tl
5 \tl_build_begin:N % error on this line
6   \l_example_tl
7 \tl_build_end:N
8   \l_example_tl

```

### Unfinished semi-built token list [W530]

A function `\tl_build_*begin:N` is called on a token list variable without calling a function `\tl_build_*end:N` later.

```

1  % file-wide warning
2  \tl_new:N
3  \l_example_tl
4  \tl_build_begin:N
5  \l_example_tl

```

## Caveats

The warnings and errors in this documents do not cover the complete expl3 language. The caveats currently include the following areas, among others:

- Functions with “weird” (`w`) argument specifiers
- Symbolic evaluation of expansion functions [2, sections 5.4–5.10]
- Validation of parameters in (inline) functions (c.f. E425 and W426)
- Shorthands such as `\~` and `\\"` in message texts [2, sections 11.4 and 12.1.3]
- Quotes in shell commands and file names [2, Section 10.7 and Chapter 12]
- Functions used outside their intended context:
  - `\sort_return_*`: outside comparison code [2, Section 6.1]
  - `\prg_return_*`: outside conditional functions [2, Section 9.1]
  - Predicates (`\*_p:*`) outside boolean expressions [2, Section 9.3]
  - `\*_map_break:*` outside a corresponding mapping [2, sections 9.8]
  - `\msg_line_*`, `\iow_char:N`, and `\iow_newline`: outside message text [2, sections 11.3 and 12.1.3]
  - `\iow_wrap_allow_break` and `\iow_indent:n` outside wrapped message text [2, Section 12.1.4]
  - Token list and string variables without accessor functions `\tl_use:N` and `\str_use:N`
  - Boolean variable without an accessor function `\bool_to_str:N` outside boolean expressions [2, Section 21.4]
  - Integer variable without an accessor function `\int_use:N` outside integer or floating point expressions [2, Section 21.4]
  - Dimension variable without an accessor function `\dim_use:N` outside dimension or floating point expressions [2, Section 26.7]
  - Skip variable without an accessor function `\skip_use:N` outside skip or floating point expressions [2, Section 26.14]
  - Muskip variable without an accessor function `\muskip_use:N` outside muskip or floating point expressions [2, Section 26.21]
  - Floating point variable without an accessor function `\fp_use:N` outside floating point expressions [2, Section 29.3]
  - Box variable without accessor functions `\box_use(_drop)?:N` or `\[hv]box_unpack(_drop)?:N`, or without a measuring function `\box_(dp|ht|wd|ht_plus_dp):*` outside dimension or floating point expressions [2, sections 35.2 and 35.3]

- Coffin variable without accessor function `\coffin_typeset:Nnnnn` outside dimension or floating point expressions [2, Section 36.4]
  - Lonely variables of other types that may or may not have accessor functions
- Validation of literal expressions:
  - Comparison expressions in functions `\*_compare(_p:n|:nT?F?)`
  - Regular expressions and replacement text [2, sections 8.1 and 8.2]
  - Boolean expressions [2, Section 9.3]
  - Integer expressions and bases [2, sections 21.1 and 21.8]
  - Dimension, skip, and muskip expressions [2, Chapter 26]
  - Floating point expressions [2, Section 29.12]
  - Color expressions [2, Chapter 37.3]
- Validation of naming schemes and member access:
  - String encoding and escaping [2, Section 18.1]
  - Key-value interfaces [2, Chapter 27]:
    - \* Are keys defined at the point of use or is the module or its subdivision set up to accept unknown keys? [2, sections 27.2, 27.5, and 27.6]
    - \* Are inheritance parents, choices, multi-choices, and groups used in a key definition defined at points of use? [2, sections 27.1, 27.3, and 27.7]
  - Floating-point symbolic expressions and user-defined functions [2, sections 29.6 and 29.7]
  - Names of bitset indexes [2, Section 31.1]
  - BCP-47 language tags [2, Section 34.2]
  - Color support [2, Chapter 37]:
    - \* Named colors [2, Section 37.4]
    - \* Color export targets [2, Section 37.8]
    - \* Color models and their families and params [2, sections 37.2 and 37.9]
- Function `\file_input_stop`: not used on its own line [2, Section 12.2.3]
- Exhaustively or fully expanding quarks and scan marks [2, Chapter 19]
- Bounds checking for accessing constant sequences and other sequences where the number of items can be easily bounded such as integer and floating point arrays [2, chapters 28 and 30]:
  - Index checking functions `\*_range*:*` and `\*_item*:*`
  - Endless loop checking in functions `\*_step_*:*` [2, Section 21.7]
  - Number of symbols in a value-to-symbol mapping [2, Section 21.8]
- Applying functions `\clist_remove_duplicates:N` and `\clist_if_in:*` to comma lists that contain {, }, or \* [2, sections 23.3 and 23.4]

- Incorrect parameters to function `\char_generate:nn` [2, Section 24.1]
- Incorrect parameters to functions `\char_set_*code:nn` [2, Section 24.2]
- Using implicit tokens `\c_catcode_(letter|other)_token` or the token list `\c_catcode_active_tl` [2, Section 24.3]
- Validation of key–value interfaces [2, Chapter 27]:
  - Setting a key with some properties `.*_g?(set|put)*::*` should be validated similarly to calling the corresponding functions directly: Have the variables been declared, do they have the correct type, does the value have the correct type?
  - Do points of use always set keys with property `.value_required:n` and never set keys with property `.value_forbidden:n?`
- Horizontal box operation on a vertical box or vice versa [2, Chapter 35], similarly for coffins

## References

- [1] Vít Starý Novotný. *Static analysis of expl3 programs (3). Design Specification.* To be released. URL: <https://witiko.github.io/Expl3-Linter-3/>.
- [2] The L<sup>A</sup>T<sub>E</sub>X Project. *The L<sup>A</sup>T<sub>E</sub>X3 interfaces.* The referenced version of the document is attached to this document. May 8, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/13kernel/interface3.pdf> (visited on 05/15/2024).
- [3] The L<sup>A</sup>T<sub>E</sub>X Project. *The L<sup>A</sup>T<sub>E</sub>X3 kernel. Style guide for code authors.* The referenced version of the document is attached to this document. Apr. 11, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/13kernel/13styleguide.pdf> (visited on 05/08/2024).
- [4] The L<sup>A</sup>T<sub>E</sub>X Project. *The expl3 package and L<sup>A</sup>T<sub>E</sub>X3 programming.* The referenced version of the document is attached to this document. Apr. 11, 2024. URL: <http://mirrors.ctan.org/macros/latex/required/13kernel/expl3.pdf> (visited on 05/08/2024).
- [5] Joseph Wright. Apr. 29, 2024. URL: <https://github.com/latex3/latex3/pull/1542#issuecomment-2082352499> (visited on 05/15/2024).

## Index

### **E**

E102, 5

E104, 6

E201, 7

E203, 7

E208, 7

E209, 8

E300, 8

E301, 8

E304, 9

E404, 11

E405, 11

E408, 12

E411, 13

E417, 17

E418, 17

E420, 18

E421, 18

E424, 24

E425, 24

E427, 25

E500, 25

E504, 29

E505, 30

E506, 31

E508, 33

E509, 33

E510, 34

E513, 35

E514, 36

E515, 36

E517, 37

E519, 38

E521, 38

E523, 39

E524, 40

E525, 40

E529, 42

### **S**

S103, 6

S105, 6

S204, 7

S412, 14

S413, 15

S414, 16

### **T**

T305, 9

T403, 11

T422, 18

T527, 41

T528, 41

### **W**

W100, 4

W101, 5

W200, 6

W202, 7

W302, 8

W303, 9

W401, 10

W402, 10

W410, 12

W415, 16

W416, 17

W419, 17

W423, 23

W426, 24

W501, 27

W502, 28

W503, 28

W507, 32

W511, 34

W512, 35

W516, 37

W518, 37

W520, 38

W522, 39

W526, 40

W530, 42