

Package ‘FIESTAutils’

January 29, 2025

Type Package

Title Utility Functions for Forest Inventory Estimation and Analysis

Version 1.3.0

Date 2025-01-28

Description A set of tools for data wrangling, spatial data analysis, statistical modeling (including direct, model-assisted, photo-based, and small area tools), and USDA Forest Service data base tools. These tools are aimed to help Foresters, Analysts, and Scientists extract and perform analyses on USDA Forest Service data.

Depends R (>= 4.2.0)

Imports data.table, DBI, gdalraster, graphics, hbsae, JoSAE, mase, methods, nlme, Rcpp, RColorBrewer, RPostgres, RSQLite, sae, sf, sqldf, stats, terra, units, utils

Suggests knitr

License GPL-3

Copyright See file COPYRIGHTS for details.

URL <https://github.com/USDAForestService/FIESTAutils>

BugReports <https://github.com/USDAForestService/FIESTAutils/issues>

Encoding UTF-8

LazyData true

LinkingTo Rcpp

RoxygenNote 7.3.2

NeedsCompilation yes

Author Tracey Frescino [aut],
Chris Toney [aut],
Grayson White [aut, cre],
Joshua Yamamoto [aut]

Maintainer Grayson White <graysonwhite13@gmail.com>

Repository CRAN

Date/Publication 2025-01-29 05:40:07 UTC

Contents

.update_refs	3
database_options	3
datExportData	4
datSum_options	5
DBtestPostgreSQL	7
DBtestSQLite	8
eval_options	9
GDT_NAMES	10
kindcd3old	11
multest_options	11
popFilters	12
popTableIDs	14
popTables	16
ref_codes	18
ref_codes_archive	19
ref_cond	19
ref_conversion	20
ref_diacl2in	20
ref_domain	21
ref_estimators	21
ref_estvar	21
ref_evaltyp	22
ref_plt	22
ref_popType	23
ref_shp	23
ref_species	24
ref_statecd	24
ref_titles	25
ref_tree	25
ref_units	26
savadata_options	26
spMakeSpatial_options	28
strata_options	29
stunitco	30
tableIDs	31
table_options	32
title_options	34
unit_options	36
xy_options	37

Index

39

.update_refs *Updates reference tables*

Description

Updates reference tables

Usage

```
.update_refs(write = FALSE)
```

Arguments

write Logical. Should the internal reference tables be overwritten?

Value

No return value. Called for side effects.

Author(s)

Josh Yamamoto

database_options *Database options.*

Description

Returns a list of user-supplied parameters and parameter values for database access.

Usage

```
database_options(  
  dbname = NULL,  
  host = NULL,  
  port = NULL,  
  user = NULL,  
  password = NULL,  
  schema = NULL,  
  dbconnopen = TRUE,  
  ...  
)
```

Arguments

dbname	String. Name of database.
host	String. Name of database host.
port	String. Database port.
user	String. User name for database access.
password	String. Password for database access.
schema	String. Name of schema in database.
dbconnopen	Logical. If TRUE, keep database connection open.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for saving data.

Author(s)

Tracey S. Frescino

Examples

```
savedata_options(outfolder = "path", overwrite_dsn = FALSE)
```

datExportData	<i>Spatial - Exports a data frame object.</i>
---------------	---

Description

Exports a data frame object to a specified output.

Usage

```
datExportData(
  dfobj,
  create_dsn = FALSE,
  index.unique = NULL,
  index = NULL,
  lowernames = FALSE,
  savedata_opts = savedata_options(),
  dbconn = NULL,
  dbconnopen = TRUE
)
```

Arguments

dfobj	Data.frame class R object. Data frame object to export.
create_dsn	Boolean.
index.unique	String. Name of variable(s) in dfobj to make unique index.
index	String. Name of variable(s) in dfobj to make (non-unique) index.
lowernames	Logical. If TRUE, convert column names to lowercase before writing to output.
	dbconnopen Logical. If TRUE, keep database connection open.
savedata_opts	List. See help(savedata_options()) for a list of options.
dbconn	Open database connection.
dbconnopen	Logical. If TRUE, keep database connection open.

Details

Wrapper for sf::st_write function.

Value

An sf spatial object is written to the out_dsn.

Note

If out_fmt='shp':

The ESRI shapefile driver truncates variable names to 10 characters or less. Variable names are changed before export using an internal function (trunc10shp). Name changes are output to the outfolder, 'outshpnm'_newnames.csv.

If sf object has more than 1 record, it cannot be exported to a shapefile.

Author(s)

Tracey S. Frescino

datSum_options

Options for summarizing tree data.

Description

Returns a list of user-supplied parameters and parameter values for summarizing tree data.

Usage

```

datSum_options(
  lbs2tons = TRUE,
  metric = FALSE,
  tround = 5,
  TPA = TRUE,
  adjTPA = 1,
  ACI = FALSE,
  adjtree = FALSE,
  adjvar = "tadjfac",
  NAt0 = TRUE,
  ...
)

```

Arguments

lbs2tons	Logical. If TRUE, converts biomass or carbon variables from pounds to tons (1 pound = 0.0005 short tons). If metric=TRUE, converts to metric tons, else short tons.
metric	Logical. If TRUE, converts response to metric units based on ref_conversion, if any variable in tsumvarlst is in FIESTAutils::ref_estvar. Note: if TPA, TPA is converted to trees per hectare (TPH: (1/ tpavar * 0.4046860)).
tround	Number. The number of digits to round to. If NULL, default=5.
TPA	Logical. If TRUE, tsumvarlst variable(s) are multiplied by the respective trees-per-acre variable (see details) to get per-acre measurements.
adjTPA	Numeric. A tree-per-acre adjustment. Use for DESIGNCD=1 (annual inventory), if using less than 4 subplots. If using only 1 subplot for estimate, adjTPA=4. The default is 1.
ACI	Logical. If TRUE, if ACI (All Condition Inventory) plots exist, any trees on these plots will be included in summary. If FALSE, you must include condition table.
adjtree	Logical. If TRUE, trees are individually adjusted by adjustment factors. Adjustment factors must be included in tree table (see adjvar).
adjvar	String. If adjtree=TRUE, the name of the variable to use for multiplying by adjustment (e.g., tadjfac).
NAt0	Logical. If TRUE, change NA values to 0
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for summarizing tree data.

Author(s)

Tracey S. Frescino

Examples

```
datSum_options(lbs2tons = TRUE, metric = TRUE)
```

DBtestPostgreSQL *Database - Test a PostgreSQL database.*

Description

Checks a PostgreSQL database.

Usage

```
DBtestPostgreSQL(  
  dbname = NULL,  
  host = NULL,  
  port = NULL,  
  user = NULL,  
  password = NULL,  
  dbconnopen = FALSE,  
  showlist = TRUE,  
  ...  
)
```

Arguments

dbname	String. Name of the database on the host.
host	String. Host name.
port	String. Port number.
user	String. User name.
password	String. Password.
dbconnopen	Logical. If TRUE, the database connection is returned and not closed.
showlist	Logical. If TRUE, prints list of tables in database.
...	Additional authentication arguments passed to DBI::dbConnect

Value

An S4 object that inherits from DBIConnection via the DBI package if dbconnopen = TRUE, or NULL otherwise. For more information, see 'help(DBI::dbConnect)'.

Author(s)

Tracey S. Frescino

 DBtestSQLite

Database - Checks access to a SQLite database.

Description

Checks a SQLite database.

Usage

```
DBtestSQLite(
  SQLitefn = NULL,
  gpkg = FALSE,
  dbconnopen = FALSE,
  outfolder = NULL,
  showlist = TRUE,
  returnpath = TRUE,
  createnew = TRUE,
  stopifnull = FALSE,
  overwrite = TRUE
)
```

Arguments

SQLitefn	String. Name of SQLite database (*.sqlite).
gpkg	Logical. If TRUE, Sqlite geopackage database.
dbconnopen	Logical. If TRUE, the dbconn connection is not closed.
outfolder	String. Optional. Name of output folder. If NULL, export to working directory.
showlist	Logical. If TRUE, shows list of tables in database.
returnpath	Logical. If TRUE, returns full path to SQLite file name. If FALSE, returns SQLitefn.
createnew	If TRUE, creates new SQLite database.
stopifnull	Logical. If TRUE, stops if SQLite database doesn't exist.
overwrite	Logical. If TRUE, overwrites data.

Value

Character string containing the path to the SQLite database of interest.

Author(s)

Tracey S. Frescino

eval_options	<i>List of population tables.</i>
--------------	-----------------------------------

Description

Returns a list of user-supplied parameters and parameter values for data evaluation (FIA or custom) extraction to be supplied to *DB functions.

Usage

```
eval_options(
  Cur = FALSE,
  Endyr = NULL,
  Endyr.filter = NULL,
  All = FALSE,
  Type = "VOL",
  evalid = NULL,
  invyrs = NULL,
  measyrs = NULL,
  varCur = "INVYR",
  evalType = NULL,
  ...
)
```

Arguments

Cur	Logical. If eval='FIA': extract plots with most current evaluation. If eval='custom': extract the most current sampled plots in the database.
Endyr	Integer (YYYY). If eval='FIA', defines end year for extracting one or more FIA evaluation. If eval='custom', defines end year for extracting the most current sampled plots until.
Endyr.filter	Filter. If endyr != NULL, a filter to identify when to use measEndyr, such as areas or plots identified as being disturbed in a particular year. In this example, plots sampled after the disturbance will be excluded.
All	Logical. If eval='FIA': includes all evaluations in database (annual inventory only). If eval='custom': includes all years in database (annual inventory only).
Type	String vector. Evaluation types ('ALL', 'CURR', 'VOL', 'P2VEG', 'DWM', 'INV', 'CHNG', 'GRM', 'REGEN'). If eval='FIA', Type is equivalent to plots for FIA Evaluations where 'ALL' includes nonsampled plots; 'CURR' and 'VOL' include plots used for area or tree estimates, respectively; Type = 'GRM' includes plots used for growth, removals, mortality; and Type = 'CHNG' includes plots used for change estimates (See FIA database manual for region availability and/or differences (https://www.fia.fs.usda.gov/library/database-documentation/index.php) If eval='custom', the associated tables are extracted for each Type. Multiple Types are accepted.
evalid	Integer. Only eval='FIA': extract data for a specific evaluation period. See notes for more information about FIA Evaluations.

invyrs	Integer vector. eval='custom': defines specific inventory years of data (e.g., 2010:2015). See FIA manual for definition of INVYR.
measyrs	Integer vector. eval='custom': defines specific measurement years of data (e.g., 2010:2015).
varCur	String. Name of variable to use for most current plot ('MEASYEAR', 'INVYR').
evalType	Deprecated. Use Type instead.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Tracey S. Frescino

Examples

```
eval_options(invyrs = 2015:2018)
```

GDT_NAMES

Reference tables - gdal data types.

Description

Table with gdal data type names.

Format

A vector of 12 data type values.

Source

gdal values.

kindcd3old	<i>Reference table - List of RMRS plots that have fallen out of inventory because they were not found or they were in the wrong place.</i>
------------	--

Description

Table with variable codes (VALUE) and descriptions (MEANING).

Format

A dataframe

Source

FIA query. SELECT bp.STATECD, bp.COUNTYCD, bp.PLOT_FIADB NEW_PLOT, bp.START_DATE NEW_START_DATE, bp_old.COUNTYCD OLD_COUNTYCD, bp_old.PLOT_FIADB OLD_PLOT, bp_old.END_DATE OLD_END_DATE, p.CN FROM fs_nims_rmrs.NIMS_BASE_PLOT bp JOIN fs_nims_rmrs.NIMS_BASE_PLOT bp_old on (bp.PREV_NBP_CN=bp_old.CN) JOIN fs_nims_rmrs.NIMS_PLOT_RMRS p on(p.NBP_CN=bp_old.CN) WHERE p.KINDCD = 1 ORDER BY bp.STATECD, bp.COUNTYCD, bp_old.PLOT_FIADB"

multest_options	<i>Multest output options.</i>
-----------------	--------------------------------

Description

Returns a list of user-supplied parameters and parameter values for outputting multest with custom aesthetics.

Usage

```
multest_options(
  multest_estimators = "all",
  multest_fmt = "csv",
  multest_outfolder = NULL,
  multest_dsn = NULL,
  multest_layer = NULL,
  multest.append = FALSE,
  multest.AOOnly = FALSE,
  ...
)
```

Arguments

<code>multest_estimators</code>	String vector. If <code>multest = TRUE</code> , vector of estimators to include in multest output ('JU.GREG', 'JU.EBLUP', 'JFH', 'hbsaeU', 'hbsaeA'). See <code>ref_estimators</code> for descriptions. Use <code>multest_estimators = 'all'</code> to output all estimators.
<code>multest_fmt</code>	String. Format for multest output tables ('csv', 'sqlite', 'gpkg').
<code>multest_outfolder</code>	String. Outfolder for multest. If NULL, same as outfolder.
<code>multest_dsn</code>	String. Name of database if <code>multest_fmt = c('sqlite', 'gpkg')</code> .
<code>multest_layer</code>	String. Name of database layer if <code>multest_fmt = c('sqlite', 'gpkg')</code> .
<code>multest.append</code>	Logical. If TRUE, appends multest dataframe to output.
<code>multest.AOIonly</code>	Logical. If TRUE, appends multest dataframe (AOI=1) to output.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting multest.

Author(s)

Grayson W. White

Examples

```
multest_options(multest.append = TRUE)
```

popFilters

Population data filters.

Description

Returns a list of user-supplied parameters and parameter values for population data filters.

Usage

```
popFilters(
  evalid = NULL,
  states = NULL,
  evalCur = FALSE,
  evalEndyr = NULL,
  measCur = FALSE,
  measEndyr = NULL,
  invyrs = NULL,
  measyrs = NULL,
  intensity = NULL,
  ACI = FALSE,
  AOIonly = FALSE,
  pfilter = NULL,
  ...
)
```

Arguments

evalid	Numeric. FIA Evaluation identifier for subsetting plots for population.
states	String or numeric vector. Name (e.g., 'Arizona','New Mexico') or code (e.g., 4, 35) of state(s) for evalid. If all states in one or more FIA Research Station is desired, set states=NULL and use RS argument to define RS.
evalCur	Logical. If TRUE, the most current FIA Evaluation is extracted for state(s).
evalEndyr	Number. The end year of the FIA Evaluation of interest. Selects only sampled plots and conditions for the evaluation period. If more than one state, create a named list object with evalEndyr labeled for each state (e.g., list(Utah=2014, Colorado=2013)).
measCur	Logical. If TRUE, the most current sampled plots available for state(s).
measEndyr	Number. The most current sampled plots measured before or during end given..
invyrs	Integer vector. Inventory year(s) (e.g., c(2000, 2001, 2002)).
measyrs	Integer vector. Measurement year(s) (e.g., c(2000, 2001, 2002)).
intensity	Integer code. Code(s) indicating intensity to use for population.
ACI	Logical. If TRUE, including All Condition Inventory (ACI) plots.
AOIonly	Logical. If TRUE, and there is an AOI (1/0) attribute in the population data, only AOI=1 are used for estimation.
pfilter	String. Logical filter for plot or pltassgn.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for population data filters.

Author(s)

Grayson W. White

popTableIDs

List of population table unique IDs.

Description

Returns a list of user-supplied parameters and parameter values for data table unique IDs to be supplied to *pop functions.

Usage

```
popTableIDs(
  cond = "PLT_CN",
  plt = "CN",
  tree = "PLT_CN",
  seed = "PLT_CN",
  seedling = "PLT_CN",
  vsubpspp = "PLT_CN",
  p2veg_subplot_spp = "PLT_CN",
  vsubpstr = "PLT_CN",
  p2veg_subp_structure = "PLT_CN",
  invsubp = "PLT_CN",
  invasive_subplot_spp = "PLT_CN",
  subplot = "PLT_CN",
  subp_cond = "PLT_CN",
  dwm = "PLT_CN",
  cond_dwm_calc = "PLT_CN",
  sccm = "PLT_CN",
  subp_cond_chng_mtrx = "PLT_CN",
  grm = "PLT_CN",
  tree_grm_component = "PLT_CN",
  begin = "PLT_CN",
  tree_grm_begin = "PLT_CN",
  midpt = "PLT_CN",
  tree_grm_midpt = "PLT_CN",
  plot = "CN",
  pltu = "CN",
  plotu = "CN",
  condu = "PLT_CN",
  ...
)
```

Arguments

cond	String. Unique identifier of plot in cond.
plt	String. Unique identifier of plot in plt.
tree	String. Unique identifier of plot in tree and seed.
seed	String.
seedling	String.
vsubpspp	String.
p2veg_subplot_spp	String.
vsubpstr	String.
p2veg_subp_structure	String.
invasubp	String.
invasive_subplot_spp	String.
subplot	String.
subp_cond	String.
dwm	String.
cond_dwm_calc	String.
sccm	String.
subp_cond_chng_mtrx	String.
grm	String.
tree_grm_component	String.
begin	String.
tree_grm_begin	String.
midpt	String.
tree_grm_midpt	String.
plot	String.
pltu	String.
plotu	String.
condu	String.
...	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied unique identifier of a plot in population tables.

Author(s)

Grayson W. White

popTables

*List of population tables.***Description**

Returns a list of user-supplied parameters and parameter values for data tables to be supplied to *pop functions.

Usage

```
popTables(
  cond = "COND",
  plt = "PLOT",
  tree = "TREE",
  seed = "SEEDLING",
  seedling = "SEEDLING",
  vsubpspp = "P2VEG_SUBPLOT_SPP",
  p2veg_subplot_spp = "P2VEG_SUBPLOT_SPP",
  vsubpstr = "P2VEG_SUBP_STRUCTURE",
  p2veg_subp_structure = "P2VEG_SUBP_STRUCTURE",
  invsubp = "INVASIVE_SUBPLOT_SPP",
  invasive_subplot_spp = "INVASIVE_SUBPLOT_SPP",
  subplot = "SUBPLOT",
  subp_cond = "SUBP_COND",
  dwm = "COND_DWM_CALC",
  cond_dwm_calc = "COND_DWM_CALC",
  sccm = "SUBP_COND_CHNG_MTRX",
  subp_cond_chng_mtrx = "SUBP_COND_CHNG_MTRX",
  grm = "TREE_GRM_COMPONENT",
  tree_grm_component = "TREE_GRM_COMPONENT",
  begin = "TREE_GRM_BEGIN",
  tree_grm_begin = "TREE_GRM_BEGIN",
  midpt = "TREE_GRM_MIDPT",
  tree_grm_midpt = "TREE_GRM_MIDPT",
  plot = "plot",
  pltu = "pltu",
  plotu = "plotu",
  condu = "condu",
  ...
)
```


Arguments

cond	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Condition-level data with one record for each condition, including or excluding nonsampled conditions. Plot variables and strata/estimation unit variable(s) may be included if plt and pltassgn=NULL. See details for necessary variables to include.
plt	DF/DT, Optional. R object, sf R object, comma-delimited file(*.csv), layer or spatial layer in dsn, or shapefile(*.shp). Plot-level data with one record for each plot, including or excluding nonsampled conditions. If nonsampled plots are included, PLOT_STATUS_CD variable must be in table or a filter defined in plt.nonsamp.filter.
tree	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level data with one record for each tree. Tree data are aggregated to condition-level. See details for necessary variables to include.
seed	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Seedling data with one record for each seedling count.
seedling	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Seedling data with one record for each seedling count.
vsubpspp	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Vegetation species-level data with one record for each species (P2VEG_SUBPLOT_SPP).
p2veg_subplot_spp	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Vegetation species-level data with one record for each species (P2VEG_SUBPLOT_SPP).
vsubpstr	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Vegetation species-structure data with one record for each species (P2VEG_SUBP_STRUCTURE).
p2veg_subp_structure	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Vegetation species-structure data with one record for each species (P2VEG_SUBP_STRUCTURE).
invsubp	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Invasive species data with one record for each species (INVASIVE_SUBPLOT_SPP).
invasive_subplot_spp	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Invasive species data with one record for each species (INVASIVE_SUBPLOT_SPP).
subplot	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Subplot-level data with one record for each species (SUBPLOT).
subp_cond	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Subplot condition-level data with one record for each species (SUBP_COND).
dwm	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Calculated down woody material (COND_DWM_CALC).
cond_dwm_calc	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Calculated down woody material (COND_DWM_CALC).
sccm	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Subplot-level data (SUBP_COND_CHNG_MTRX).
subp_cond_chng_mtrx	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Subplot-level data (SUBP_COND_CHNG_MTRX).

grm	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_COMPONENT).
tree_grm_component	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_COMPONENT).
begin	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_BEGIN).
tree_grm_begin	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_BEGIN).
midpt	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_MIDPT).
tree_grm_midpt	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Tree-level growth, removal, and mortality data (TREE_GRM_MIDPT).
plot	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Plot data unioned with remeasured plot data.
pltu	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Plot data unioned with remeasured plot data.
plotu	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Plot data unioned with remeasured plot data.
condu	DF/DT, R object, comma-delimited file(*.csv), or layer in dsn. Cond data unioned with remeasured cond data.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

ref_codes

Reference tables - Code definitions.

Description

Table with variable codes (VALUE) and descriptions (MEANING).

Format

A dataframe with 7 columns, VARIABLE, VALUE, MEANING, COLORHEX, GROUP, GROUPNM, GROUPEX.

Source

FIA look-up tables.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_codes_archive	<i>Reference tables - Code definitions (Archive).</i>
-------------------	---

Description

Table with variable codes (VALUE) and descriptions (MEANING).

Format

A dataframe with 7 columns, VARIABLE, VALUE, MEANING, COLORHEX, GROUP, GROUPNM, GROUPHEX.

Source

FIA look-up tables.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_cond	<i>Reference table - Metadata for cond default variables output from DBgetPlots()</i>
----------	---

Description

Data frame with variable names and descriptions

Format

A data frame with 61 rows and 3 columns VARIABLE - Variable in cond data frame DESCRIPTION - Description of variable in cond data frame TABLE - Table in database where variable originates or if derived

Source

FIA look-up table

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_conversion	<i>Reference table - for conversion factors.</i>
----------------	--

Description

Table with conversion factors from English to metric units.

Format

A dataframe with 6 columns: TYPE, ENGLISH, ENGLISH_ABBR, METRIC, METRIC_ABBR, CONVERSION.

Source

Conversion table.

ref_diacl2in	<i>Reference table - diameter 2-inch class codes (DIA).</i>
--------------	---

Description

Table with min (MIN), max (MAX), and 2-inch class diameter codes (MEANING).

Format

A dataframe with 3 columns, MIN, MAX, and MEANING.

Source

Imported from comma-delimited file.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_domain	<i>Reference table - for generating tables.</i>
------------	---

Description

Table with row/column domain (VARNM) and their pretty names for table output (TABLENM).

Format

A dataframe with 2 columns, VARNM and TABLENM.

Source

FIA look-up table.

ref_estimators	<i>Reference table - FIESTA estimators.</i>
----------------	---

Description

Table with list of estimators currently in FIESTA.

Format

A dataframe with 7 columns: ESTIMATOR, SHORTNAME, PACKAGE, OUTNAME, ESTIMATOR_TYPE, ESTIMATOR_DATA, DESCRIPTION, CITATION

Source

Comma-delimited file.

ref_estvar	<i>Reference table - for generating estimates</i>
------------	---

Description

Data frame with variable names and descriptions

Format

A data frame to use a reference for estimation variables and filters.

ref_evaltyp	<i>Reference table - for generating tables.</i>
-------------	---

Description

Table with row/column domain (VARNM) and their pretty names for table output (TABLENM).

Format

A dataframe with 3 columns, EVAL_TYP_CD, EVAL_TYP, DESCRIPTION.

Source

FIA look-up table.

ref_plt	<i>Reference table - Metadata for plt default variables output from DBgetPlots()</i>
---------	--

Description

Data frame with variable names and descriptions.

Format

A data frame with 43 rows and 3 columns VARIABLE - Variable in plt data frame DESCRIPTION - Description of variable in plt data frame TABLE - Table in database where variable originates or if derived

Source

FIA look-up table

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_popType	<i>Reference table - popType codes.</i>
-------------	---

Description

Table with population type (popType) and associated evaluation code (EVAL_TYP_CD).

Format

A dataframe with 2 columns, VARNM and TITLE.

Source

Comma-delimited file.

ref_shp	<i>Reference table - Metadata for shp_* default variables output from DBgetPlots()</i>
---------	--

Description

Data frame with variable names and descriptions

Format

A dataframe with 63 rows and 4 columns
 VARIABLE - Variable in plt data frame
 DESCRIPTION - Description of variable in plt data frame
 TABLE - Table in database where variable originates or if derived
 SHPEXPORT - Name of variable for exported shapefile (<= 10 characters)

Source

FIA look-up table

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_species	<i>Reference table - Code definitions.</i>
-------------	--

Description

Table with species information downloaded from datamart FIADB_REFERENCES, subset from REF_SPECIES TABLE.

Format

A dataframe with 14 columns: SPCD, COMMON_NAME, GENUS, SPECIES, SPECIES_SYMBOL, E_SPGRCD, W_SPGRCD, C_SPGRCD, P_SPGRCD, MAJOR_SPGRCD, JENKINS_TOTAL_B1, JENKINS_TOTAL_B2, DRYWT_TO_GREENWT_CONERSION, SCIENTIFIC_NAME (GENUS + SPECIES).

Source

Imported from comma-delimited file.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_statecd	<i>Reference table - state codes (STATECD).</i>
-------------	---

Description

Table with state codes (VALUE), name (MEANING), abbreviation (ABBR), and UNIT.

Format

A dataframe with 4 columns, VALUE, MEANING, ABBR, UNIT.

Source

Imported from comma-delimited file.

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_titles	<i>Reference table - Variable titles.</i>
------------	---

Description

Table with variable name (VARNM) and associated title (TITLE).

Format

A dataframe with 2 columns, VARNM and TITLE.

Source

Comma-delimited file.

ref_tree	<i>Reference table - Metadata for tree default variables output from DBgetPlots()</i>
----------	---

Description

Data frame with variable names and descriptions

Format

A data frame with 72 rows and 3 columns
 VARIABLE - Variable in tree data frame
 DESCRIPTION - Description of variable in tree data frame
 TABLE - Table in database where variable originates

Source

FIA look-up table

References

O'Connell, B.M.; LaPoint, E.B.; Turner, J.A.; Ridley, T.; Boyer, D.; Wilson, A.M.; Waddell, K.L.; Christensen, G.; Conkling, B.L. 2012. The Forest Inventory and Analysis Database: Database Description and Users Manual Version 5.1.2 for Phase 2. U.S. Department of Agriculture. (http://fia.fs.fed.us/library/database-documentation/current/ver5-2012/FIADB_user_manual_5-1-2_p2_07_2012.pdf)

ref_units	<i>Reference table - for variable units.</i>
-----------	--

Description

Table with units for TREE variables. The WOODLAND column was added to identify which variables include woodland species. The kg2tons column was added to identify which variables are commonly converted from kilograms to tons in estimation process.

Format

A dataframe with 4 columns: VARIABLE, UNITS, METRICUNITS, WOODLAND, kg2tons.

Source

Units table.

savedata_options	<i>Data saving options.</i>
------------------	-----------------------------

Description

Returns a list of user-supplied parameters and parameter values for saving data.

Usage

```
savedata_options(
  outfolder = NULL,
  out_fmt = "csv",
  outsp_fmt = "shp",
  outobj_fmt = "rds",
  out_dsn = NULL,
  out_layer = "outdat",
  outfn.pre = NULL,
  outfn.date = FALSE,
  addtitle = TRUE,
  raw_fmt = "csv",
  raw_dsn = NULL,
  overwrite_dsn = FALSE,
  overwrite_layer = TRUE,
  append_layer = FALSE,
  add_layer = TRUE,
  layer.pre = NULL,
  outconn = NULL,
  ...
)
```

Arguments

outfolder	String. The outfolder to write files to. If NULL, files are written to working directory, or if gui=TRUE, a window to browse.
out_fmt	String. Format for output tables ('csv', 'sqlite', 'gpkg', 'gdb').
outsp_fmt	String. Format for output spatial ('shp', 'sqlite', 'gpkg', 'gdb').
outobj_fmt	String. Format for output spatial ('rda', 'rds', 'llo').
out_dsn	String. Data source name for output. If extension is not included, out_fmt is used. Use full path if outfolder=NULL.
out_layer	outlayer.
outfn.pre	String. If savedata=TRUE, prefix for output files. If rawdata=TRUE, prefix for rawdata files (if raw_fmt = 'csv') or raw_dsn (if raw_fmt != 'csv').
outfn.date	Logical. If TRUE, add current date to out_dsn.
addtitle	Logical. If TRUE and savedata=TRUE, adds title to outfile.
raw_fmt	String. Format for output rawdata tables ('sqlite', 'gpkg', 'csv', 'gdb').
raw_dsn	String. Data source name for rawdata output. If extension is not included, out_fmt is used. Use full path if outfolder=NULL.
overwrite_dsn	Logical. If TRUE, overwrites raw_dsn, if exists.
overwrite_layer	Logical. If TRUE, overwrites the output. If rawdata=TRUE, overwrites out_layer in rawdata folder (if raw_fmt = 'csv') or out_layers in raw_dsn (if raw_fmt != 'csv').
append_layer	Logical. If TRUE, and appends data to existing *.csv files (if *_fmt = 'csv') or *_dsn layers (if *_fmt != 'csv').
add_layer	Logical. If TRUE, adds layer to an existing out_dsn (if out_fmt != c('csv', 'shp')).
layer.pre	Layer prefix.
outconn	Open database connection to save to.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for saving data.

Author(s)

Grayson W. White

Examples

```
savedata_options(outfolder = "path", overwrite_dsn = FALSE)
```

spMakeSpatial_options *Make SpatialPoints options*

Description

Returns a list of user-supplied parameters and parameter values for making SpatialPoints.

Usage

```
spMakeSpatial_options(  
  xvar = NULL,  
  yvar = NULL,  
  xy.crs = 4269,  
  prj = NULL,  
  datum = NULL,  
  zone = NULL,  
  zones = FALSE,  
  aea.param = "USGS",  
  ...  
)
```

Arguments

xvar	String. Name of variable in xyplt defining x coordinate.
yvar	String. Name of variable in xyplt defining y coordinate.
xy.crs	PROJ.4 String or CRS object or Integer EPSG code defining Coordinate Reference System. (e.g., EPSG:4269-Geodetic coordinate system for North America, NAD83).
prj	String. Projection, or coordinate system of the X/Y coordinates ("longlat", "utm", "aea"). If other, include PROJ.4 string in prj4str.
datum	String. Datum of projection ("WGS84", "NAD83", "NAD27").
zone	Integer. If prj="utm", the UTM zone.
zones	Logical. If prj="utm", if the UTM zone is in the Southern hemisphere.
aea.param	String. If prj="aea", the associated lat/lon parameters (USGS: " +lat_1=29.5 +lat_2=45.5 +lat_0=23 +lon_0=-96 +x_0=0 +y_0=0"). If other, include PROJ.4 string in prj4str.
...	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
spMakeSpatial_options()
```

strata_options	<i>Strata options.</i>
----------------	------------------------

Description

Returns a list of user-supplied parameters and parameter values for strata.

Usage

```
strata_options(
  getwt = FALSE,
  getwtvar = "P1POINTCNT",
  strwtvar = "strwt",
  stratcombine = TRUE,
  minplotnum.strat = 2,
  pivot = FALSE,
  nonresp = FALSE,
  ...
)
```

Arguments

getwt	Logical. If TRUE, calculates strata weights from stratlut getwtvar. If FALSE, strwtvar variable must be in stratalut.
getwtvar	String. If getwt=TRUE, name of variable in stratalut to calculate weights (Default = 'P1POINTCNT').
strwtvar	String. If getwt=FALSE, name of variable in stratalut with calculated weights (Default = 'strwt').
stratcombine	Logical. If TRUE, and strata=TRUE, automatically combines strata categories if less than minplotnum.strat plots in any one stratum. See notes for more info.
minplotnum.strat	Integer. Minimum number of plots for a stratum within an estimation unit.
pivot	Logical. If TRUE, pivot stratalut.
nonresp	Deprecated.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
strata_options(getwt = FALSE)
```

stunitco	<i>SpatialPolygonsDataFrame with FIA state, unit, county codes and names</i>
----------	--

Description

Polygon feature class with state and county boundaries defined by Census Bureau, including Federal Information Processing Standards (FIPS) codes. The FIA Survey Unit code and name attributes (UNITCD, UNITNM) were appended to dataset, with joining columns of STATECD and COUNTYCD.

Format

A SpatialPolygonsDataFrame with 3233 features and 8 attributes RS - FIA Research Station name RSCD - FIA Research Station code STATECD - FIPS state code STATENM - FIPS state name STATEAB - FIPS state abbreviation UNITCD - FIA survey unit code UNITNM - FIA survey unit name COUNTYCD - FIPS county code COUNTYNM - FIPS county name

Details

Derived from cb_2018_us_county_5m. STATEFP was converted to numeric and named STATECD COUNTYFP was converted to numeric and named COUNTYCD Lookup table for FIA Research Station (REF_RESEARCH_STATION) was downloaded from FIA DataMart on 20191105 (FIADB_1.6.1.00) and joined by STATECD. A lookup table for UNITCD was created from plot data using unique STATECD, COUNTYCD, UNITCD and joined to table.

Converted to simple feature

Transformed CRS from longlat(EPSC:4269) to Albers (EPSC:5070)

Saved to R object, with compression='xz'

Source

Downloaded from the United States Census Bureau on 2019 November 3, format Esri Shapefile (<https://www.census.gov/geographies/mapping-files/time-series/geo/carto-boundary-file.html>) Projection: Geographic (GCS_North_American_1983) EPSG: 4269

tableIDs	<i>List of FIADB table unique IDs.</i>
----------	--

Description

Returns a list of user-supplied parameters and parameter values for data table unique IDs to be supplied to *pop functions.

Usage

```
tableIDs(
  cond = "PLT_CN",
  plt = "CN",
  tree = "PLT_CN",
  seedling = "PLT_CN",
  subplot = "PLT_CN",
  subp_cond = "PLT_CN",
  condid = "CONDID",
  subpid = "SUBP",
  ...
)
```

Arguments

cond	String. Unique identifier of plot in cond.
plt	String. Unique identifier of plot in plt.
tree	String. Unique identifier of plot in tree.
seedling	String. Unique identifier of plot in seedling.
subplot	String. Unique identifier of plot in subplot.
subp_cond	String. Unique identifier of plot in subp_cond.
condid	String. Unique identifier of a condition in cond.
subpid	String. Unique identifier of a subplot in subplot and subp_cond.
...	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied unique identifier of a plot in tables.

Author(s)

Tracey S. Frescino

table_options	<i>Table aesthetics and output options.</i>
---------------	---

Description

Returns a list of user-supplied parameters and parameter values for outputting tables with custom aesthetics.

Usage

```
table_options(
  row.FIAname = FALSE,
  col.FIAname = FALSE,
  row.orderby = NULL,
  col.orderby = NULL,
  row.add0 = FALSE,
  col.add0 = FALSE,
  rowlut = NULL,
  collut = NULL,
  row.classify = NULL,
  col.classify = NULL,
  rawonly = FALSE,
  raw.keep0 = FALSE,
  rowgrp = FALSE,
  rowgrpnm = NULL,
  rowgrpord = NULL,
  totals = TRUE,
  allin1 = FALSE,
  metric = FALSE,
  estround = 1,
  pseround = 2,
  estnull = "--",
  psenull = "--",
  row.NAname = "Other",
  col.NAname = row.NAname,
  divideby = NULL,
  ...
)
```


Arguments

row.FIAname	Logical. If TRUE, retrieves default FIA reference names for rowvar located in ref_codes data frame. Names are only available for certain variables (Check <code>sort(unique(ref_codes\$VARIABLE))</code> for available names. If row.FIAname = TRUE and rowvar is in ref_codes, the rowvar name is used for the output table, and the rowvar code is used to sort.
col.FIAname	Logical. If TRUE, retrieves default FIA reference names for colvar located in ref_codes data frame. Names are only available for certain variables. Check: <code>sort(unique(ref_codes\$VARIABLE))</code> for available names. If col.FIAname = TRUE and rowvar is in ref_codes, the colvar name is used for the output table, and the colvar code is used to sort.
row.orderby	String. Optional. Name of variable to sort table rows. Both the rowvar and row.orderby variables must be included in the same input data.frame. if NULL, and row.FIAname=FALSE or rowvar is not in ref_codes, the rows are ordered by rowvar.
col.orderby	String. Optional. Name of variable to sort table columns. Both the colvar and col.orderby variables must be included in the same input data.frame. if NULL, and col.FIAname=FALSE or colvar is not in ref_codes, the columns are ordered by colvar.
row.add0	Logical. If TRUE, include rows with 0 values to the output table.
col.add0	Logical. If TRUE, include columns with 0 values to the output table.
rowlut	Data frame. A lookup table with variable codes and code names to include as rows of output table (See notes for more information and format).
collut	Data frame. A lookup table with variable codes and code names to include as columns of output table (See notes for more information and format).
row.classify	Data frame (if categorical) or Vector (if continuous). If clasifying categories, input a dataframe with two columns ('FROM' and 'TO'). If clasifying continuous values, input a vector of class breaks for row
col.classify	Data frame (if categorical) or Vector (if continuous). If clasifying categories, input a dataframe with two columns ('FROM' and 'TO'). If clasifying continuous values, input a vector of class breaks for column
rawonly	Logical. If TRUE, only rawdata are output. If dataset includes many estimation units, and only raw data tables are desired, it is more efficient to output raw data only.
raw.keep0	Logical. If TRUE, keep 0 values in raw data tables.
rowgrp	Logical. If TRUE, appends row groups to first column of table. Only available if group category exists in ref_codes table or defined in rowgrpnm (e.g., FORTYPGRPCD, OWNGRPCD).
rowgrpnm	String. Name of variable for grouping rowvar. Variable must be included in same input table as rowvar.
rowgrpord	String. Name of variable to sort row group variable. Variable must be included in same input table as rowgrpnm.
totals	Logical. If TRUE, returns total estimate (mean * AREAUSED).

allin1	Logical. If TRUE, both estimates and percent sample error are output in one table as: estimates (percent sample error).
metric	Logical. If TRUE, output if returned in metric units.
estround	Integer. Number of decimal places for estimates.
pseround	Integer. Number of decimal places for percent sampling error.
estnull	Number or character. The number or symbol to use to indicate 'not sampled' for estimate.
psenull	Number or character. The number or symbol to use to indicate 'not sampled' for percent standard error.
row.NAname	String. The name to use for NA values for rows.
col.NAname	String. String. The name to use for NA values for columns.
divideby	String. Conversion number for output ('hundred', 'thousand', 'million').
...	For extendibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting tables with custom aesthetics.

Author(s)

Grayson W. White

Examples

```
table_options(row.FIAname = TRUE, col.FIAname = TRUE)
```

title_options

Title output options.

Description

Returns a list of user-supplied parameters and parameter values for outputting title with custom aesthetics.

Usage

```

title_options(
  title.main = NULL,
  title.ref = NULL,
  title.rowvar = NULL,
  title.colvar = NULL,
  title.unitvar = NULL,
  title.estvar = NULL,
  title.estvarn = NULL,
  title.filter = NULL,
  title.units = "acres",
  ...
)

```

Arguments

title.main	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: the complete title used for table. If title.main=NULL, the title.* parameters are used to generate title string. Note: if title.ref is not NULL, it is added to title.main.
title.ref	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: the ending text of the table title (e.g., Nevada, 2004-2005). If NULL, = "".
title.rowvar	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: pretty name for the row domain variable. If NULL, = rowvar.
title.colvar	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: pretty name for the column domain variable. If NULL, = colvar.
title.unitvar	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: pretty name for the estimation unit variable. If NULL, = unitvar.
title.estvar	String. TITLE: if savedata=TRUE and/or returtitle=TRUE: pretty name for the estimate variable. If NULL, title.estvar = estvar.name.
title.estvarn	String. TITLE: if savedata=TRUE and/or returtitle=TRUE: pretty name for the estimate variable. If NULL, title.estvar = estvar.name.
title.filter	String. TITLE, if savedata=TRUE and/or returtitle=TRUE: pretty name for filter(s). If title.filter=NULL, a default is generated from cfilter. If title.filter="", no title.filter is used.
title.units	String.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for outputting titles with custom aesthetics.

Author(s)

Grayson W. White

Examples

```
title_options(title.main = "My fancy title", title.estvar = "Estimate title")
```

unit_options

Unit options.

Description

Returns a list of user-supplied parameters and parameter values for unit.

Usage

```
unit_options(
  unitvar2 = NULL,
  areaunits = "acres",
  minplotnum.unit = 10,
  unit.action = "keep",
  npixelvar = "npixels",
  ...
)
```

Arguments

unitvar2	String. Name of a second level estimation unit variable in unitarea and cond or pltassgn with assignment for each plot (e.g., 'STATECD').
areaunits	String. Units of areavar in unitarea ('acres', 'hectares').
minplotnum.unit	Integer. Minimum number of plots for estimation unit.
unit.action	String. What to do if number of plots in an estimation unit is less than minplotnum.unit ('keep', 'remove', 'combine'). If unit.action='keep', estimation units with less than minplotnum.unit will be kept in output tables; if unit.action='remove', the estimation units with less than minplotnum.unit will be removed from the output tables; and if unit.action='combine', combines estimation unit to the following estimation unit, ordered in stratalut or unitzonal.
npixelvar	String. Name of variable in unitlut defining number of pixels by estimation unit.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Grayson W. White

Examples

```
unit_options()
```

xy_options	<i>List of population tables.</i>
------------	-----------------------------------

Description

Returns a list of user-supplied parameters and parameter values for data xyuation (FIA or custom) extraction to be supplied to *DB functions.

Usage

```
xy_options(
  xy.uniqueid = "CN",
  xvar = "LON",
  yvar = "LAT",
  xy.crs = 4269,
  xyjoinid = NULL,
  ...
)
```

Arguments

xy.uniqueid	String. Unique identifier of xy.
xvar	String. Name of variable in xy defining x coordinate.
yvar	String. Name of variable in xy defining y coordinate.
xy.crs	PROJ.4 String or CRS object or Integer EPSG code defining Coordinate Reference System.
xyjoinid	String. Name of variable in xy to join to plot data. If NULL, xyjoinid = xy.uniqueid.
...	For extensibility.

Details

If no parameters, an empty list is returned.

Value

A list of user-supplied parameters and parameter values for strata.

Author(s)

Tracey S. Frescino

Examples

```
xy_options(xvar="LON", yvar="LAT")
```

Index

* datasets

- GDT_NAMES, 10
- kindcd3old, 11
- ref_codes, 18
- ref_codes_archive, 19
- ref_cond, 19
- ref_conversion, 20
- ref_diacl2in, 20
- ref_domain, 21
- ref_estimators, 21
- ref_estvar, 21
- ref_evaltyp, 22
- ref_plt, 22
- ref_popType, 23
- ref_shp, 23
- ref_species, 24
- ref_statecd, 24
- ref_titles, 25
- ref_tree, 25
- ref_units, 26
- stunitco, 30

* data

- datExportData, 4
- DBtestPostgreSQL, 7
- DBtestSQLite, 8

* filters

- popFilters, 12

* list

- eval_options, 9
- popTableIDs, 14
- popTables, 16
- tableIDs, 31
- xy_options, 37

* options

- database_options, 3
- datSum_options, 5
- multest_options, 11
- savedata_options, 26
- spMakeSpatial_options, 28

- strata_options, 29
- table_options, 32
- title_options, 34
- unit_options, 36
- .update_refs, 3

- database_options, 3
- datExportData, 4
- datSum_options, 5
- DBtestPostgreSQL, 7
- DBtestSQLite, 8

- eval_options, 9

- GDT_NAMES, 10

- kindcd3old, 11

- multest_options, 11

- popFilters, 12
- popTableIDs, 14
- popTables, 16

- ref_codes, 18
- ref_codes_archive, 19
- ref_cond, 19
- ref_conversion, 20
- ref_diacl2in, 20
- ref_domain, 21
- ref_estimators, 21
- ref_estvar, 21
- ref_evaltyp, 22
- ref_plt, 22
- ref_popType, 23
- ref_shp, 23
- ref_species, 24
- ref_statecd, 24
- ref_titles, 25
- ref_tree, 25
- ref_units, 26

savedata_options, [26](#)
spMakeSpatial_options, [28](#)
strata_options, [29](#)
stunitco, [30](#)

table_options, [32](#)
tableIDs, [31](#)
title_options, [34](#)

unit_options, [36](#)

xy_options, [37](#)