

Package ‘GoodFitSBM’

January 20, 2025

Title Monte Carlo Goodness-of-Fit Tests for Stochastic Block Models

Version 0.0.1

Description Performing goodness-of-fit tests for stochastic block models used to fit network data. Among the three variants discussed in Karwa et al. (2023) <[doi:10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)>, goodness-of-fit test has been performed for the Erdos-Renyi (ER) and Beta versions.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.2.3

URL <https://github.com/Roy-SR-007/GoodFitSBM>

BugReports <https://github.com/Roy-SR-007/GoodFitSBM/issues>

Imports stats, igraph, utils, irlba

Depends R (>= 2.10)

LazyData true

Collate 'Bipartite_Walk.R' 'Estimation_BetaSBM.R' 'Estimation_Block.R'
'Estimation_ERSBM.R' 'Get_Directed_Piece.R'
'Get_Directed_Move_p1_ed.R'
'Get_Between_Blocks_Move_beta_SBM.R' 'as_arbitrary_directed.R'
'Get_Bidirected_Piece.R' 'Get_Bidirected_Move.R'
'Get_Induced_Subgraph.R' 'Get_Within_Blocks_beta_SBM.R'
'Get_Move_Beta_SBM.R' 'Get_Next_Network.R'
'Sampling_Graph_BetaSBM.R' 'TestStatistic_BetaSBM.R'
'GoFTest_BetaSBM.R' 'Sampling_Graph_ERSBM.R'
'TestStatistic_ERSBM.R' 'GoFTest_ERSBM.R' 'zachary.R'

NeedsCompilation no

Author Soham Ghosh [aut, cre],
Somjit Roy [aut],
Debdeep Pati [aut]

Maintainer Soham Ghosh <sohamghosh@tamu.edu>

Repository CRAN

Date/Publication 2024-02-23 19:10:08 UTC

Contents

get_mle_BetaSBM	2
get_mle_ERSBM	3
gofstest_BetaSBM	5
gofstest_ERSBM	7
graphchi_BetaSBM	9
graphchi_ERSBM	10
sample_a_move_BetaSBM	12
sample_a_move_ERSBM	13
zachary	15
Index	16

get_mle_BetaSBM	<i>Maximum Likelihood Estimation of edge probabilities between blocks of a graph, under beta-SBM</i>
-----------------	--

Description

get_mle_BetaSBM obtains MLE for the probability of edges between blocks in a graph, used in calculating the goodness-of-fit test statistic for the beta-SBM (Karwa et al. (2023))

Usage

```
get_mle_BetaSBM(G, C)
```

Arguments

G	an igraph object which is an undirected graph with no self loop
C	a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)

Value

A matrix of maximum likelihood estimates

mleMatr	a matrix containing the estimated edge probabilities between blocks in a graph
---------	--

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

See Also

[gofstest_BetaSBM\(\)](#) performs the goodness-of-fit test for the beta-SBM, where the MLE of the edge probabilities are required

Examples

```

RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 <- 2
n2 <- 2
n3 <- 2

# Generating block assignments for each of the nodes
n <- n1 + n2 + n3
class <- rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat <- matrix(
  c(
    0.80, 0.50, 0.50,
    0.50, 0.80, 0.50,
    0.50, 0.50, 0.80
  ),
  ncol = 3,
  byrow = TRUE
)
pmat <- cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p <- pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] <- rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm <- adj + t(adj)

# graph from the adjacency matrix
G <- igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# mle of the edge probabilities
get_mle_BetaSBM(G, class)

```

Description

get_mle_ERSBM obtains MLE for the probability of edges between blocks in a graph, used in calculating the goodness-of-fit test statistic for the ERSBM (Karwa et al. (2023))

Usage

```
get_mle_ERSBM(G, C)
```

Arguments

G an igraph object which is an undirected graph with no self loop
 C a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)

Value

A matrix of maximum likelihood estimates

mleMatr a matrix containing the estimated edge probabilities between blocks in a graph

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

See Also

[gofest_ERSBM\(\)](#) performs the goodness-of-fit test for the ERSBM, where the MLE of the edge probabilities are required

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 2
n2 = 2
n3 = 2

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    0.80, 0.05, 0.05,
    0.05, 0.80, 0.05,
```

```

    0.05, 0.05, 0.80
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# graph from the adjacency matrix
G = igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# mle of the edge probabilities
get_mle_ERSBM(G, class)

```

gofest_BetaSBM	<i>Monte Carlo goodness-of-fit test for a beta stochastic blockmodel (beta-SBM)</i>
----------------	---

Description

gofest_BetaSBM performs chi square goodness-of-fit test for network data considering the model as beta-SBM (Karwa et al. (2023))

Usage

```
gofest_BetaSBM(A, K = NULL, C = NULL, numGraphs = 100)
```

Arguments

A	n by n binary symmetric adjacency matrix representing an undirected graph where n is the number of nodes in the graph
K	positive integer scalar representing the number of blocks; $K > 1$
C	positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)
numGraphs	number of graphs to be sampled; default value is 100

Value

A list with the elements

statistic	the values of the chi-square test statistics on each sampled graph
p.value	the p-value for the test

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 10
n2 = 10
n3 = 10

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    0.80, 0.05, 0.05,
    0.05, 0.80, 0.05,
    0.05, 0.05, 0.80
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# When class assignment is known
out = gofest_BetaSBM(adjsymm, C = class, numGraphs = 10)
```

```

chi_sq_seq = out$statistic
pvalue = out$p.value
print(pvalue)

# Plotting histogram of the sequence of the test statistics
hist(chi_sq_seq, 20, xlab = "chi-square test statistics", main = NULL)
abline(v = chi_sq_seq[1], col = "red", lwd = 5) # adding test statistic on the observed network
legend("topleft", legend = paste("observed GoF = ", chi_sq_seq[1]))

```

gofest_ERSBM	<i>Monte Carlo goodness-of-fit test for an Erdős-Rényi stochastic block-model (ERSBM)</i>
--------------	---

Description

gofest_ERSBM performs chi square goodness-of-fit test for network data considering the model as ERSBM (Karwa et al. (2023))

Usage

```
gofest_ERSBM(A, K = NULL, C = NULL, numGraphs = 100)
```

Arguments

A	n by n binary symmetric adjacency matrix representing an undirected graph where n is the number of nodes in the graph
K	positive integer scalar representing the number of blocks; $K > 1$
C	positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)
numGraphs	number of graphs to be sampled; default value is 100

Value

A list with the elements	
statistic	the values of the chi-square test statistics on each sampled graph
p.value	the p-value for the test

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

Examples

```

RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 10
n2 = 10
n3 = 10

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    0.80, 0.05, 0.05,
    0.05, 0.80, 0.05,
    0.05, 0.05, 0.80
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# When class assignment is known
out = gofest_ERSBM(adjsymm, C = class, numGraphs = 10)

chi_sq_seq = out$statistic
pvalue = out$p.value
print(pvalue)

# Plotting histogram of the sequence of the test statistics
hist(chi_sq_seq, 20, xlab = "chi-square test statistics", main = NULL)
abline(v = chi_sq_seq[1], col = "red", lwd = 5) # adding test statistic on the observed network
legend("topleft", legend = paste("observed GoF = ", chi_sq_seq[1]))

```

graphchi_BetaSBM	<i>Computation of the chi-square test statistic for goodness-of-fit, under beta-SBM</i>
------------------	---

Description

graphchi_BetaSBM obtains the value of the chi-square test statistic required for the goodness-of-fit of a beta-SBM (Karwa et al. (2023))

Usage

```
graphchi_BetaSBM(G, C, p_mle)
```

Arguments

G	an igraph object which is an undirected graph with no self loop
C	a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)
p_mle	a matrix with the MLE estimates of the edge probabilities

Value

A numeric value	
teststat_val	The value of the chi-square test statistic

See Also

[gofest_BetaSBM\(\)](#) performs the goodness-of-fit test for the beta-SBM, where the values of the chi-square test statistics are required

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 2
n2 = 2
n3 = 2

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
```

```

    0.80, 0.5, 0.5,
    0.5, 0.80, 0.5,
    0.5, 0.5, 0.80
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# graph from the adjacency matrix
G = igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# mle of the edge probabilities
p.hat = get_mle_BetaSBM (G, class)

# chi-square test statistic values
graphchi_BetaSBM(G, class, p.hat)

```

graphchi_ERSBM	<i>Computation of the chi-square test statistic for goodness-of-fit, under ERSBM</i>
----------------	--

Description

graphchi_ERSBM obtains the value of the chi-square test statistic required for the goodness-of-fit of a ERSBM (Karwa et al. (2023))

Usage

```
graphchi_ERSBM(G, C, p_mle)
```

Arguments

G	an igraph object which is an undirected graph with no self loop
C	a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)
p_mle	a matrix with the MLE estimates of the edge probabilities

Value

A numeric value

teststat_val The value of the chi-square test statistic

See Also

[gofest_ERSBM\(\)](#) performs the goodness-of-fit test for the ERSBM, where the values of the chi-square test statistics are required

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 2
n2 = 2
n3 = 2

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    0.8, 0.5, 0.5,
    0.5, 0.8, 0.5,
    0.5, 0.5, 0.8
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# graph from the adjacency matrix
G = igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# mle of the edge probabilities
```

```
p.hat = get_mle_ERSBM(G, class)

# chi-square test statistic values
graphchi_ERSBM(G, class, p.hat)
```

sample_a_move_BetaSBM *Sampling a graph through a Markov move (basis) for beta-SBM*

Description

sample_a_move_BetaSBM to sample a graph in the same fiber; sampling according to the beta-SBM (Karwa et al. (2023))

Usage

```
sample_a_move_BetaSBM(C, G_current)
```

Arguments

C	a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)
G_current	an igraph object which is an undirected graph with no self loop

Value

A graph	
sampled graph	the sampled graph after one move as per the beta-SBM

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

See Also

[gofest_BetaSBM\(\)](#) performs the goodness-of-fit test for the beta-SBM, where graphs are being sampled

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 5
n2 = 5
n3 = 5
```

```

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    10, 0.05, 0.05,
    0.05, 10, 0.05,
    0.05, 0.05, 10
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# graph from the adjacency matrix
G = igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# sampling a Markov move for the beta-SBM
G_sample = sample_a_move_BetaSBM(class, G)

# plotting the sampled graph
plot(G_sample, main = "The sampled graph after one Markov move for beta-SBM")

```

sample_a_move_ERSBM *Sampling a graph through a Markov move (basis) for ERSBM*

Description

sample_a_move_ERSBM to sample a graph in the same fiber; sampling according to the ERSBM (Karwa et al. (2023))

Usage

```
sample_a_move_ERSBM(C, G_current)
```

Arguments

C a positive integer vector of size n for block assignments of each node; from 1 to K (no of blocks)

G_current an igraph object which is an undirected graph with no self loop

Value

A graph

sampled graph the sampled graph after one move as per the ERSBM

References

Karwa et al. (2023). "Monte Carlo goodness-of-fit tests for degree corrected and related stochastic blockmodels", *Journal of the Royal Statistical Society Series B: Statistical Methodology*, doi:[10.1093/jrsssb/qkad084](https://doi.org/10.1093/jrsssb/qkad084)

See Also

[gofest_ERSBM\(\)](#) performs the goodness-of-fit test for the ERSBM, where graphs are being sampled

Examples

```
RNGkind(sample.kind = "Rounding")
set.seed(1729)

# We model a network with 3 even classes
n1 = 5
n2 = 5
n3 = 5

# Generating block assignments for each of the nodes
n = n1 + n2 + n3
class = rep(c(1, 2, 3), c(n1, n2, n3))

# Generating the adjacency matrix of the network
# Generate the matrix of connection probabilities
cmat = matrix(
  c(
    10, 0.05, 0.05,
    0.05, 10, 0.05,
    0.05, 0.05, 10
  ),
  ncol = 3,
  byrow = TRUE
)
pmat = cmat / n

# Creating the n x n adjacency matrix
adj <- matrix(0, n, n)
```

```
for (i in 2:n) {
  for (j in 1:(i - 1)) {
    p = pmat[class[i], class[j]] # We find the probability of connection with the weights
    adj[i, j] = rbinom(1, 1, p) # We include the edge with probability p
  }
}

adjsymm = adj + t(adj)

# graph from the adjacency matrix
G = igraph::graph_from_adjacency_matrix(adjsymm, mode = "undirected", weighted = NULL)

# sampling a Markov move for the ERSBM
G_sample = sample_a_move_ERSBM(class, G)

# plotting the sampled graph
plot(G_sample, main = "The sampled graph after one Markov move for ERSBM")
```

zachary

Zachary Karate Club Data

Description

Zachary's Karate club data is a classic, well-studied social network of friendships between 34 members of a Karate club at a US university, collected by Wayne Zachary in 1977. Each node represents a member of the club, and each edge represents a tie between two members of the club. The network is undirected. An often discussed problem using this dataset is to find the two groups of people into which the karate club split after an argument between two teachers. Refer to the example in README.

Usage

zachary

Format

Two 34 by 34 matrices:

ZACHE symmetric, binary 34 by 34 adjacency matrix.

ZACHC symmetric, valued 34 by 34 matrix, indicating the relative strength of the associations

Source

(Zachary, 1977), <http://vlado.fmf.uni-lj.si/pub/networks/data/Ucinet/UciData.htm#zachary>.

Index

* datasets

zachary, [15](#)

get_mle_BetaSBM, [2](#)

get_mle_ERSBM, [3](#)

gofitest_BetaSBM, [5](#)

gofitest_BetaSBM(), [2](#), [9](#), [12](#)

gofitest_ERSBM, [7](#)

gofitest_ERSBM(), [4](#), [11](#), [14](#)

graphchi_BetaSBM, [9](#)

graphchi_ERSBM, [10](#)

sample_a_move_BetaSBM, [12](#)

sample_a_move_ERSBM, [13](#)

zachary, [15](#)