

Package ‘Slick’

September 11, 2025

Type Package

Title Interactive Visualization of MSE Results

Version 1.0.0

Maintainer Adrian Hordyk <adrian@bluematterscience.com>

Description A framework for visualizing and exploring results of a Management Strategy Evaluation (MSE). The publication quality figures and tables can be developed directly from the R console, or interactively explored with the 'Slick' App. For more details, see the `Slick` website <<https://slick.bluematterscience.com>>.

URL <https://slick.bluematterscience.com/>,
<https://github.com/Blue-Matter/Slick>

License GPL-2

Depends R (>= 4.1.0)

Imports cli, dplyr, DT, ggplot2, ggrepel, golem, graphics, grDevices, methods, scales, shiny, stats, tibble, utils

Suggests bookdown, colourpicker, colorspace, cowplot, esquisse, flextable, fresh, httr, kableExtra, knitr, MSEtool, openMSE, RColorBrewer, shiny.i18n, shinyalert, shinyBS, shinycssloaders, shinydashboard, shinydashboardPlus, shinyhelper, shinyjs, shinyWidgets, rmarkdown, testthat (>= 3.0.0), waiter

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.3

Collate 'RunSlick.R' 'Slick_tools.R' 'a_classunions.R' 'a_imports.R' 'aa_generics.R' 'app_config.R' 'app_server.R' 'app_ui.R' 'class_Boxplot.R' 'class_Check.R' 'class_Kobe.R' 'class_MPs.R' 'class_OMs.R' 'class_Quilt.R' 'class_Tradeoff.R' 'class_Timeseries.R' 'class_Spider.R' 'class_Slick.R' 'fct_FilterSlick.R' 'fct_Update.R' 'fct_check_required_packages.R' 'fct_check_slick.R' 'fct_colors.R' 'fct_dashboardHeader2.R'

'fct_load_casestudies.R' 'fct_misc.R' 'fct_plotBoxplot.R'
 'fct_plotKobe.R' 'fct_plotQuilt.R' 'fct_plotSpider.R'
 'fct_plotTimeseries.R' 'fct_plotTradeoff.R' 'fct_translator.R'
 'make_Slick_old.R' 'man_functions.R' 'misc.R' 'mod_About.R'
 'mod_Boxplot.R' 'mod_Boxplot_OM.R' 'mod_Boxplot_overall.R'
 'mod_Global_Filters.R' 'mod_Home.R' 'mod_Kobe.R'
 'mod_Kobe_overall.R' 'mod_Kobe_time.R' 'mod_MP_Color.R'
 'mod_MP_Info.R' 'mod_Metadata.R' 'mod_OM_Info.R'
 'mod_PM_Info.R' 'mod_Page_Filter.R' 'mod_Quilt.R'
 'mod_Report_Add.R' 'mod_Report_Add_Button.R'
 'mod_Report_Page.R' 'mod_Report_Page_plot.R' 'mod_Resources.R'
 'mod_Sidebar.R' 'mod_Spider.R' 'mod_Spider_MPR.R'
 'mod_Spider_OM.R' 'mod_Spider_overall.R' 'mod_Timeseries.R'
 'mod_Timeseries_byMPR.R' 'mod_Timeseries_byOM.R'
 'mod_Timeseries_overall.R' 'mod_Tradeoff.R'
 'mod_filter_selection.R' 'mod_filter_selection_OM.R'
 'mod_subtitle.R' 'mod_toplink.R' 'utils_Table.R' 'utils_util.R'

BugReports <https://github.com/Blue-Matter/Slick/issues>

NeedsCompilation no

Author Adrian Hordyk [aut, cre],
 Tom Carruthers [aut],
 Quang Huynh [aut],
 Shana Miller [aut]

Repository CRAN

Date/Publication 2025-09-11 09:20:18 UTC

Contents

App	3
Boxplot	4
Boxplot-class	7
Check	8
Code	10
Color	15
Defaults	16
default_mp_colors	17
Design	17
Factors	18
FilterSlick	19
get_casestudies	20
Kobe	21
Kobe-class	25
Limit	27
Make_Slick	29
Metadata	31
MinValue	33

MPs	34
MPs-class	36
NewSlick	37
OMs	38
OMs-class	40
plotBoxplot	42
plotKobe	44
plotQuilt	46
plotSpider	48
plotTimeseries	51
plotTradeoff	55
PMnorm	56
Preset	57
Quilt	59
Quilt-class	62
RefPoints	64
show	65
Slick-class	66
Spider	70
Spider-class	73
Time	75
TimeLab	76
TimeNow	77
Timeseries	78
Timeseries-class	82
TimeTerminal	85
Tradeoff	86
Tradeoff-class	89
Update	90
Value	91
Index	93

App

Run the Slick App in the local browser

Description

An online hosted version of the Slick App is available [here](#)

Usage

App(...)

Arguments

... Additional arguments. To load a object directly in the App, use App(slick=myslick) where myslick is your `Slick-class()` object.

Details

`App()` runs the Slick Shiny Application

Value

None

Boxplot

Methods for Creating, Accessing and Assigning Boxplot objects

Description

The `Boxplot` function is used both to create and modify an `Boxplot-class()` object. and to access and assign `Boxplot` for an object of class `Slick-class()`. See Details.

Usage

```
Boxplot(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list(),
  Defaults = list("overall", "boxplot")
)

Boxplot(Slick) <- value

## S4 method for signature 'missing'
Boxplot()

## S4 method for signature 'character_list'
Boxplot(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list(),
  Defaults = list("overall", "boxplot")
)

## S4 method for signature 'Slick'
Boxplot(Code)

## S4 replacement method for signature 'Slick'
Boxplot(Slick) <- value
```

Arguments

Code	A <i>short</i> code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details
Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Mark-down, see Examples . A character string length nPI or a named list for multi-language support. See Details
Value	A numeric array with the stochastic performance indicator values for each simulation (sim), operating model (OM), management procedure (MP), and performance indicator (PI). Dimensions: c(nsim, nOM, nMP, and nPI).
Preset	An optional named list for the preset buttons in the App() . The name of the list element will appear as a button in the App() .
Defaults	A list object with default selections for the Boxplot
Slick	A Slick-class() object
value	A Boxplot-class() object

Details

Objects of class Boxplot are created with [Boxplot\(\)](#)

Use [plotBoxplot\(\)](#) to create the boxplot from the console.

Use the [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#) functions to access and assign the values for an existing Boxplot object, see [Examples](#)

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in Code, Label, and Description must all be same length as the number of performance indicators (nPIs) in 'Value'

Defaults:

Defaults is used to select the plot options that are selected in the Boxplot. It is a list of length 2, with the following requirements for the list elements:

1. A character string. Options: 'overall' (default) or 'byom'
2. A character string. Options: 'boxplot' (default), 'violin', or 'both'

If unrecognized values are entered, the defaults will be used.

Functions

- `Boxplot(missing)`: Create an empty Boxplot object
- `Boxplot(character_list)`: Create a populated Boxplot object
- `Boxplot(Slick)`: Return Boxplot from a `Slick-class()` object
- `Boxplot(Slick) <- value`: Assign a `Boxplot-class()` object to a `Slick-class()` object

See Also

[Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Metadata\(\)](#), [Value\(\)](#), [Preset\(\)](#), [Defaults\(\)](#), [plotBoxplot\(\)](#)

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 3

values <- array(NA, dim=c(nsim, nOM, nMP, nPI))
pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi] <- rlnorm(nsim, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
boxplot <- Boxplot(Code=c('PI1', 'PI2', 'PI3'),
                  Label=c('Performance Indicator 1',
                          'Performance Indicator 2',
                          'Performance Indicator 3'),
                  Description = c('This is the description for PI 1',
                                  'This is the description for PI 2',
                                  'This is the description for PI 3'),
                  Value=values)

# Check
Check(boxplot)

# Add to `Slick` object
slick <- Slick()
Boxplot(slick) <- boxplot

# Plots
plotBoxplot(slick)

plotBoxplot(slick, type='violin')

plotBoxplot(slick, byOM=TRUE)
```

```
plotBoxplot(slick, 2, type='both', byOM=TRUE)
```

 Boxplot-class

 Boxplot *S4 Object Class*

Description

Objects of class `Boxplot` are used to store information for the `Boxplot` and `Violin` plots. Like all `S4` objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See [Boxplot\(\)](#) and the the See Also section below.

Details

Objects of class `Boxplot` are created with `Boxplot()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (`nPIs`) in `Value`

Slots

Code A *short* code for the Performance Indicators for this object. A character string length `nPI` or a named list for multi-language support. See [Details](#)

Label A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than `Code` but recommended to keep short as possible so it shows clearly in plots and tables. A character string length `nPI` or a named list for multi-language support. See [Details](#)

Description A description for the Performance Indicators for this object. Can include `Markdown`, see [Examples](#). A character string length `nPI` or a named list for multi-language support. See [Details](#)

Value A numeric array with the stochastic performance indicator values for each simulation (`sim`), operating model (`OM`), management procedure (`MP`), and performance indicator (`PI`). Dimensions: `c(nsim, nOM, nMP, and nPI)`.

Preset An optional named list for the preset buttons in the [App\(\)](#). The name of the list element will appear as a button in the [App\(\)](#).

Defaults A list object with default selections for the `Boxplot`. See [Boxplot\(\)](#)

See Also

[Boxplot\(\)](#), [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Metadata\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 3

values <- array(NA, dim=c(nsim, nOM, nMP, nPI))
pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi] <- rlnorm(nsim, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
boxplot <- Boxplot(Code=c('PI1', 'PI2', 'PI3'),
                  Label=c('Performance Indicator 1',
                          'Performance Indicator 2',
                          'Performance Indicator 3'),
                  Description = c('This is the description for PI 1',
                                  'This is the description for PI 2',
                                  'This is the description for PI 3'),
                  Value=values)

# Check
Check(boxplot)

# Add to `Slick` object
slick <- Slick()
Boxplot(slick) <- boxplot

# Plots
plotBoxplot(slick)

plotBoxplot(slick, type='violin')

plotBoxplot(slick, byOM=TRUE)

plotBoxplot(slick, 2, type='both', byOM=TRUE)
```


Description

Checks S4 objects to check for warnings and errors

Usage

```
Check(object, ...)  
  
## S4 method for signature 'Boxplot'  
Check(object, req_dims = c(NA, NA, NA, NA))  
  
## S4 method for signature 'Kobe'  
Check(object)  
  
## S4 method for signature 'MPs'  
Check(object)  
  
## S4 method for signature 'OMs'  
Check(object)  
  
## S4 method for signature 'Quilt'  
Check(object)  
  
## S4 method for signature 'Tradeoff'  
Check(object)  
  
## S4 method for signature 'Timeseries'  
Check(object)  
  
## S4 method for signature 'Spider'  
Check(object)  
  
## S4 method for signature 'Slick'  
Check(object)
```

Arguments

object	An object of class: Slick-class() , MPs-class() , OMs-class() or the six chart types: Boxplot-class() , Kobe-class() , Quilt-class() , Spider-class() , Timeseries-class() , and Tradeoff-class() .
...	Additional arguments
req_dims	Required dimensions for Value slot. Used internally

Value

Prints messages to the console

Methods (by class)

- Check(Boxplot): Check `Boxplot-class()` objects for errors
- Check(Kobe): Check `Kobe-class()` objects for errors
- Check(MPs): Check `MPs-class()` objects for errors
- Check(OMs): Check `OMs-class()` objects for errors
- Check(Quilt): Check `Quilt-class()` objects for errors
- Check(Tradeoff): Check `Tradeoff-class()` objects for errors
- Check(Timeseries): Check `Timeseries-class()` objects for errors
- Check(Spider): Check `Spider-class()` objects for errors
- Check(Slick): Check `Slick-class()` objects for errors

Examples

```
slick <- Slick()
Check(slick)
```

Code	<i>Access or assign Code, Label, and Description for a valid object class</i>
------	---

Description

Access or assign Code, Label, and Description for a valid object class

Usage

```
Code(object, lang = "en")

Code(object) <- value

Description(object, lang = "en")

Description(object) <- value

Label(object, lang = "en")

Label(object) <- value

## S4 method for signature 'Boxplot'
Code(object, lang = "en")

## S4 replacement method for signature 'Boxplot'
Code(object) <- value
```

```
## S4 method for signature 'Boxplot'
Description(object, lang = "en")

## S4 method for signature 'Boxplot'
Label(object, lang = "en")

## S4 replacement method for signature 'Boxplot'
Label(object) <- value

## S4 replacement method for signature 'Boxplot'
Description(object) <- value

## S4 method for signature 'Kobe'
Code(object, lang = "en")

## S4 replacement method for signature 'Kobe'
Code(object) <- value

## S4 method for signature 'Kobe'
Description(object, lang = "en")

## S4 replacement method for signature 'Kobe'
Description(object) <- value

## S4 method for signature 'Kobe'
Label(object, lang = "en")

## S4 replacement method for signature 'Kobe'
Label(object) <- value

## S4 method for signature 'MPs'
Code(object, lang = "en")

## S4 replacement method for signature 'MPs'
Code(object) <- value

## S4 method for signature 'MPs'
Label(object, lang = "en")

## S4 replacement method for signature 'MPs'
Label(object) <- value

## S4 method for signature 'MPs'
Description(object, lang = "en")

## S4 replacement method for signature 'MPs'
Description(object) <- value
```

```
## S4 method for signature 'Quilt'
Code(object, lang = "en")

## S4 replacement method for signature 'Quilt'
Code(object) <- value

## S4 method for signature 'Quilt'
Description(object, lang = "en")

## S4 replacement method for signature 'Quilt'
Description(object) <- value

## S4 method for signature 'Quilt'
Label(object, lang = "en")

## S4 replacement method for signature 'Quilt'
Label(object) <- value

## S4 method for signature 'Tradeoff'
Code(object, lang = "en")

## S4 replacement method for signature 'Tradeoff'
Code(object) <- value

## S4 method for signature 'Tradeoff'
Description(object, lang = "en")

## S4 replacement method for signature 'Tradeoff'
Description(object) <- value

## S4 method for signature 'Tradeoff'
Label(object, lang = "en")

## S4 replacement method for signature 'Tradeoff'
Label(object) <- value

## S4 method for signature 'Timeseries'
Code(object, lang = "en")

## S4 replacement method for signature 'Timeseries'
Code(object) <- value

## S4 method for signature 'Timeseries'
Description(object, lang = "en")

## S4 replacement method for signature 'Timeseries'
Description(object) <- value
```

```

## S4 method for signature 'Timeseries'
Label(object, lang = "en")

## S4 replacement method for signature 'Timeseries'
Label(object) <- value

## S4 method for signature 'Spider'
Code(object, lang = "en")

## S4 replacement method for signature 'Spider'
Code(object) <- value

## S4 method for signature 'Spider'
Description(object, lang = "en")

## S4 replacement method for signature 'Spider'
Description(object) <- value

## S4 method for signature 'Spider'
Label(object, lang = "en")

## S4 replacement method for signature 'Spider'
Label(object) <- value

```

Arguments

object	An object of class <code>MPs-class()</code> , <code>Boxplot-class()</code> , <code>Kobe-class()</code> , <code>Quilt-class()</code> , <code>Spider-class()</code> , <code>Timeseries-class()</code> , or <code>Tradeoff-class()</code>
lang	Optional text string specifying the language (if available). Either 'en', 'es', or 'fr' for English, Spanish, or French respectively
value	A character vector or a named list for multi-language support

Details

Code, Label, and Description must all be equal length.

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Value

Returns character string or named list with the contents of the Code, Label, or Description slot of object

Methods (by class)

- `Code(Boxplot)`: Return Code from a `Boxplot-class()` object
- `Code(Boxplot) <- value`: Assign Code to a `Boxplot-class()` object
- `Description(Boxplot)`: Return Description from a `Boxplot-class()` object
- `Label(Boxplot)`: Return Label from a `Boxplot-class()` object
- `Label(Boxplot) <- value`: Assign Label to a `Boxplot-class()` object
- `Description(Boxplot) <- value`: Assign Description to a `Boxplot-class()` object
- `Code(Kobe)`: Return Code from a `Kobe-class()` object
- `Code(Kobe) <- value`: Assign Code to a `Kobe-class()` object
- `Description(Kobe)`: Return Description from a `Kobe-class()` object
- `Description(Kobe) <- value`: Assign Description to a `Kobe-class()` object
- `Label(Kobe)`: Return Label from a `Kobe-class()` object
- `Label(Kobe) <- value`: Assign Label to a `Kobe-class()` object
- `Code(MPs)`: Return Code from a `MPs-class()` object
- `Code(MPs) <- value`: Assign Code to a `MPs-class()` object
- `Label(MPs)`: Return Label from a `MPs-class()` object
- `Label(MPs) <- value`: Assign Label to a `MPs-class()` object
- `Description(MPs)`: Return Description from a `MPs-class()` object
- `Description(MPs) <- value`: Assign Description to a `MPs-class()` object
- `Code(Quilt)`: Return Code from a `Quilt-class()` object
- `Code(Quilt) <- value`: Assign Code to a `Quilt-class()` object
- `Description(Quilt)`: Return Description from a `Quilt-class()` object
- `Description(Quilt) <- value`: Assign Description to a `Quilt-class()` object
- `Label(Quilt)`: Return Label from a `Quilt-class()` object
- `Label(Quilt) <- value`: Assign Label to a `Quilt-class()` object
- `Code(Tradeoff)`: Return Code from a `Tradeoff-class()` object
- `Code(Tradeoff) <- value`: Assign Code to a `Tradeoff-class()` object
- `Description(Tradeoff)`: Return Description from a `Tradeoff-class()` object
- `Description(Tradeoff) <- value`: Assign Description to a `Tradeoff-class()` object
- `Label(Tradeoff)`: Return Label from a `Tradeoff-class()` object
- `Label(Tradeoff) <- value`: Assign Label to a `Tradeoff-class()` object
- `Code(Timeseries)`: Return Code from a `Timeseries-class()` object
- `Code(Timeseries) <- value`: Assign Code to a `Timeseries-class()` object
- `Description(Timeseries)`: Return Description from a `Timeseries-class()` object
- `Description(Timeseries) <- value`: Assign Description to a `Timeseries-class()` object
- `Label(Timeseries)`: Return Label from a `Timeseries-class()` object

- `Label(Timeseries) <- value`: Assign Label to a `Timeseries-class()` object
- `Code(Spider)`: Return Code from a `Spider-class()` object
- `Code(Spider) <- value`: Assign Code to a `Spider-class()` object
- `Description(Spider)`: Return Description from a `Spider-class()` object
- `Description(Spider) <- value`: Assign Description to a `Spider-class()` object
- `Label(Spider)`: Return Label from a `Spider-class()` object
- `Label(Spider) <- value`: Assign Label to a `Spider-class()` object

See Also

[Label\(\)](#), [Description\(\)](#), [MPs-class\(\)](#), [Boxplot-class\(\)](#), [Kobe-class\(\)](#), [Quilt-class\(\)](#), [Spider-class\(\)](#), [Timeseries-class\(\)](#), [Tradeoff-class\(\)](#)

Color

Access or assign Color for MPs and Quilt objects

Description

Access or assign Color for MPs and Quilt objects

Usage

```
Color(object)

Color(object) <- value

## S4 method for signature 'MPs'
Color(object)

## S4 replacement method for signature 'MPs'
Color(object) <- value

## S4 method for signature 'Quilt'
Color(object)

## S4 replacement method for signature 'Quilt'
Color(object) <- value
```

Arguments

<code>object</code>	An <code>MPs-class()</code> or <code>Quilt-class()</code> object
<code>value</code>	A character vector formatted to match the class of object. See the documentation for corresponding object class for more details.

Value

Returns a character string with the contents of the Color slot of object

Methods (by class)

- `Color(MPs)`: Return Color from a `MPs-class()` object
- `Color(MPs) <- value`: Preset Assign Color to a `MPs-class()` object
- `Color(Quilt)`: Return Color from a `Quilt-class()` object
- `Color(Quilt) <- value`: Preset Assign Color to a `Quilt-class()` object

Defaults

Access or assign the default selections for the plots in the App()

Description

Access or assign the default selections for the plots in the App()

Usage

```
Defaults(object)
```

```
Defaults(object) <- value
```

```
## S4 method for signature 'Boxplot'
```

```
Defaults(object)
```

```
## S4 replacement method for signature 'Boxplot'
```

```
Defaults(object) <- value
```

```
## S4 method for signature 'Kobe'
```

```
Defaults(object)
```

```
## S4 replacement method for signature 'Kobe'
```

```
Defaults(object) <- value
```

Arguments

object A `Boxplot()` or `Kobe()` object

value A list of default selections for the `App()`

Value

Returns a list object with default selections from the Defaults slot of `Boxplot()` and `Kobe()` objects.

Methods (by class)

- Defaults(Boxplot): Defaults Code from a `Boxplot-class()` object
- Defaults(Boxplot) <- value: Assign Defaults to a `Boxplot-class()` object
- Defaults(Kobe): Defaults Code from a `Kobe-class()` object
- Defaults(Kobe) <- value: Assign Defaults to a `Kobe-class()` object

default_mp_colors	<i>Set Default Colors for the MPs</i>
-------------------	---------------------------------------

Description

Requires the colorspace package

Usage

```
default_mp_colors(nMP)
```

Arguments

nMP The number of management procedures

Value

A character vector of length nMP with color hex codes

Examples

```
cols <- default_mp_colors(4)
cols
```

Design	<i>Return the Design matrix from an OMs object</i>
--------	--

Description

Return the Design matrix from an OMs object

Usage

```

Design(object)

Design(object) <- value

## S4 method for signature 'OMs'
Design(object)

## S4 replacement method for signature 'OMs'
Design(object) <- value

## S4 method for signature 'Slick'
Design(object)

## S4 replacement method for signature 'Slick'
Design(object) <- value

```

Arguments

object	A Slick-class() object
value	A <code>data.frame</code> with the Design matrix

Value

The Design matrix from an OMs object in a Slick object

Methods (by class)

- `Design(OMs)`: Return the operating model Design matrix from a [OMs-class\(\)](#) object
- `Design(OMs) <- value`: Assign the operating model Design matrix to a [OMs-class\(\)](#) object
- `Design(Slick)`: Access the operating model Design matrix from a [Slick-class\(\)](#) object
- `Design(Slick) <- value`: Assign the operating model Design matrix to a [Slick-class\(\)](#) object

Factors

Return the Factors matrix from an OMs object

Description

Return the Factors matrix from an OMs object

Usage

```

Factors(object, lang = "en")

Factors(object) <- value

## S4 method for signature 'OMs'
Factors(object, lang = "en")

## S4 replacement method for signature 'OMs'
Factors(object) <- value

## S4 method for signature 'Slick'
Factors(object, lang = "en")

## S4 replacement method for signature 'Slick'
Factors(object) <- value

```

Arguments

object	A Slick-class() object
lang	Optional text string specifying the language (if available). Either 'en', 'es', or 'fr' for English, Spanish, or French respectively
value	A data.frame with the Factors

Value

The Design matrix from an OMs object in a Slick object

Methods (by class)

- `Factors(OMs)`: Return the operating model Factors table from a [OMs-class\(\)](#) object
- `Factors(OMs) <- value`: Assign the operating model Factors table to a [OMs-class\(\)](#) object
- `Factors(Slick)`: Access the operating model Factors table from a [Slick-class\(\)](#) object
- `Factors(Slick) <- value`: Assign the operating model Factors table to a [Slick-class\(\)](#) object

 FilterSlick

FilterSlick

Description

Filter a Slick Object

Usage

```
FilterSlick(slick = NULL, MPs = NULL, OMs = NULL, PIs = NULL, plot = NULL)
```

Arguments

slick	An object of class Slick
MPs	Numeric values of the MPs to keep. Default NULL keeps all MPs.
OMs	Numeric values of the OMs to keep (rows of OM@Design). Default NULL keeps all OMs.
PIs	Numeric values of the PIs in plot to keep. Default NULL keeps all PIs.
plot	The plot to filter the PIs. One of: Timeseries, Boxplot, Kobe, Quilt, Spider, orTradeoff

Details

Filter a Slick Object by management procedures (MPs), operating models (OMs), and performance indicators (PIs) for a given plot

Value

A filtered Slick Object

Examples

```
slick <- Slick() # a completed slick object
boxplot_OM_1 <- FilterSlick(slick, OMs=1, plot='boxplot')
```

get_casestudies

Get Case Studies from the SlickLibrary GitHub Repo

Description

Get Case Studies from the SlickLibrary GitHub Repo

Usage

```
get_casestudies()

download_casestudy(
  name,
  case_studies = NULL,
  dir = NULL,
  silent = FALSE,
  object = TRUE,
  delete = object
)
```

Arguments

name	The name of the case study to download. Name column from <code>get_casestudies()</code>
case_studies	optional. Dataframe returned by <code>get_casestudies()</code>
dir	Optional. Directory to save the file. Defaults to a temporary directory
silent	Logical. Print out messages?
object	Logical. Return the Slick object? Default downloads Slick object to a temporary location, loads and returns the Slick object, and then deletes downloaded file.
delete	Logical. Delete the downloaded file after function finishes? Only useful if <code>object = TRUE</code>

Value

A data.frame for `get_casestudies` and a Slick object for `download_casestudy`
 The downloaded Slick object if `object==TRUE`, otherwise nothing.

Functions

- `download_casestudy()`: download a case study file

Examples

```
case_studies <- get_casestudies()
slick <- download_casestudy(case_studies$Name[1])
```

Description

The Kobe function is used both to create and modify an `Kobe-class()` object. and to access and assign Kobe for an object of class `Slick-class()`. See Details.

Usage

```
Kobe(
  Code = "",
  Label = "",
  Description = "",
  Time = numeric(),
  TimeLab = "Year",
  Value = array(),
  Preset = list(),
  Target = 1,
  Limit = NULL,
```

```

    Defaults = list(),
    TimeTerminal = numeric()
)

Kobe(Slick) <- value

## S4 method for signature 'missing'
Kobe()

## S4 method for signature 'character'
Kobe(
  Code = "",
  Label = "",
  Description = "",
  Time = numeric(),
  TimeLab = "Year",
  Value = array(),
  Preset = list(),
  Target = 1,
  Limit = NULL,
  Defaults = list(),
  TimeTerminal = numeric()
)

## S4 method for signature 'list'
Kobe(
  Code = "",
  Label = "",
  Description = "",
  Time = numeric(),
  TimeLab = "Year",
  Value = array(),
  Preset = list(),
  Target = 1,
  Limit = NULL,
  Defaults = list(),
  TimeTerminal = numeric()
)

## S4 method for signature 'Slick'
Kobe(Code)

## S4 replacement method for signature 'Slick'
Kobe(Slick) <- value

```

Arguments

Code A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details

Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Markdown, see Examples. A character string length nPI or a named list for multi-language support. See Details
Time	A numeric vector with values for the projection time-steps. Must match length nTS in Value
TimeLab	Character string length 1. Name of the time step (e.g., 'Year'). Will be used as the label in the Kobe Time plot. Use a named list for multiple languages.
Value	A numeric array with the stochastic performance indicator values for each simulation (sim), operating model (OM), management procedure (MP), performance indicator (PI), and projection time-steps (nTS). Dimensions: c(nsim, nOM, nMP, nPI, nTS)
Preset	An optional named list for the preset buttons in the <code>App()</code> . The name of the list element will appear as a button in the <code>App()</code> .
Target	Numeric vector length nPI with the target value for the PIs. Defines the color quadrants on the Kobe plot. Defaults to c(1,1).
Limit	Numeric vector length nPI with the limit value for the PIs. Shows as red line on Kobe plot. NULL to ignore.
Defaults	A list object with default selections for the Kobe See <code>Kobe()</code>
TimeTerminal	Optional. By default the Kobe plot shows the terminal projection year. TimeTerminal can be used to override this. Use a numeric value indicating the time (must match a value in Time) to use for the Kobe plot
Slick	A <code>Slick-class()</code> object
value	A <code>Kobe-class()</code> object

Details

Objects of class Kobe are created with `Kobe()`

The Kobe plot typically shows B/BMSY (or something similar) on the x-axis, and F/FMSY (or something similar) on the y-axis.

Performance Indicators:

The first PI will be on the x-axis (usually B/BMSY or something similar) and the second on the y-axis (e.g., F/FMSY)

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in Code, Label, and Description must all be same length as the number of performance indicators (nPIs) in Value

Functions

- `Kobe(missing)`: Create an empty Kobe object
- `Kobe(character)`: Create a populated Kobe object
- `Kobe(list)`: Create a populated Kobe object
- `Kobe(Slick)`: Return Kobe from a `Slick-class()` object
- `Kobe(Slick) <- value`: Assign a `Kobe-class()` object to a `Slick-class()` object

See Also

`Code()`, `Label()`, `Description()`, `Time()`, `[TimeLab()`, `Value()`, `Preset()`, `Target()` and `Limit()`

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 2
nTS <- 30

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1)

for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi,] <- pi_means[pi] *
        matrix(
          cumprod(c(rlnorm(nTS*nsim, 0, 0.05))),
          nrow=nsim)
    }
  }
}

# Create and populate Object
kobe <- Kobe(Code=c('B/BMSY', 'F/FMSY'),
            Label=c('B/BMSY',
                  'F/FMSY'),
            Description = c('This is the description for PI 1',
                           'This is the description for PI 2'),
            Value=values
)

# Add values for projection time steps
Time(kobe) <- seq(2025, by=1, length.out=nTS)

# Check
Check(kobe)
```



```
# Add to `Slick` object
slick <- Slick()
Kobe(slick) <- kobe

# Plots
plotKobe(slick)

plotKobe(slick, Time=TRUE)
```

Kobe-class

S4 class Kobe

Description

Slots can be accessed and assigned using functions corresponding to slot name. See [See Also](#) section below.

Details

Objects of class Kobe are created with `Kobe()`

Performance Indicators:

By default, the first PI will be on the x-axis (usually B/BMSY or something similar) and the second on the y-axis (e.g., F/FMSY). The Slick `App()` provides drop down menus for selecting other PIs.

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Slots

Code A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See [Details](#)

Label A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than `Code` but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See [Details](#)

Description A description for the Performance Indicators for this object. Can include Markdown, see [Examples](#). A character string length nPI or a named list for multi-language support. See [Details](#)

- Time** A numeric vector with values for the projection time-steps. Must match length `nTS` in `Value`
- TimeLab** Character string length 1. Name of the time step (e.g., 'Year'). Will be used as the label in the Kobe Time plot. Use a named list for multiple languages.
- Value** A numeric array with the stochastic performance indicator values for each simulation (`sim`), operating model (`OM`), management procedure (`MP`), performance indicator (`PI`), and projection time-steps (`nTS`) Dimensions: `c(nsim, nOM, nMP, nPI, nTS)`
- Preset** An optional named list for the preset buttons in the `App()`. The name of the list element will appear as a button in the `App()`.
- Target** Numeric vector length `nPI` with the target value for the PIs. Defines the color quadrants on the Kobe plot. Defaults to 1.
- Limit** Numeric vector length `nPI` with the limit value for the two PIs. Shows as red line on Kobe plot. NULL to ignore.
- Defaults** A list object with default selections for the Kobe See `Kobe()`
- TimeTerminal** Optional. By default the Kobe plot shows the terminal projection year. `TimeTerminal` can be used to override this. Use a numeric value indicating the time (must match a value in `Time`) to use for the Kobe plot

See Also

[Kobe\(\)](#), [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 2
nTS <- 30

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1)

for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi,] <- pi_means[pi] *
        matrix(
          cumprod(c(rlnorm(nTS*nsim, 0, 0.05))),
          nrow=nsim)
    }
  }
}

# Create and populate Object
kobe <- Kobe(Code=c('B/BMSY', 'F/FMSY'),
             Label=c('B/BMSY',
                    'F/FMSY'),
```

```

        Description = c('This is the description for PI 1',
                        'This is the description for PI 2'),
        Value=values
    )

# Add values for projection time steps
Time(kobe) <- seq(2025, by=1, length.out=nTS)

# Check
Check(kobe)

# Add to `Slick` object
slick <- Slick()
Kobe(slick) <- kobe

# Plots
plotKobe(slick)

plotKobe(slick, Time=TRUE)

```

Limit	<i>Access or assign Target and Limit for object of class Kobe or Timeseries</i>
-------	---

Description

Access or assign Target and Limit for object of class Kobe or Timeseries

Usage

```

Limit(object)

Limit(object) <- value

Target(object)

Target(object) <- value

## S4 method for signature 'Kobe'
Limit(object)

## S4 replacement method for signature 'Kobe'
Limit(object) <- value

## S4 method for signature 'Kobe'
Target(object)

## S4 replacement method for signature 'Kobe'

```

```
Target(object) <- value

## S4 method for signature 'Timeseries'
Limit(object)

## S4 replacement method for signature 'Timeseries'
Limit(object) <- value

## S4 method for signature 'Timeseries'
Target(object)

## S4 replacement method for signature 'Timeseries'
Target(object) <- value
```

Arguments

object	A Kobe-class() or Timeseries() class object
value	Value to assign to Target

Value

Returns a numeric vector with the contents of the Target or Limit slots of [Kobe\(\)](#) and [Timeseries\(\)](#) objects

Methods (by class)

- `Limit(Kobe)`: Return Limit from a [Kobe-class\(\)](#) object
- `Limit(Kobe) <- value`: Assign Limit to a [Kobe-class\(\)](#) object
- `Target(Kobe)`: Return Target from a [Kobe-class\(\)](#) object
- `Target(Kobe) <- value`: Assign Target to a [Kobe-class\(\)](#) object
- `Limit(Timeseries)`: Return Limit from a [Timeseries-class\(\)](#) object
- `Limit(Timeseries) <- value`: Assign Limit to a [Timeseries-class\(\)](#) object
- `Target(Timeseries)`: Return Target from a [Timeseries-class\(\)](#) object
- `Target(Timeseries) <- value`: Assign Target to a [Timeseries-class\(\)](#) object

Functions

- `Target(object) <- value`: Assign value to `object@Target`

 Make_Slick

 Make an example Slick object

Description

A function that creates an example Slick data object

Usage

```

Make_Slick(
  name = "Unnamed Slick object",
  OM = NULL,
  MPs = c("DCAC", "AvC", "Fratio", "FMSYref", "FMSYref50", "matlenlim"),
  MP_Desc = NULL,
  PMS = c("AAVE", "AAVY", "LTY", "P10", "P50", "P100", "PNOF", "STY", "Yield"),
  Design = as.data.frame(cbind(rbind(as.matrix(expand.grid(1:2, 1:3, 1:2)), matrix(1,
    nrow = 5, ncol = 3)), c(rep(1, 12), 2:6))),
  SN = list(Factor_Labels = c("Natural Mortality", "Resilience", "Stock Depletion",
    "Robustness"), Labels = list(c("M=0.2", "M=0.3"), c("h=0.5", "h=0.7", "h=0.9"),
    c("Dep=0.1", "Dep=0.3"), c("Ref_Case", "L50=0.5", "Vmaxlen=0.1", "Cobs=0.5",
    "Perr=0.5", "AC=0.95")), Codes = list(c("M2", "M3"), c("h5", "h7", "h9"), c("D1",
    "D3"), c("Ref_case", "mat_low", "dome", "h_Cerr", "h_Perr", "h_AC")), Description =
    list(c("M=0.2", "M=0.3"), c("h=0.5", "h=0.7", "h=0.9"), c("Dep=0.1", "Dep=0.3"),
    c("Reference Case",
    "L50=0.5", "Vmaxlen=0.1", "Cobs=0.5", "Perr=0.5",
    "AC=0.95"))),
  mods = list(function(OM, lev) {
    if (lev == 1) OM@M <- c(0.2, 0.2)
    if (lev ==
  2) OM@M <- c(0.3, 0.3)
    OM
  }, function(OM, lev) {
    if (lev == 1) OM@h <-
  c(0.5, 0.5)
    if (lev == 2) OM@h = c(0.7, 0.7)
    if (lev == 3) OM@h = c(0.9,
  0.9)
    OM
  }, function(OM, lev) {
    if (lev == 1) OM@D <- c(0.1, 0.1)
    if
  (lev == 2) OM@D <- c(0.3, 0.3)
    OM
  }, function(OM, lev) {
    if (lev == 2)
  OM@L50 <- c(0.5, 0.5)
    if (lev == 3) OM@Vmaxlen = c(0.1, 0.1)
  
```

```

    if (lev == 4)
      OM@Cobs = c(0.5, 0.5)
    if (lev == 5) OM@Perr = c(0.5, 0.5)
    if (lev == 6)
      OM@AC = c(0.9, 0.9)
    OM
  }),
  nsim = 48,
  MSElist = NULL,
  fstYr = NULL,
  returnMSEs = FALSE
)

```

Arguments

name	Character string that is the object name (abbreviated for use in menus etc)
OM	An operating model object (class 'OM')
MPs	A vector of methods (character string) of class MP
MP_Desc	A vector method descriptions (character string) nMPs long
PMs	A vector of performance metrics of class PM
Design	A design matrix of OM runs
SN	A list of Labels, Codes and Descriptions of the factor levels. Each list item is a factor containing a vector of factor levels.
mods	A nested list of mods
nsim	Integer, the number of simulations
MSElist	An optional list of prerun MSEs
fstYr	An optional numeric value for first projection year. Otherwise current year is used
returnMSEs	Logical, rather than the Slick object should the list of MSEs be returned?

Value

An object of class [Slick](#)

Author(s)

T. Carruthers

Metadata	<i>Return Code, Label, Description and other information from an object</i>
----------	---

Description

Return Code, Label, Description and other information from an object

Usage

```
Metadata(object, lang = "en")

Metadata(object) <- value

## S4 method for signature 'Boxplot'
Metadata(object, lang = "en")

## S4 replacement method for signature 'Boxplot'
Metadata(object) <- value

## S4 method for signature 'Kobe'
Metadata(object, lang = "en")

## S4 replacement method for signature 'Kobe'
Metadata(object) <- value

## S4 method for signature 'MPs'
Metadata(object, lang = "en")

## S4 replacement method for signature 'MPs'
Metadata(object) <- value

## S4 method for signature 'Quilt'
Metadata(object, lang = "en")

## S4 replacement method for signature 'Quilt'
Metadata(object) <- value

## S4 method for signature 'Tradeoff'
Metadata(object, lang = "en")

## S4 replacement method for signature 'Tradeoff'
Metadata(object) <- value

## S4 method for signature 'Timeseries'
Metadata(object, lang = "en")
```

```
## S4 replacement method for signature 'Timeseries'
Metadata(object) <- value

## S4 method for signature 'Spider'
Metadata(object, lang = "en")

## S4 replacement method for signature 'Spider'
Metadata(object) <- value

## S4 method for signature 'Slick'
Metadata(object, lang = "en")
```

Arguments

object	A Slick-class() , MPs-class() , Boxplot-class() , Kobe-class() , Quilt-class() , Spider-class() , Timeseries-class() , or Tradeoff-class() object
lang	Optional text string specifying the language (if available). Either 'en', 'es', or 'fr' for English, Spanish, or French respectively
value	Replacement value for <code>Metadata()</code> in the corresponding object. See help documentation for the relevant object class for details.

Value

A data.frame
A data.frame

Methods (by class)

- `Metadata(Boxplot)`: Return Metadata for [Boxplot-class\(\)](#) objects
- `Metadata(Boxplot) <- value`: Assign Metadata for [Boxplot-class\(\)](#) objects
- `Metadata(Kobe)`: Return Metadata for [Kobe-class\(\)](#) objects
- `Metadata(Kobe) <- value`: Assign Metadata for [Kobe-class\(\)](#) objects
- `Metadata(MPs)`: Return Metadata for [MPs-class\(\)](#) objects
- `Metadata(MPs) <- value`: Assign Metadata for [MPs-class\(\)](#) objects
- `Metadata(Quilt)`: Return Metadata for [Quilt-class\(\)](#) objects
- `Metadata(Quilt) <- value`: Assign Metadata for [Quilt-class\(\)](#) objects
- `Metadata(Tradeoff)`: Return Metadata for [Tradeoff-class\(\)](#) objects
- `Metadata(Tradeoff) <- value`: Assign Metadata for [Tradeoff-class\(\)](#) objects
- `Metadata(Timeseries)`: Return Metadata for [Timeseries-class\(\)](#) objects
- `Metadata(Timeseries) <- value`: Assign Metadata for [Timeseries-class\(\)](#) objects
- `Metadata(Spider)`: Return Metadata for [Spider-class\(\)](#) objects
- `Metadata(Spider) <- value`: Assign Metadata for [Spider-class\(\)](#) objects
- `Metadata(Slick)`: Return Author, Email, and Institution from [Slick\(\)](#) objects

MinValue	<i>Assign and access MinValue and MaxValue for a Quilt object</i>
----------	---

Description

Assign and access MinValue and MaxValue for a Quilt object

Usage

```
MinValue(Quilt)
```

```
MinValue(Quilt) <- value
```

```
MaxValue(Quilt)
```

```
MaxValue(Quilt) <- value
```

Arguments

Quilt A [Quilt-class\(\)](#) object

value A numeric vector with minimum or maximum values for the Performance Indicators.

Value

A numeric value

Functions

- `MinValue()`: Return MinValue from a [Quilt-class\(\)](#) object
- `MinValue(Quilt) <- value`: Assign MinValue to a [Quilt-class\(\)](#) object
- `MaxValue()`: Return MaxValue from a [Quilt-class\(\)](#) object
- `MaxValue(Quilt) <- value`: Assign MaxValue to a [Quilt-class\(\)](#) object

See Also

[Quilt\(\)](#)

Description

The `MPs` function is used both to create and modify an `MPs-class()` object. and to access and assign MPs for an object of class `Slick-class()`. See Details.

Usage

```
MPs(Code = "", Label = "", Description = "", Color = "", Preset = list())
```

```
MPs(object) <- value
```

```
## S4 method for signature 'missing'
```

```
MPs()
```

```
## S4 method for signature 'character_list'
```

```
MPs(Code = "", Label = "", Description = "", Color = "", Preset = list())
```

```
## S4 method for signature 'Slick'
```

```
MPs(Code)
```

```
## S4 replacement method for signature 'Slick'
```

```
MPs(object) <- value
```

Arguments

Code	A <i>short</i> code for the Management Procedures in this <code>Slick</code> object. A character string length <code>nMP</code> or a named list for multi-language support. See Details
Label	A short label for the Management Procedures in this <code>Slick</code> object. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length <code>nMP</code> or a named list for multi-language support. See Details
Description	A description for the Management Procedures in this <code>Slick</code> object. Can include Markdown, see Examples. A character string length <code>nMP</code> or a named list for multi-language support. See Details
Color	A character vector of colors for the MPs.
Preset	An optional named list for the preset buttons in the <code>App()</code> . The name of the list element will appear as a button in the <code>App()</code> . Use <code>Code()</code> , <code>Label()</code> , <code>Description()</code> , and <code>Preset()</code> to access and assign the values for an existing MPs object, see Examples.
object	A <code>Slick-class()</code> object
value	A <code>MPs-class()</code> object

Details

Objects of class MPs are created with `MPs()`

Functions

- `MPs(missing)`: Create an empty MPs object
- `MPs(character_list)`: Create a populated MPs object
- `MPs(Slick)`: Return an `MPs-class()` object from a `Slick()` object
- `MPs(Slick) <- value`: Assign an `MPs-class()` object to a `Slick()` object

See Also

[Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Color\(\)](#), [Metadata\(\)](#), [Preset\(\)](#)

Examples

```
myMPs <- MPs()
Code(myMPs) <- c('MP1', 'MP2', 'MP3')
Label(myMPs) <- c('Management Procedure 1',
                 'Management Procedure 2',
                 'Management Procedure 3')
Description(myMPs) <- c('This is the description for Management Procedure 1',
                       'This is the description for Management Procedure 2',
                       'This is the description for Management Procedure 3')

Preset(myMPs) <- list(All=1:3, FirstTwo=1:2)

myMPs

# Multi-language
Description(myMPs) <- list(en=c('This is the English description for Management Procedure 1',
                              'This is the English description for Management Procedure 2',
                              'This is the English description for Management Procedure 3'),
                          es=c("This is the Spanish description for Management Procedure 1",
                              "This is the Spanish description for Management Procedure 2",
                              "This is the Spanish description for Management Procedure 3"),
                          fr=c("This is the French description for Management Procedure 1",
                              "This is the French description for Management Procedure 2",
                              "This is the French description for Management Procedure 3")
                          )

Metadata(myMPs)
Metadata(myMPs, 'es')
Metadata(myMPs, 'fr')
```

 MPs-class

 MPs S4 class and functions

Description

An object of class MPs contains information about the management procedures (MPs) in a [Slick-class\(\)](#) object. Like all S4 objects in [Slick](#), slots in this object can be accessed and assigned using functions corresponding to slot name. See [MPs\(\)](#) and the [See Also](#) section below.

Details

Objects of class MPs are created with [MPs\(\)](#)

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of management procedures (nMPs) in the plot objects `Boxplot`, `Kobe`, `Quilt`, `Spider`, `Timeseries`, and `Tradeoff`.

Slots

Code A *short* code for the Management Procedures in this [Slick](#) object. A character string length nMP or a named list for multi-language support. See *Details Required*

Label A short label for the Management Procedures in this [Slick](#) object. Can be longer than `Code` but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nMP or a named list for multi-language support. See *Details Required*

Description A description for the Management Procedures in this [Slick](#) object. Can include [Markdown](#), see [Examples](#). A character string length nMP or a named list for multi-language support. See *Details*

Color A character vector of colors for the MPs. Defaults will be used if not populated

Preset An optional named list for the preset buttons in the [App\(\)](#). The name of the list element will appear as a button in the [App\(\)](#).

See Also

[Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Preset\(\)](#)

Examples

```

myMPs <- MPs()
Code(myMPs) <- c('MP1', 'MP2', 'MP3')
Label(myMPs) <- c('Management Procedure 1',
                 'Management Procedure 2',
                 'Management Procedure 3')
Description(myMPs) <- c('This is the description for Management Procedure 1',
                       'This is the description for Management Procedure 2',
                       'This is the description for Management Procedure 3')

Preset(myMPs) <- list(All=1:3, FirstTwo=1:2)

myMPs

# Multi-language
Description(myMPs) <- list(en=c('This is the English description for Management Procedure 1',
                               'This is the English description for Management Procedure 2',
                               'This is the English description for Management Procedure 3'),
                          es=c("This is the Spanish description for Management Procedure 1",
                               "This is the Spanish description for Management Procedure 2",
                               "This is the Spanish description for Management Procedure 3"),
                          fr=c("This is the French description for Management Procedure 1",
                               "This is the French description for Management Procedure 2",
                               "This is the French description for Management Procedure 3")
                          )

Metadata(myMPs)
Metadata(myMPs, 'es')
Metadata(myMPs, 'fr')

```

NewSlick

Creates a blank Slick object

Description

Creates a blank Slick object

Usage

```

NewSlick(
  name = "Unnamed Slick Object",
  nPerf = list(nD = 5, nS = 6, nP = 7),
  nMPs = 5,
  nsim = 10,
  nProjYr = 50,
  nStateVar = 2,
  nHistYr = 55,
  Design = expand.grid(1:2, 1:2)
)

```

Arguments

name	Character string that is the object name (shortened for use in menus etc.)
nPerf	An integer vector of the number of deterministic (nD), stochastic (nS) and projected (nP) performance metrics
nMPs	Integer, the number of management options (aka management procedures).
nsim	Integer, the number of simulations (stochastic replicates per state of nature)
nProjYr	Integer, the number of projected years
nStateVar	Integer, the number of state variables
nHistYr	Integer, the number of historical years for state variables
Design	A design matrix of factor levels SN, factor

Value

An object of class [Slick](#)

Author(s)

T. Carruthers

OMs

Methods for Creating, Accessing and Assigning OMs objects

Description

The OMs function is used both to create and modify an [OMs-class\(\)](#) object. and to access and assign OMs for an object of class [Slick-class\(\)](#). See Details.

Usage

```
OMs(Factors = data.frame(), Design = data.frame(), Preset = list())
```

```
OMs(object) <- value
```

```
## S4 method for signature 'missing'
OMs()
```

```
## S4 method for signature 'dataframe_list'
OMs(Factors = data.frame(), Design = data.frame(), Preset = list())
```

```
## S4 method for signature 'Slick'
OMs(Factors)
```

```
## S4 replacement method for signature 'Slick'
OMs(object) <- value
```

Arguments

Factors	A data.frame with column headings Factor, Level, and Description. See Details
Design	A data.frame with nFactor columns (i.e., length(unique(Factors\$Factor))), and nOM rows. See Details
Preset	An optional named list for the preset buttons in the <code>App()</code> . The name of the list element will appear as a button in the <code>App()</code> .. See Details and 'Examples
object	A <code>Slick-class()</code> object
value	A <code>OMs-class()</code> object

Details**Factors:**

Factors can be accessed and assigned using `Factors(myslick)` and `Factors(myslick) <- data.frame()` respectively.

The Factor column should be character strings with the name of each factor, while the Level column is a numeric or character value with the level for the corresponding factor.

The Description column is a description for each row, i.e., a unique factor and level. See Examples.

Design:

The Design matrix is nOM rows and nFactor columns. The values in each column should either be numeric values indicating the levels for the corresponding factor, or the actual level values (i.e., `Factors$Level`) that correspond to each OM. See Examples.

Preset:

For OMs objects, Preset should be a named list, where each list element represents a different preset button to be shown in the app by the name of the list element, and each named list element should be a list of length nFactors, with the list elements for each Factor containing numeric values indicating the levels to include for that factor. See Examples

Use `Factors()`, `Design()`, and `Preset()` to access and assign the values for an existing OMs object, see Examples.

Functions

- `OMs(missing)`: Create an empty OMs object
- `OMs(dataframe_list)`: Create a populated OMs object
- `OMs(Slick)`: Return an `OMs-class()` object from a `Slick()` object
- `OMs(Slick) <- value`: Assign an `OMs-class()` object to a `Slick()` object

See Also

`OMs-class()`, `Factors()`, `Design()`, `Preset()`

Examples

```

# Create Object
oms <- OMs()

# Specify Factors
Factors(oms) <- data.frame(Factor='M',
                           Level=c('Base', 'Low M', 'High M'),
                           Description=c('Base Case',
                                          'Lower Natural Mortality',
                                          'Higher Natural Mortality'))

)

Factors(oms)

# OM Design

Design(oms) <- data.frame(M=c('Base', 'Low M', 'High M'))

# Add names for OMs
rownames(Design(oms)) <- c('Base Case', 'Less Productive', 'More Productive')

Design(oms)

# Preset

Preset(oms) <- list('Base Case'=list(1),
                   'Low M' = list(2),
                   'High M' = list(3),
                   'All'= list(1:3))

)

# Create Slick Object
myslick <- Slick()

# Add OMs to Slick Object
OMs(myslick) <- oms

```

OMs-class

OMs *S4 class and functions*

Description

An object of class OMs contains information about the operating models (MPs) in the `Slick()` object. Like all S4 objects in Slick, slots in this object can be accessed and assigned using functions corresponding to slot name. See `OMs()` and the See Also section below.

Details**Multi-Language Support:**

Use a named list to use multi-languages in Factors

Factors:

Factors can be accessed and assigned using `Factors(myslick)` and `Factors(myslick) <- data.frame()` respectively.

The `Factor` column should be character strings with the name of each factor, while the `Level` column is a numeric or character value with the level for the corresponding factor.

The `Description` column is a description for each row, i.e., a unique factor and level. See `Examples`.

Design:

The `Design` matrix is `nOM` rows and `nFactor` columns. The values in each column should either be numeric values indicating the levels for the corresponding factor, or the actual level values (i.e., `Factors$Level`) that correspond to each OM. See `Examples`.

Preset:

For OMs objects, `Preset` should be a named list, where each list element represents a different preset button to be shown in the app by the name of the list element, and each named list element should be a list of length `nFactors`, with the list elements for each `Factor` containing numeric values indicating the levels to include for that factor. See `Examples`

Slots

`Factors` A `data.frame` with column headings `Factor`, `Level`, and `Description`. See `Details`

`Design` A `data.frame` with `nFactor` columns (i.e., `length(unique(Factors$Factor))`), and `nOM` rows. See `Details`

`Preset` An optional named list for the preset buttons in the `App()`. The name of the list element will appear as a button in the `App()`. See `Details` and `Examples`

See Also

[OMs\(\)](#), [Factors\(\)](#), [Design\(\)](#), [Preset\(\)](#)

Examples

```
# Create Object
oms <- OMs()

# Specify Factors
Factors(oms) <- data.frame(Factor='M',
                          Level=c('Base', 'Low M', 'High M'),
                          Description=c('Base Case',
                                       'Lower Natural Mortality',
                                       'Higher Natural Mortality')
)

Factors(oms)

# OM Design

Design(oms) <- data.frame(M=c('Base', 'Low M', 'High M'))
```

```

# Add names for OMs
rownames(Design(oms)) <- c('Base Case', 'Less Productive', 'More Productive')

Design(oms)

# Preset

Preset(oms) <- list('Base Case'=list(1),
                  'Low M' = list(2),
                  'High M' = list(3),
                  'All'= list(1:3)
                )

# Create Slick Object
myslick <- Slick()

# Add OMs to Slick Object
OMs(myslick) <- oms

```

plotBoxplot

Plot Boxplot

Description

Plots boxplot, violin plot, or a combined box+violin plot for information stored in a [Boxplot](#) object

Usage

```

plotBoxplot(
  slick,
  PI = NULL,
  type = c("boxplot", "violin", "both", "all"),
  byOM = FALSE,
  ncol = 4,
  MP_label = "Code",
  PI_label = "Code"
)

```

Arguments

slick	A Slick-class() object
PI	Numeric value indicating the Performance Indicator(s) to plot from the <code>Boxplot-class</code> object. If <code>NULL</code> , it will <code>facet_wrap</code> all PIs
type	Character string specifying the plot type.
byOM	Logical. Facet the plots by operating model? PI must be a single value
ncol	Numeric. Number of columns

MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.
PI_label	Label to use for the PIs. Either Code or Label. Description works as well, but you probably don't want to do that.

Value

A ggplot2 object, or a list of ggplot2 objects

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 3

values <- array(NA, dim=c(nsim, nOM, nMP, nPI))
pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi] <- rlnorm(nsim, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
boxplot <- Boxplot(Code=c('PI1', 'PI2', 'PI3'),
                  Label=c('Performance Indicator 1',
                          'Performance Indicator 2',
                          'Performance Indicator 3'),
                  Description = c('This is the description for PI 1',
                                  'This is the description for PI 2',
                                  'This is the description for PI 3'),
                  Value=values)

# Check
Check(boxplot)

# Add to `Slick` object
slick <- Slick()
Boxplot(slick) <- boxplot

# Plots
plotBoxplot(slick)

plotBoxplot(slick, type='violin')

plotBoxplot(slick, byOM=TRUE)

plotBoxplot(slick, 2, type='both', byOM=TRUE)
```

plotKobe

*Plot Kobe***Description**

Plots a Kobe plot for a given projection year, or a Kobe Time plot.

Usage

```
plotKobe(
  slick,
  xPI = 1,
  yPI = 2,
  Time = FALSE,
  BLcol = "#F8DC7A",
  TLcol = "#D8775D",
  TRcol = "#FDBD56",
  BRcol = "#67C18B",
  axis_label = "Code",
  percentile = 0.9,
  axis.text.size = 14,
  axis.title.size = 16,
  strip.text.size = 16,
  strip.text.color = "#D6501C",
  incMP_label = TRUE,
  mp.text.size = 7,
  mp.point.size = 4,
  mp.init.point.size = 2,
  xmax = 2,
  ymax = 2,
  hist_traj = FALSE,
  ncol = 4,
  lang = "en",
  MP_label = "Code"
)
```

Arguments

slick	A Slick-class() object
xPI	Numeric value specifying the performance indicator for the x-axis
yPI	Numeric value specifying the performance indicator for the y-axis
Time	Logical. Kobe Time plot?
BLcol	Color for the bottom left quadrant
TLcol	Color for the top left quadrant

TRcol	Color for the top right quadrant
BRcol	Color for the bottom right quadrant
axis_label	Label to use for the axes. Either Code or Label. Description works as well, but you probably don't want to do that.
percentile	Numeric value specifying the percentile for the x and y percentile bars. Use NULL to remove percentile lines.
axis.text.size	Font size for axis text
axis.title.size	Font size for axis title
strip.text.size	Font size for facet strip text
strip.text.color	Color for facet strip text
incMP_label	Logical. Include MP labels?
mp.text.size	Font size for MP labels
mp.point.size	Point size for MP labels
mp.init.point.size	Point size for start of trajectory. If hist_traj==TRUE
xmax	Maximum value for the x-axis. Values greater than xmax will be shown at xmax
ymax	Maximum value for the yx-axis. Values greater than ymax will be shown at ymax
hist_traj	Logical. Plot the historical trajectories?
ncol	Numeric. Number of columns for Kobe Time
lang	Optional. Language (if supported in Slick Object). Either 'en', 'es', 'fr'
MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.

Details

By default plotKobe shows the terminal projection year. TimeTerminal(Kobe) can be used to override this. Use a numeric value indicating the time (must match a value in Time(Kobe)) to use for the Kobe plot.

Value

A ggplot2 object

See Also

[Kobe\(\)](#), [Kobe-class\(\)](#)

Examples

```

# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 2
nTS <- 30

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1)

for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[,om, mp, pi,] <- pi_means[pi] *
        matrix(
          cumprod(c(rlnorm(nTS*nsim, 0, 0.05))),
          nrow=nsim)
    }
  }
}

# Create and populate Object
kobe <- Kobe(Code=c('B/BMSY', 'F/FMSY'),
             Label=c('B/BMSY',
                    'F/FMSY'),
             Description = c('This is the description for PI 1',
                             'This is the description for PI 2'),
             Value=values
)

# Add values for projection time steps
Time(kobe) <- seq(2025, by=1, length.out=nTS)

# Check
Check(kobe)

# Add to `Slick` object
slick <- Slick()
Kobe(slick) <- kobe

# Plots
plotKobe(slick)

plotKobe(slick, Time=TRUE)

```

Description

Create a Quilt plot (unless shading==FALSE in which case it's just a table)

Usage

```
plotQuilt(  
  slick,  
  MP_label = "Code",  
  minmax = FALSE,  
  shading = TRUE,  
  kable = FALSE,  
  signif = 2,  
  alpha = 0.5  
)
```

Arguments

slick	A Slick-class() object
MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.
minmax	Logical. Color shading from min to max values in each column? If TRUE, ignores MinValue(quilt) and MaxValue(quilt)
shading	Logical. Color shading for the columns?
kable	Logical. Return a kable object?
signif	Numeric Number of significant figures
alpha	Numeric value. Transparency for color shading

Details

The columns are color shaded from light (lowest values) to dark (highest values).

Colors are set in `Color(quilt)`.

The color shading has 10 steps, from `MinValue(quilt)` to `MaxValue(quilt)` for each Performance Indicator. If those values are missing (NA) for a given PI, colors are shaded from lowest to highest values. If `minmax==TRUE`, `MinValue(quilt)` and `MaxValue(quilt)` are ignored.

Value

A `DT::datatable` or a `knitr::kable` object

See Also

[Quilt\(\)](#), [Quilt-class\(\)](#)

Examples

```

# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- rlnorm(1, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
quilt <- Quilt(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
              Label=c('Performance Indicator 1',
                     'Performance Indicator 2',
                     'Performance Indicator 3',
                     'Performance Indicator 4'),
              Description = c('This is the description for PI 1',
                             'This is the description for PI 2',
                             'This is the description for PI 3',
                             'This is the description for PI 4'),
              Value=values)

# Check
Check(quilt)

# Add to `Slick` object
slick <- Slick()
Quilt(slick) <- quilt

# Plots
plotQuilt(slick)

```

plotSpider

Plot Spider

Description

A Spider or Radar plot

Usage

```

plotSpider(
  slick,
  byOM = FALSE,
  byMP = FALSE,
  incMean = TRUE,
  incMax = TRUE,
  relScale = FALSE,
  col.om.title = "#D6501C",
  cex.om.title = 2,
  col.Mean = "white",
  bg.Mean = "black",
  grid.fill = "#f2f3f5",
  grid.line = "black",
  fill = byMP | all(byOM),
  inc.grid = TRUE,
  PI.labels = !(byMP | all(byOM)),
  MP_label = "Code",
  mp.lwd = 3,
  alpha = 0.3,
  ncol = 4,
  PI.mean.cex = 2.2,
  incMPtitle = byMP,
  mplab.cex = 2.2,
  max.pt.cex = 2,
  max.pt.col = "darkred"
)

```

Arguments

slick	A Slick-class() object
byOM	Logical Plot by OM? Otherwise mean over OMs
byMP	Logical. Plot by MP? Otherwise all MPs together on one plot
incMean	Logical. Include mean PI score in center?
incMax	Logical. Include colored points indicating maximum PI values?
relScale	Logical. Scale PI values between minimum (0) and maximum (1)?
col.om.title	Color of the OM names/labels
cex.om.title	Size of OM names/labels
col.Mean	Color of mean value text
bg.Mean	Background color of mean value text
grid.fill	Color of fill for the spider grid
grid.line	Color of lines for the spider grid
fill	Logical Fill the spider plot?
inc.grid	Logical. Include the grid?

PI.labels	Logical Show PI labels?
MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.
mp.lwd	Line width
alpha	Alpha value for the fill
ncol	Number of columns
PI.mean.cex	Size of PI mean score text
incMPtitle	Logical. Include MP label?
mplab.cex	MP label size
max.pt.cex	Max value point size
max.pt.col	Max value point color

Value

A ggplot2 object

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

# Note: PI values must be between 0 and 1, with 1 indicating better performance
pi_means <- runif(nPI, 0, 1)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- runif(1, pi_means[pi])
    }
  }
}

# Create and populate Object
spider <- Spider(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
    'Performance Indicator 2',
    'Performance Indicator 3',
    'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
    'This is the description for PI 3',
    'This is the description for PI 4'),
  Value=values)

# Check
Check(spider)
```

```
# Add to `Slick` object
slick <- Slick()
Spider(slick) <- spider

# Plots
plotSpider(slick)

plotSpider(slick, fill=TRUE)

plotSpider(slick, byMP=TRUE)

plotSpider(slick, byOM=TRUE)
```

plotTimeseries	<i>Plot Timeseries</i>
----------------	------------------------

Description

Plot the historical and projected values for a performance indicator.

Usage

```
plotTimeseries(
  slick,
  PI = 1,
  byMP = FALSE,
  byOM = FALSE,
  includeHist = TRUE,
  ncol = 4,
  col_line = "darkgray",
  includeQuants = TRUE,
  includeLabels = TRUE,
  MeanMed = c("mean", "median"),
  fill_ribbon1 = "#ededed",
  col_ribbon1 = "#ededed",
  quants1 = c(0.25, 0.75),
  alpha1 = 0.3,
  fill_ribbon2 = "white",
  col_ribbon2 = "#c9c9c9",
  linetype_ribbon2 = "dashed",
  quants2 = c(0.1, 0.9),
  alpha2 = 0.1,
  MP_label = "Code",
  col_title = "#D6501C",
  size.title = 18,
  size.axis.title = 18,
```

```

size.axis.text = 16,
size.mp.label = 6,
linewidth.median.line = 0.5,
targ_color = "green",
targ_name = "Target",
lim_color = "red",
lim_name = "Limit",
inc_y_label = TRUE,
sims = NULL,
lang = "en"
)

```

Arguments

slick	A Slick-class() object
PI	A numeric value specifying the performance indicator to plot
byMP	Logical. Facet by MP? Defaults to FALSE, where all MPs are shown on the same plot
byOM	Logical. Facet by OM? Defaults to FALSE where values are calculated as mean across OMs
includeHist	Logical. Include the historical period in the projections?
ncol	Numeric. Number of columns if faceting by MP or OM
col_line	Color for the median line (historical)
includeQuants	Logical. Include quantile shading for the projections?
includeLabels	Logical. Include MP labels?
MeanMed	Character. Plot the 'mean' (default) or 'median'.
fill_ribbon1	Fill color for the inner ribbon
col_ribbon1	Color of the line for inner ribbon
quants1	Quantiles for the inner ribbon. Numeric length 2
alpha1	Alpha for the colored MPs inner shading
fill_ribbon2	Fill color for the outer ribbon
col_ribbon2	Color of the line for outer ribbon
linetype_ribbon2	Line type for outer ribbon
quants2	Quantiles for the outer ribbon. Numeric length 2.
alpha2	Alpha for the colored MPs outer shading
MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.
col_title	Color of the MP title (if byMP==TRUE)
size.title	Numeric length 1. Size for plot title
size.axis.title	Numeric length 1. Size for axis title

size.axis.text	Numeric length 1. Size for axis text
size.mp.label	Numeric length 1. Size of MP labels. Set to NULL for no MP labels
linewidth.median.line	Width of the mean/median line
targ_color	Color for the target line (if it exists in Target(Timeseries(slick)))
targ_name	Label for the target line
lim_color	Color for the limit line (if it exists in Limit(Timeseries(slick)))
lim_name	Label for the limit line
inc_y_label	Include the label for the y-axis?
sims	Optional. Numeric values indicating the simulations to include. Defaults to all.
lang	Optional. Language (if supported in Slick Object). Either 'en', 'es', 'fr'

Details

If byOM==FALSE the results are shown as the mean across operating models.

Value

A ggplot2 object

See Also

[Timeseries\(\)](#), [Timeseries-class\(\)](#)

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 3
nHistTS <- 50
nProjTS <- 30
nTS <- nHistTS + nProjTS

set.seed(101)

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1, 1000)

for (om in 1:nOM) {
  for (pi in 1:nPI) {
    # PI identical for historical
    histVals <- matrix(
      pi_means[pi] *
      cumprod(c(rlnorm(nHistTS*nsim, 0, 0.05))),
      nrow=nsim, ncol=nHistTS, byrow=TRUE)
    histVals <- replicate(nMP, histVals)
```

```

values[,om, , pi,1:nHistTS] <- aperm(histVals, c(1,3,2))

for (mp in 1:nMP) {
  values[,om, mp, pi,(nHistTS+1):nTS] <- matrix(
    pi_means[pi] *
    cumprod(c(rlnorm(nProjTS*nsim, 0, 0.05))),
    nrow=nsim, ncol=nProjTS, byrow=FALSE)
}
}
}

# Create and populate Object
timeseries <- Timeseries(Code=c('B/BMSY', 'F/FMSY', 'TAC'),
  Label=c('B/BMSY',
    'F/FMSY',
    'TAC'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
    'This is the description for PI 3'),
  Value=values
)

# Last historical time step
TimeNow(timeseries) <- 2024

# Add values for time steps
Time(timeseries) <- c(rev(seq(TimeNow(timeseries), by=-1, length.out=nHistTS)),
  seq(TimeNow(timeseries)+1, by=1, length.out=nProjTS))

# Check
Check(timeseries)

# Add to `Slick` object
slick <- Slick()
Timeseries(slick) <- timeseries

# Plots
plotTimeseries(slick)
plotTimeseries(slick, 2)
plotTimeseries(slick, 3)

plotTimeseries(slick, byMP=TRUE)

plotTimeseries(slick, byOM=TRUE)

# Custom Reference Points
RefPoints(timeseries) <- list(
  list(Name=c('0.5 BMSY', 'BMSY', '1.5 BMSY'),
    Value=c(0.5, 1, 1.5),
    Color=c('red', 'orange', 'green')),
  list(Name=c('0.8 FMSY', 'FMSY'),
    Value=c(0.8,1),
    Color=c('orange', 'red')),

```

```

    list(Name='Target Catch',
          Value=1200,
          Color='blue')
  )

  Timeseries(slick) <- timeseries
  plotTimeseries(slick)
  plotTimeseries(slick, 2)
  plotTimeseries(slick, 3)

```

plotTradeoff	<i>Plot Tradeoff</i>
--------------	----------------------

Description

Plot Tradeoff

Usage

```

plotTradeoff(
  slick,
  xPI = NULL,
  yPI = NULL,
  MP_label = "Code",
  lab_size = 6,
  point_size = 2,
  size.axis.title = 14,
  size.axis.text = 12
)

```

Arguments

slick	A Slick-class() object
xPI	Numeric value indicating the PI to plot on the x-axis. Multiple values are accepted. Recycled if xPI<yPI
yPI	Numeric value indicating the PI to plot on the y-axis. Multiple values are accepted. Recycled if yPI<xPI
MP_label	Label to use for the MPs. Either Code or Label. Description works as well, but you probably don't want to do that.
lab_size	Size of the MP labels
point_size	Size of the points
size.axis.title	Size of axis title
size.axis.text	Size of axis text

Value

A ggplot2 object

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- rlnorm(1, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
tradeoff <- Tradeoff(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
          'Performance Indicator 2',
          'Performance Indicator 3',
          'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
                 'This is the description for PI 2',
                 'This is the description for PI 3',
                 'This is the description for PI 4'),
  Value=values)

# Check
Check(tradeoff)

# Add to `Slick` object
slick <- Slick()
Tradeoff(slick) <- tradeoff

# Plots
plotTradeoff(slick)

plotTradeoff(slick, c(1,1,2), c(2,3,3))
```


Description

A function that converts deterministic or stochastic performance metrics to the range 0-100 and optionally inverts these

Usage

```
PMnorm(obj, det = TRUE, inv = NULL)
```

Arguments

obj	An object of class 'slick'
det	logical, should the normalization be applied to the deterministic performance metrics (or, if false the stochastic ones)
inv	A logical vector nPM long. If true, the PM will be inverted (100-value).

Value

An object of class [Slick](#)

Author(s)

T. Carruthers

Preset	<i>Assign or access Preset for a valid object class</i>
--------	---

Description

Assign or access Preset for a valid object class

Usage

```
Preset(object)

Preset(object) <- value

## S4 method for signature 'Boxplot'
Preset(object)

## S4 replacement method for signature 'Boxplot'
Preset(object) <- value

## S4 method for signature 'Kobe'
Preset(object)

## S4 replacement method for signature 'Kobe'
Preset(object) <- value
```

```
## S4 method for signature 'MPs'
Preset(object)

## S4 replacement method for signature 'MPs'
Preset(object) <- value

## S4 method for signature 'OMs'
Preset(object)

## S4 replacement method for signature 'OMs'
Preset(object) <- value

## S4 method for signature 'Quilt'
Preset(object)

## S4 replacement method for signature 'Quilt'
Preset(object) <- value

## S4 method for signature 'Tradeoff'
Preset(object)

## S4 replacement method for signature 'Tradeoff'
Preset(object) <- value

## S4 method for signature 'Timeseries'
Preset(object)

## S4 replacement method for signature 'Timeseries'
Preset(object) <- value

## S4 method for signature 'Spider'
Preset(object)

## S4 replacement method for signature 'Spider'
Preset(object) <- value
```

Arguments

object	An object of class <code>Boxplot-class()</code> , <code>Kobe-class()</code> , <code>Quilt-class()</code> , <code>Spider-class()</code> , <code>Timeseries-class()</code> , or <code>Tradeoff-class()</code>
value	A list, formatted to match the class of object. See the documentation for corresponding object class for more details.

Value

Returns a list object from the `Preset` slot in object

Methods (by class)

- `Preset(Boxplot)`: Return Preset from a `Boxplot-class()` object
- `Preset(Boxplot) <- value`: Assign Preset slot from a `Boxplot-class()` object
- `Preset(Kobe)`: Return Preset from a `Kobe-class()` object
- `Preset(Kobe) <- value`: Assign Preset to a `Kobe-class()` object
- `Preset(MPs)`: Return Preset from a `MPs-class()` object
- `Preset(MPs) <- value`: Assign Preset to a `MPs-class()` object
- `Preset(OMs)`: Return Preset from a `OMs-class()` object
- `Preset(OMs) <- value`: Assign Preset to an `OMs-class()` object
- `Preset(Quilt)`: Return Preset from a `Quilt-class()` object
- `Preset(Quilt) <- value`: Assign Preset to a `Quilt-class()` object
- `Preset(Tradeoff)`: Return Preset from a `Tradeoff-class()` object
- `Preset(Tradeoff) <- value`: Assign Preset to a `Tradeoff-class()` object
- `Preset(Timeseries)`: Return Preset from a `Timeseries-class()` object
- `Preset(Timeseries) <- value`: Assign Preset to a `Timeseries-class()` object
- `Preset(Spider)`: Return Preset from a `Spider-class()` object
- `Preset(Spider) <- value`: Assign Preset slot from a `Spider-class()` object

 Quilt

Methods for Creating, Accessing and Assigning Quilt objects

Description

The `Quilt` function is used both to create and modify an `Quilt-class()` object. and to access and assign `Quilt` for an object of class `Slick-class()`. See Details.

Usage

```

Quilt(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list(),
  Color = c("darkblue", "lightblue"),
  MinValue = as.numeric(NA),
  MaxValue = as.numeric(NA)
)

Quilt(Slick) <- value

## S4 method for signature 'missing'
```

```

Quilt()

## S4 method for signature 'character_list'
Quilt(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list(),
  Color = c("darkblue", "lightblue"),
  MinValue = as.numeric(NA),
  MaxValue = as.numeric(NA)
)

## S4 method for signature 'Slick'
Quilt(Code)

## S4 replacement method for signature 'Slick'
Quilt(Slick) <- value

```

Arguments

Code	A <i>short</i> code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details
Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Mark-down, see Examples . A character string length nPI or a named list for multi-language support. See Details
Value	A numeric array with the stochastic performance indicator values for each operating model (OM), management procedure (MP), and performance indicator (PI). Dimensions: c(nOM, nMP, and nPI)
Preset	An optional named list for the preset buttons in the App() . The name of the list element will appear as a button in the App() .
Color	A character vector length 2 of colors for the maximum and minimum values in the chart.
MinValue	Numeric vector length nPI with the minimum possible value for the respective PIs. Defaults to minimum PI value in Value (averaged across OMs in some cases)
MaxValue	Numeric vector length nPI with the maximum possible value (i.e., best performance) for the respective PIs. Defaults to maximum PI value in Value (averaged across OMs in some cases).
Slick	A Slick-class() object
value	A Quilt-class() object

Details

Objects of class `Quilt` are created with `Quilt()`

Use the `Code()`, `Label()`, `Description()`, `Value()`, `Preset()`, `Color()`, `MinValue()`, and `MaxValue()` functions to access and assign the values for an existing `Quilt` object, see Examples

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Functions

- `Quilt(missing)`: Create an empty `Quilt` object
- `Quilt(character_list)`: Create a populated `Quilt` object
- `Quilt(Slick)`: Return `Quilt` from a `Slick-class()` object
- `Quilt(Slick) <- value`: Assign a `Quilt-class()` object to a `Slick-class()` object

See Also

`Code()`, `Label()`, `Description()`, `Color()`, `Metadata()`, `Preset()`, `Color()`, `MinValue()`, `MaxValue()`

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- rlnorm(1, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
quilt <- Quilt(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
              Label=c('Performance Indicator 1',
                     'Performance Indicator 2',
                     'Performance Indicator 3',
```

```

        'Performance Indicator 4'),
Description = c('This is the description for PI 1',
               'This is the description for PI 2',
               'This is the description for PI 3',
               'This is the description for PI 4'),
Value=values)

# Check
Check(quilt)

# Add to `Slick` object
slick <- Slick()
Quilt(slick) <- quilt

# Plots
plotQuilt(slick)

```

Quilt-class

S4 class Quilt

Description

Objects of class `Quilt` are used to store information for the Quilt chart. Like all S4 objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See [Quilt\(\)](#) and the the See Also section below.

Details

Objects of class `Quilt` are created with `Quilt()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Slots

`Code` A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See [Details](#)


```

                                'This is the description for PI 3',
                                'This is the description for PI 4'),
                                Value=values)

# Check
Check(quilt)

# Add to `Slick` object
slick <- Slick()
Quilt(slick) <- quilt

# Plots
plotQuilt(slick)

```

RefPoints

Assign or access RefPoints for a valid object class

Description

Assign or access RefPoints for a valid object class

Usage

```

RefPoints(object)

RefPoints(object) <- value

## S4 method for signature 'Timeseries'
RefPoints(object)

## S4 replacement method for signature 'Timeseries'
RefPoints(object) <- value

```

Arguments

object	An object of class <code>Timeseries-class()</code>
value	A list, formatted to match the class of object. See the documentation for corresponding object class for more details.

Value

Returns a list object with the contents of the RefPoints slot of `Timeseries()` objects

Methods (by class)

- RefPoints(Timeseries): Return RefPoints from a [Timeseries-class\(\)](#) object
- RefPoints(Timeseries) <- value: Assign RefPoints to a [Timeseries-class\(\)](#) object

show

Generic show method

Description

A copy of [methods::show\(\)](#)

Usage

```
show(object)

## S4 method for signature 'Boxplot'
show(object)

## S4 method for signature 'CheckList'
show(object)

## S4 method for signature 'Kobe'
show(object)

## S4 method for signature 'MPs'
show(object)

## S4 method for signature 'OMs'
show(object)

## S4 method for signature 'Quilt'
show(object)

## S4 method for signature 'Tradeoff'
show(object)

## S4 method for signature 'Timeseries'
show(object)

## S4 method for signature 'Spider'
show(object)

## S4 method for signature 'Slick'
show(object)
```

Arguments

object Object to print to console

Value

show returns an invisible NULL

Methods (by class)

- show(Boxplot): Print a [Boxplot-class\(\)](#) object
- show(CheckList): Print a CheckList object
- show(Kobe): Print a [Kobe-class\(\)](#) object
- show(MPs): Print a [MPs-class\(\)](#) object
- show(OMs): Print a [OMs-class\(\)](#) object
- show(Quilt): Print a [Quilt-class\(\)](#) object
- show(Tradeoff): Print a [Tradeoff-class\(\)](#) object
- show(Timeseries): Print a [Timeseries-class\(\)](#) object
- show(Spider): Print a [Spider-class\(\)](#) object
- show(Slick): Print a [Slick-class\(\)](#) object

Slick-class

Create a Slick class object

Description

The Slick class is the main object class used in the Slick package. It contains sub-objects for the management procedures [MPs\(\)](#), operating models [OMs\(\)](#), and the six chart types: [Boxplot\(\)](#), [Kobe\(\)](#), [Quilt\(\)](#), [Spider\(\)](#), [Timeseries\(\)](#), and [Tradeoff\(\)](#), as well as metadata information for the Slick object such as Title, Author, and Introduction.

Usage

```
Slick(
  Title = "",
  Subtitle = "",
  Date = Sys.Date(),
  Author = "",
  Email = "",
  Institution = "",
  Introduction = "",
  MPs = NULL,
  OMs = NULL,
  Boxplot = NULL,
  Kobe = NULL,
```

```

    Quilt = NULL,
    Spider = NULL,
    Timeseries = NULL,
    Tradeoff = NULL
  )

Title(object, lang = "en", markdown = FALSE)

Title(object) <- value

Subtitle(object, lang = "en", markdown = FALSE)

Subtitle(object) <- value

Date(object)

Date(object) <- value

Author(object, markdown = FALSE)

Author(object) <- value

Email(object, markdown = FALSE)

Email(object) <- value

Institution(object, lang = "en", markdown = FALSE)

Institution(object) <- value

Introduction(object, lang = "en", markdown = FALSE)

Introduction(object) <- value

```

Arguments

Title	Title for the Slick object. A character string. For multiple languages, use a named list with names: en, es, fr for the three supported languages.
Subtitle	Subtitle for the Slick object. A character string or a named list with languages: en, es, fr
Date	Date the Slick object was created. Text in format 'YYYY-MM-DD' or class Date e.g., Sys.Date()
Author	A character vector with Author(s) names. The length of the vector should equal the number of authors.
Email	A character vector with email addresses for the author(s). Must be same length as Author. Can include Markdown.
Institution	A character vector with institution details for the author(s). Must be same length as Author. Can include Markdown.

Introduction	Introduction text for the Slick object. Supports all markdown formatting. Character string, must be length 1. For multiple languages, use a named list with names: en, es, fr for the three supported languages.
MPs	An object of class <code>MPs-class()</code>
OMs	An object of class <code>OMs-class()</code>
Boxplot	An object of class <code>Boxplot-class()</code>
Kobe	An object of class <code>Kobe-class()</code>
Quilt	An object of class <code>Quilt-class()</code>
Spider	An object of class <code>Spider-class()</code>
Timeseries	An object of class <code>Timeseries-class()</code>
Tradeoff	An object of class <code>Tradeoff-class()</code>
object	A <code>Slick-class()</code> object
lang	Optional text string specifying the language (if available). Either 'en', 'es', or 'fr' for English, Spanish, or French respectively
markdown	Logical. Process markdown?
value	The value to assign to the object. See Slots for format of the relevant object class

Details

Objects of class `Slick` are created with `Slick()`.

Like all S4 objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See Usage and Functions section.

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

All functions with the exception of `Date` support Markdown.

Value

A `Slick` object

Functions

- `Slick()`: Create a `Slick-class()` object
- `Title()`: Access Title, Multi-language support
- `Title(object) <- value`: Assign Title, Multi-language support
- `Subtitle()`: Access Subtitle, Multi-language support
- `Subtitle(object) <- value`: Assign Subtitle, Multi-language support
- `Date()`: Access Date

- `Date(object) <- value`: Assign Date
- `Author()`: Access Author
- `Author(object) <- value`: Assign Author
- `Email()`: Access Email
- `Email(object) <- value`: Assign Email
- `Institution()`: Access Institution
- `Institution(object) <- value`: Assign Institution
- `Introduction()`: Access Introduction
- `Introduction(object) <- value`: Assign Introduction, can include Markdown. See Examples

Slots

Title Title for the Slick object. A character string. For multiple languages, use a named list with names: `en`, `es`, `fr` for the three supported languages.

Subtitle Subtitle for the Slick object. A character string or a named list with languages: `en`, `es`, `fr`

Date Date the Slick object was created. Text in format `'YYYY-MM-DD'` or class `Date` e.g., `Sys.Date()`

Author A character vector with Author(s) names. The length of the vector should equal the number of authors.

Email A character vector with email addresses for the author(s). Must be same length as `Author`. Can include Markdown.

Institution A character vector with institution details for the author(s). Must be same length as `Author`. Can include Markdown.

Introduction Introduction text for the Slick object. Supports all markdown formatting. Character string, must be length 1. For multiple languages, use a named list with names: `en`, `es`, `fr` for the three supported languages.

MPs An object of class `MPs-class()`

OMs An object of class `OMs-class()`

Boxplot An object of class `Boxplot-class()`

Kobe An object of class `Kobe-class()`

Quilt An object of class `Quilt-class()`

Spider An object of class `Spider-class()`

Timeseries An object of class `Timeseries-class()`

Tradeoff An object of class `Tradeoff-class()`

See Also

`MPs()`, `OMs()`, `Boxplot()`, `Kobe()`, `Quilt()`, `Spider()`, `Timeseries()`, `Tradeoff()`, `Check()`, `Title()`, `Subtitle()`, `Date()`, `Author()`, `Email()`, `Institution()`, `Introduction()`

Examples

```

# Assign values to a new `Slick` object
slick <- Slick()

Title(slick) <- 'An Example Slick Object'
Subtitle(slick) <- ""
Date(slick) <- Sys.Date()
Author(slick) <- 'Adrian Hordyk'
Email(slick) <- "[mailto:adrian@bluematterscience.com](mailto:adrian@bluematterscience.com)"
Institution(slick) <- "[Blue Matter Science](bluematterscience.com)"

Introduction(slick) <- "This is the Introduction text"

# Access values from `Slick` object
Title(slick)
Subtitle(slick)
Date(slick)
Author(slick)
Email(slick)
Institution(slick)
Introduction(slick)

```

 Spider

Methods for Creating, Accessing and Assigning Spider objects

Description

The Spider function is used both to create and modify an [Spider-class\(\)](#) object. and to access and assign Spider for an object of class [Slick-class\(\)](#). See Details.

Usage

```

Spider(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list()
)

Spider(Slick) <- value

## S4 method for signature 'missing'
Spider()

## S4 method for signature 'character'
Spider(

```

```

Code = "",
Label = "",
Description = "",
Value = array(),
Preset = list()
)

## S4 method for signature 'list'
Spider(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list()
)

## S4 method for signature 'Slick'
Spider(Code)

## S4 replacement method for signature 'Slick'
Spider(Slick) <- value

```

Arguments

Code	A <i>short</i> code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details
Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Markdown, see Examples . A character string length nPI or a named list for multi-language support. See Details
Value	A numeric array with the stochastic performance indicator values for each operating model (OM), management procedure (MP), and performance indicator (PI). Dimensions: c(nOM, nMP, and nPI). All PI values must range between 0 and 1 or 0 and 100. If all values are <= 1, they will be multiplied by 100 in the plot.
Preset	An optional named list for the preset buttons in the App() . The name of the list element will appear as a button in the App() .
Slick	A Slick-class() object
value	A Spider-class() object

Details

Objects of class Spider are created with `Spider()`

Use the [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#) functions to access and assign the values for an existing Spider object, see [Examples](#)

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in Code, Label, and Description must all be same length as the number of performance indicators (nPIs) in 'Value

Functions

- `Spider(missing)`: Create an empty Spider object
- `Spider(character)`: Create a populated Spider object
- `Spider(list)`: Create a populated Spider object
- `Spider(Slick)`: Return Spider from a `Slick-class()` object
- `Spider(Slick) <- value`: Assign a `Spider-class()` object to a `Slick-class()` object

See Also

[Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Metadata\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

# Note: PI values must be between 0 and 1, with 1 indicating better performance
pi_means <- runif(nPI, 0, 1)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- runif(1, pi_means[pi])
    }
  }
}

# Create and populate Object
spider <- Spider(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
    'Performance Indicator 2',
    'Performance Indicator 3',
    'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
```



```

                                'This is the description for PI 3',
                                'This is the description for PI 4'),
                                Value=values)

# Check
Check(spider)

# Add to `Slick` object
slick <- Slick()
Spider(slick) <- spider

# Plots
plotSpider(slick)

plotSpider(slick, fill=TRUE)

plotSpider(slick, byMP=TRUE)

plotSpider(slick, byOM=TRUE)

```

Spider-class

S4 class Spider

Description

Objects of class `Spider` are used to store information for the Spider plots. Like all S4 objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See [Spider](#) and the `See Also` section below.

Details

Objects of class `Spider` are created with `Spider()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Slots

Code A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See [Details](#)

Label A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See [Details](#)

Description A description for the Performance Indicators for this object. Can include Markdown, see [Examples](#). A character string length nPI or a named list for multi-language support. See [Details](#)

Value A numeric array with the stochastic performance indicator values for each operating model (OM), management procedure (MP), and performance indicator (PI). Dimensions: c(nOM, nMP, and nPI). All PI values must range between 0 and 1 or 0 and 100. If all values are ≤ 1 , they will be multiplied by 100 in the plot. Dimensions: c(nOM, nMP, and nPI)

Preset An optional named list for the preset buttons in the [App\(\)](#). The name of the list element will appear as a button in the [App\(\)](#).

See Also

[Spider](#), [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

# Note: PI values must be between 0 and 1, with 1 indicating better performance
pi_means <- runif(nPI, 0, 1)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- runif(1, pi_means[pi])
    }
  }
}

# Create and populate Object
spider <- Spider(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
    'Performance Indicator 2',
    'Performance Indicator 3',
    'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
    'This is the description for PI 3',
```

```

                                'This is the description for PI 4'),
                                Value=values)

# Check
Check(spider)

# Add to `Slick` object
slick <- Slick()
Spider(slick) <- spider

# Plots
plotSpider(slick)

plotSpider(slick, fill=TRUE)

plotSpider(slick, byMP=TRUE)

plotSpider(slick, byOM=TRUE)

```

Time

Access or assign Time for object of class Kobe or Timeseries

Description

Access or assign Time for object of class Kobe or Timeseries

Usage

```

Time(object)

Time(object) <- value

## S4 method for signature 'Kobe'
Time(object)

## S4 replacement method for signature 'Kobe'
Time(object) <- value

## S4 method for signature 'Timeseries'
Time(object)

## S4 replacement method for signature 'Timeseries'
Time(object) <- value

```

Arguments

object	A Kobe-class() or Timeseries() class object
value	Value to assign to Time

Value

Returns a numeric vector with values from the Time slot in `Kobe()` and `Timeseries()` objects

Methods (by class)

- `Time(Kobe)`: Return Time from a `Kobe-class()` object
- `Time(Kobe) <- value`: Assign Time to a `Kobe-class()` object
- `Time(Timeseries)`: Return Time from a `Timeseries-class()` object
- `Time(Timeseries) <- value`: Assign Time to a `Timeseries-class()` object

Functions

- `Time(object) <- value`: Assign value to `object@Time`

TimeLab

Access or assign TimeLab in a Kobe or Timeseries object

Description

Access or assign TimeLab in a Kobe or Timeseries object

Usage

```
TimeLab(object, lang = "en")
```

```
TimeLab(object) <- value
```

```
## S4 method for signature 'Kobe'
```

```
TimeLab(object, lang = "en")
```

```
## S4 replacement method for signature 'Kobe'
```

```
TimeLab(object) <- value
```

```
## S4 method for signature 'Timeseries'
```

```
TimeLab(object, lang = "en")
```

```
## S4 replacement method for signature 'Timeseries'
```

```
TimeLab(object) <- value
```

Arguments

- | | |
|---------------------|--|
| <code>object</code> | A <code>Kobe-class()</code> or <code>Timeseries</code> object |
| <code>lang</code> | Optional text string specifying the language (if available). Either 'en', 'es', or 'fr' for English, Spanish, or French respectively |
| <code>value</code> | A character string to assign to TimeLab in object. |

Value

Returns a character string from the TimeLab slot in `Kobe()` and `Timeseries()` objects

Methods (by class)

- `TimeLab(Kobe)`: Return TimeLab from a `Kobe-class()` object
- `TimeLab(Kobe) <- value`: Assign TimeLab to a `Kobe-class()` object
- `TimeLab(Timeseries)`: Return TimeLab from a `Timeseries-class()` object
- `TimeLab(Timeseries) <- value`: Assign TimeLab to a `Timeseries-class()` object

TimeNow

Access and return TimeNow from a `Timeseries-class()` object

Description

Access and return TimeNow from a `Timeseries-class()` object

Usage

```
TimeNow(Timeseries)
```

```
TimeNow(Timeseries) <- value
```

Arguments

`Timeseries` A `Timeseries-class()` object

`value` A character string label for the time axis. Use a named list for multiple languages

Value

A numeric value

Functions

- `TimeNow(Timeseries) <- value`: Assign TimeNow to a `Timeseries-class()` object

Description

An object of class Timeseries contains information for the Time Series chart. The Timeseries function is used both to create and modify an [Timeseries-class\(\)](#) object, and to access and assign Timeseries for an object of class [Slick-class\(\)](#). See Details.

Usage

```

Timeseries(
  Code = "",
  Label = "",
  Description = "",
  Time = numeric(),
  TimeNow = numeric(),
  TimeLab = "Year",
  Value = array(),
  Preset = list(),
  Target = NULL,
  Limit = NULL,
  RefPoints = list()
)

Timeseries(Slick) <- value

## S4 method for signature 'missing'
Timeseries()

## S4 method for signature 'character'
Timeseries(
  Code = "",
  Label = "",
  Description = "",
  Time = numeric(),
  TimeNow = numeric(),
  TimeLab = "Year",
  Value = array(),
  Preset = list(),
  Target = NULL,
  Limit = NULL,
  RefPoints = list()
)

## S4 method for signature 'list'
Timeseries(

```

```

Code = "",
Label = "",
Description = "",
Time = numeric(),
TimeNow = numeric(),
TimeLab = "Year",
Value = array(),
Preset = list(),
Target = NULL,
Limit = NULL,
RefPoints = list()
)

## S4 method for signature 'Slick'
Timeseries(Code)

## S4 replacement method for signature 'Slick'
Timeseries(Slick) <- value

```

Arguments

Code	A <i>short</i> code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details
Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Mark-down, see Examples . A character string length nPI or a named list for multi-language support. See Details
Time	A numeric vector with values for the historical and projection time-steps. Must match length nTS in Value
TimeNow	A numeric value matching the last historical timestep in Time
TimeLab	Character string length 1. Name of the time step (e.g., 'Year'). Will be used as the label in the <code>Timeseries</code> plot. Use a named list for multiple languages.
Value	A numeric array with the stochastic performance indicator values for each simulation (sim), operating model (OM), management procedure (MP), performance indicator (PI), and historical + projection timestep (nTS). Dimensions: c(nsim, nOM, nMP, nPI, nTS)
Preset	An optional named list for the preset buttons in the <code>App()</code> . The name of the list element will appear as a button in the <code>App()</code> .
Target	Numeric vector length nPI with the target value for the PIs.
Limit	Numeric vector length nPI with the limit value for the PIs.
RefPoints	List for setting custom Reference Points. Overrides Target and Limit. See Details
Slick	A <code>Slick-class()</code> object
value	A <code>Timeseries-class()</code> object

Details

Use `plotTimeseries()` to create the boxplot from the console.

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Objects of class `Timeseries` are created with `Timeseries()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Custom Reference Points with RefPoints:

`RefPoints` provides more options than the default `Target` and `Limit` reference points. It can be used to control the name and color of the reference point lines, or to add additional reference point lines to the `Timeseries` plot.

Note: If `RefPoints` is included, `Target` and `Limit` are ignored.

`RefPoints` must be a list of length \leq `length(Code)` (i.e., the number of performance indicators). Each element in `RefPoints` should be a named list:

- Name character vector with name(s) of reference point(s)
- Value numeric vector length Name with value(s) for the reference point(s)
- Color character vector length Name with color(s) for the reference point(s)

See Examples

Accessing Slots:

Use the `Code()`, `Label()`, `Description()`, `Value()`, `Preset()` functions to access and assign the values for an existing `Timeseries` object, see Examples

Functions

- `Timeseries(missing)`: Create an empty `Timeseries` object
- `Timeseries(character)`: Create a populated `Timeseries` object
- `Timeseries(list)`: Create a populated `Timeseries` object
- `Timeseries(Slick)`: Return `Timeseries` from a `Slick-class()` object
- `Timeseries(Slick) <- value`: Assign a `Timeseries-class()` object to a `Slick-class()` object

See Also

`Timeseries-class()`, `Code()`, `Label()`, `Description()`, `Metadata()`, `Value()`, `Preset()`, `plotTimeseries()`
`Code()`, `Label()`, `Description()`, `Metadata()`, `Value()`, `Preset()`

Examples

```

# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
nPI <- 3
nHistTS <- 50
nProjTS <- 30
nTS <- nHistTS + nProjTS

set.seed(101)

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1, 1000)

for (om in 1:nOM) {
  for (pi in 1:nPI) {
    # PI identical for historical
    histVals <- matrix(
      pi_means[pi] *
      cumprod(c(rlnorm(nHistTS*nsim, 0, 0.05))),
      nrow=nsim, ncol=nHistTS, byrow=TRUE)
    histVals <- replicate(nMP, histVals)
    values[,om, , pi,1:nHistTS] <- aperm(histVals, c(1,3,2))

    for (mp in 1:nMP) {
      values[,om, mp, pi,(nHistTS+1):nTS] <- matrix(
        pi_means[pi] *
        cumprod(c(rlnorm(nProjTS*nsim, 0, 0.05))),
        nrow=nsim, ncol=nProjTS, byrow=FALSE)
    }
  }
}

# Create and populate Object
timeseries <- Timeseries(Code=c('B/BMSY', 'F/FMSY', 'TAC'),
                        Label=c('B/BMSY',
                                'F/FMSY',
                                'TAC'),
                        Description = c('This is the description for PI 1',
                                       'This is the description for PI 2',
                                       'This is the description for PI 3'),
                        Value=values
)

# Last historical time step
TimeNow(timeseries) <- 2024

# Add values for time steps
Time(timeseries) <- c(rev(seq(TimeNow(timeseries), by=-1, length.out=nHistTS)),
                    seq(TimeNow(timeseries)+1, by=1, length.out=nProjTS))

```

```

# Check
Check(timeseries)

# Add to `Slick` object
slick <- Slick()
Timeseries(slick) <- timeseries

# Plots
plotTimeseries(slick)
plotTimeseries(slick, 2)
plotTimeseries(slick, 3)

plotTimeseries(slick, byMP=TRUE)

plotTimeseries(slick, byOM=TRUE)

# Custom Reference Points
RefPoints(timeseries) <- list(
  list(Name=c('0.5 BMSY', 'BMSY', '1.5 BMSY'),
        Value=c(0.5, 1, 1.5),
        Color=c('red', 'orange', 'green')),
  list(Name=c('0.8 FMSY', 'FMSY'),
        Value=c(0.8,1),
        Color=c('orange', 'red')),
  list(Name='Target Catch',
        Value=1200,
        Color='blue')
)

Timeseries(slick) <- timeseries
plotTimeseries(slick)
plotTimeseries(slick, 2)
plotTimeseries(slick, 3)

```

Timeseries-class *S4 class* Timeseries

Description

Objects of class `Timeseries` are used to store information for the Time Series plots. Like all S4 objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See [Timeseries\(\)](#) and the the See Also section below.

Details

Objects of class `Timeseries` are created with `Timeseries()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in Code, Label, and Description must all be same length as the number of performance indicators (nPIs) in Value

Slots

Code A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See [Details](#)

Label A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See [Details](#)

Description A description for the Performance Indicators for this object. Can include Markdown, see [Examples](#). A character string length nPI or a named list for multi-language support. See [Details](#)

Time A numeric vector with values for the historical and projection time-steps. Must match length nTS in Value. Can also be class Date, POSIXct or POSIXt

TimeNow A numeric value matching the last historical timestep in Time

TimeLab Character string length 1. Name of the time step (e.g., 'Year'). Will be used as the label in the plots. Use a named list for multiple languages.

Value A numeric array with the stochastic performance indicator values for each simulation (sim), operating model (OM), management procedure (MP), performance indicator (PI), and historical + projection timestep (nTS). Dimensions: c(nsim, nOM, nMP, nPI, nTS)

Preset An optional named list for the preset buttons in the [App\(\)](#). The name of the list element will appear as a button in the [App\(\)](#).

Target Numeric vector length nPI with the target value for the PIs.

Limit Numeric vector length nPI with the limit value for the PIs.

RefPoints List for setting custom Reference Points. Overrides Target and Limit. See [Details](#) section in [Timeseries\(\)](#).

See Also

[Timeseries\(\)](#), [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nsim <- 10
nOM <- 2
nMP <- 4
```

```

nPI <- 3
nHistTS <- 50
nProjTS <- 30
nTS <- nHistTS + nProjTS

set.seed(101)

values <- array(NA, dim=c(nsim, nOM, nMP, nPI, nTS))

pi_means <- c(1,1, 1000)

for (om in 1:nOM) {
  for (pi in 1:nPI) {
    # PI identical for historical
    histVals <- matrix(
      pi_means[pi] *
      cumprod(c(rlnorm(nHistTS*nsim, 0, 0.05))),
      nrow=nsim, ncol=nHistTS, byrow=TRUE)
    histVals <- replicate(nMP, histVals)
    values[,om, , pi,1:nHistTS] <- aperm(histVals, c(1,3,2))

    for (mp in 1:nMP) {
      values[,om, mp, pi,(nHistTS+1):nTS] <- matrix(
        pi_means[pi] *
        cumprod(c(rlnorm(nProjTS*nsim, 0, 0.05))),
        nrow=nsim, ncol=nProjTS, byrow=FALSE)
    }
  }
}

# Create and populate Object
timeseries <- Timeseries(Code=c('B/BMSY', 'F/FMSY', 'TAC'),
  Label=c('B/BMSY',
    'F/FMSY',
    'TAC'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
    'This is the description for PI 3'),
  Value=values
)

# Last historical time step
TimeNow(timeseries) <- 2024

# Add values for time steps
Time(timeseries) <- c(rev(seq(TimeNow(timeseries), by=-1, length.out=nHistTS)),
  seq(TimeNow(timeseries)+1, by=1, length.out=nProjTS))

# Check
Check(timeseries)

# Add to `Slick` object
slick <- Slick()

```

```

Timeseries(slick) <- timeseries

# Plots
plotTimeseries(slick)
plotTimeseries(slick, 2)
plotTimeseries(slick, 3)

plotTimeseries(slick, byMP=TRUE)

plotTimeseries(slick, byOM=TRUE)

# Custom Reference Points
RefPoints(timeseries) <- list(
  list(Name=c('0.5 BMSY', 'BMSY', '1.5 BMSY'),
        Value=c(0.5, 1, 1.5),
        Color=c('red', 'orange', 'green')),
  list(Name=c('0.8 FMSY', 'FMSY'),
        Value=c(0.8,1),
        Color=c('orange', 'red')),
  list(Name='Target Catch',
        Value=1200,
        Color='blue')
)

Timeseries(slick) <- timeseries
plotTimeseries(slick)
plotTimeseries(slick, 2)
plotTimeseries(slick, 3)

```

TimeTerminal

Assign or access TimeTerminal for a valid object class

Description

Assign or access TimeTerminal for a valid object class

Usage

```
TimeTerminal(object)
```

```
TimeTerminal(object) <- value
```

```
## S4 method for signature 'Kobe'
TimeTerminal(object)
```

```
## S4 replacement method for signature 'Kobe'
TimeTerminal(object) <- value
```

Arguments

object	An object of class <code>Kobe-class()</code>
value	A numeric value with a value matching one in <code>Kobe@Time Kobe-class()</code> for details.

Value

Returns a numeric values from the `TimeTerminal` slot in `Kobe()` objects

Methods (by class)

- `TimeTerminal(Kobe)`: Return `TimeTerminal` from a `Kobe-class()` object
- `TimeTerminal(Kobe) <- value`: Assign `TimeTerminal` to a `Kobe-class()` object

Tradeoff

Methods for Creating, Accessing and Assigning Tradeoff objects

Description

The `Tradeoff` function is used both to create and modify an `Tradeoff-class()` object. and to access and assign `Tradeoff` for an object of class `Slick-class()`. See Details.

Usage

```
Tradeoff(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list()
)

Tradeoff(Slick) <- value

## S4 method for signature 'missing'
Tradeoff()

## S4 method for signature 'character'
Tradeoff(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list()
)
```

```

## S4 method for signature 'list'
Tradeoff(
  Code = "",
  Label = "",
  Description = "",
  Value = array(),
  Preset = list()
)

## S4 method for signature 'Slick'
Tradeoff(Code)

## S4 replacement method for signature 'Slick'
Tradeoff(Slick) <- value

```

Arguments

Code	A <i>short</i> code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See Details
Label	A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than Code but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See Details
Description	A description for the Performance Indicators for this object. Can include Markdown, see Examples . A character string length nPI or a named list for multi-language support. See Details
Value	A numeric array with the stochastic performance indicator values for each operating model (OM), management procedure (MP), and performance indicator (PI) Dimensions: c(nOM, nMP, nPI)
Preset	An optional named list for the preset buttons in the App() . The name of the list element will appear as a button in the App() .
Slick	A Slick-class() object
value	A Tradeoff-class() object

Details

Objects of class Tradeoff are created with Tradeoff()

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in Code, Label, and Description must all be same length as the number of performance indicators (nPIs) in Value

Functions

- `Tradeoff(missing)`: Create an empty `Tradeoff` object
- `Tradeoff(character)`: Create a populated `Tradeoff` object
- `Tradeoff(list)`: Create a populated `Tradeoff` object
- `Tradeoff(Slick)`: Return `Tradeoff` from a `Slick-class()` object
- `Tradeoff(Slick) <- value`: Assign a `Tradeoff-class()` object to a `Slick-class()` object

See Also

[Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Metadata\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```
# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- rlnorm(1, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
tradeoff <- Tradeoff(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
    'Performance Indicator 2',
    'Performance Indicator 3',
    'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
    'This is the description for PI 2',
    'This is the description for PI 3',
    'This is the description for PI 4'),
  Value=values)

# Check
Check(tradeoff)

# Add to `Slick` object
slick <- Slick()
Tradeoff(slick) <- tradeoff

# Plots
plotTradeoff(slick)
```



```
plotTradeoff(slick, c(1,1,2), c(2,3,3))
```

Tradeoff-class	S4 class Tradeoff
----------------	-------------------

Description

Objects of class `Tradeoff` are used to store information for the Tradeoff plot. Like all S4 objects in `Slick`, slots in this object can be accessed and assigned using functions corresponding to slot name. See [Tradeoff\(\)](#) and the the See Also section below.

Details

Objects of class `Tradeoff` are created with `Tradeoff()`

Multi-Language Support:

Text with multi-language supported can be provided as a named list. Available languages:

- en: English (default)
- es: Spanish
- fr: French

Note:

Character strings in `Code`, `Label`, and `Description` must all be same length as the number of performance indicators (nPIs) in `Value`

Slots

Code A *short* code for the Performance Indicators for this object. A character string length nPI or a named list for multi-language support. See [Details](#)

Label A short label for the Performance Indicators for this object. Used to label axes on charts. Can be longer than `Code` but recommended to keep short as possible so it shows clearly in plots and tables. A character string length nPI or a named list for multi-language support. See [Details](#)

Description A description for the Performance Indicators for this object. Can include Markdown, see [Examples](#). A character string length nPI or a named list for multi-language support. See [Details](#)

Value A 3 dimensional numeric array with the stochastic performance indicator values for operating model (OM), management procedure (MP), and performance indicator (PI). Dimensions: `c(nOM, nMP, and nPI)`

Preset An optional named list for the preset buttons in the [App\(\)](#). The name of the list element will appear as a button in the [App\(\)](#).

See Also

[Tradeoff\(\)](#), [Code\(\)](#), [Label\(\)](#), [Description\(\)](#), [Value\(\)](#), [Preset\(\)](#)

Examples

```

# Generate dummy values
nOM <- 2
nMP <- 4
nPI <- 4

values <- array(NA, dim=c(nOM, nMP, nPI))

pi_means <- runif(nPI, 5, 50)
for (om in 1:nOM) {
  for (mp in 1:nMP) {
    for (pi in 1:nPI) {
      values[om, mp, pi] <- rlnorm(1, log(pi_means[pi]), 0.4)
    }
  }
}

# Create and populate Object
tradeoff <- Tradeoff(Code=c('PI1', 'PI2', 'PI3', 'PI4'),
  Label=c('Performance Indicator 1',
          'Performance Indicator 2',
          'Performance Indicator 3',
          'Performance Indicator 4'),
  Description = c('This is the description for PI 1',
                 'This is the description for PI 2',
                 'This is the description for PI 3',
                 'This is the description for PI 4'),
  Value=values)

# Check
Check(tradeoff)

# Add to `Slick` object
slick <- Slick()
Tradeoff(slick) <- tradeoff

# Plots
plotTradeoff(slick)

plotTradeoff(slick, c(1,1,2), c(2,3,3))

```

Update

Updates an old object of class Slick to new S4 class Slick

Description

Updates an old object of class Slick to new S4 class Slick

Usage

```
Update(slick)
```

Arguments

slick An S3 object of class Slick

Value

An S4 object of class Slick

Examples

```
slick <- Slick() # a dummy old Slick object
slick <- Update(slick) # updated to S4 object
```

Value *Assign or access Value for a valid object class*

Description

Assign or access Value for a valid object class

Usage

```
Value(object)

Value(object) <- value

## S4 method for signature 'Boxplot'
Value(object)

## S4 replacement method for signature 'Boxplot'
Value(object) <- value

## S4 method for signature 'Kobe'
Value(object)

## S4 replacement method for signature 'Kobe'
Value(object) <- value

## S4 method for signature 'Quilt'
Value(object)

## S4 replacement method for signature 'Quilt'
Value(object) <- value

## S4 method for signature 'Tradeoff'
Value(object)
```

```
## S4 replacement method for signature 'Tradeoff'
Value(object) <- value

## S4 method for signature 'Timeseries'
Value(object)

## S4 replacement method for signature 'Timeseries'
Value(object) <- value

## S4 method for signature 'Spider'
Value(object)

## S4 replacement method for signature 'Spider'
Value(object) <- value
```

Arguments

object	An object of class Boxplot-class() , Kobe-class() , Quilt-class() , Spider-class() , Timeseries-class() , or Tradeoff-class()
value	An array, formatted to match the class of object. See the documentation for corresponding object class for more details.

Value

Returns a numeric array with the contents of the Value slot of object

Methods (by class)

- Value(Boxplot): Return Value from a [Boxplot-class\(\)](#) object
- Value(Boxplot) <- value: Assign Value to a [Boxplot-class\(\)](#) object
- Value(Kobe): Return Value from a [Kobe-class\(\)](#) object
- Value(Kobe) <- value: Assign Value to a [Kobe-class\(\)](#) object
- Value(Quilt): Return Value from a [Quilt-class\(\)](#) object
- Value(Quilt) <- value: Assign Value to a [Quilt-class\(\)](#) object
- Value(Tradeoff): Return Value from a [Tradeoff-class\(\)](#) object
- Value(Tradeoff) <- value: Assign Value to a [Tradeoff-class\(\)](#) object
- Value(Timeseries): Return Value from a [Timeseries-class\(\)](#) object
- Value(Timeseries) <- value: Assign Value to a [Timeseries-class\(\)](#) object
- Value(Spider): Return Value from a [Spider-class\(\)](#) object
- Value(Spider) <- value: Assign Value to a [Spider-class\(\)](#) object

Index

App, 3
App(), 5, 7, 16, 23, 25, 26, 34, 36, 39, 41, 60, 63, 71, 74, 79, 83, 87, 89
Author (Slick-class), 66
Author(), 69
Author<- (Slick-class), 66

Boxplot, 4, 42
Boxplot(), 7, 8, 16, 66, 69
Boxplot, character_list-method (Boxplot), 4
Boxplot, missing-method (Boxplot), 4
Boxplot, Slick-method (Boxplot), 4
Boxplot-class, 7
Boxplot<- (Boxplot), 4
Boxplot<- , Slick-method (Boxplot), 4

Check, 8
Check(), 69
Check, Boxplot-method (Check), 8
Check, Kobe-method (Check), 8
Check, MPs-method (Check), 8
Check, OMs-method (Check), 8
Check, Quilt-method (Check), 8
Check, Slick-method (Check), 8
Check, Spider-method (Check), 8
Check, Timeseries-method (Check), 8
Check, Tradeoff-method (Check), 8
Code, 10
Code(), 5, 6, 8, 24, 26, 34–36, 61, 63, 71, 72, 74, 80, 83, 88, 89
Code, Boxplot-method (Code), 10
Code, Kobe-method (Code), 10
Code, MPs-method (Code), 10
Code, Quilt-method (Code), 10
Code, Spider-method (Code), 10
Code, Timeseries-method (Code), 10
Code, Tradeoff-method (Code), 10
Code<- (Code), 10
Code<- , Boxplot-method (Code), 10
Code<- , Kobe-method (Code), 10
Code<- , MPs-method (Code), 10
Code<- , Quilt-method (Code), 10
Code<- , Spider-method (Code), 10
Code<- , Timeseries-method (Code), 10
Code<- , Tradeoff-method (Code), 10
Color, 15
Color(), 35, 61
Color, MPs-method (Color), 15
Color, Quilt-method (Color), 15
Color<- (Color), 15
Color<- , MPs-method (Color), 15
Color<- , Quilt-method (Color), 15

Date (Slick-class), 66
Date(), 69
Date<- (Slick-class), 66
default_mp_colors, 17
Defaults, 16
Defaults(), 6
Defaults, Boxplot-method (Defaults), 16
Defaults, Kobe-method (Defaults), 16
Defaults<- (Defaults), 16
Defaults<- , Boxplot-method (Defaults), 16
Defaults<- , Kobe-method (Defaults), 16
Description (Code), 10
Description(), 5, 6, 8, 15, 24, 26, 34–36, 61, 63, 71, 72, 74, 80, 83, 88, 89
Description, Boxplot-method (Code), 10
Description, Kobe-method (Code), 10
Description, MPs-method (Code), 10
Description, Quilt-method (Code), 10
Description, Spider-method (Code), 10
Description, Timeseries-method (Code), 10
Description, Tradeoff-method (Code), 10
Description<- (Code), 10
Description<- , Boxplot-method (Code), 10
Description<- , Kobe-method (Code), 10
Description<- , MPs-method (Code), 10
Description<- , Quilt-method (Code), 10

- Description<- ,Spider-method (Code), 10
- Description<- ,Timeseries-method (Code), 10
- Description<- ,Tradeoff-method (Code), 10
- Design, 17
- Design(), 39, 41
- Design,OMs-method (Design), 17
- Design,Slick-method (Design), 17
- Design<- (Design), 17
- Design<- ,OMs-method (Design), 17
- Design<- ,Slick-method (Design), 17
- download_casestudy (get_casestudies), 20
- Email (Slick-class), 66
- Email(), 69
- Email<- (Slick-class), 66
- Factors, 18
- Factors(), 39, 41
- Factors,OMs-method (Factors), 18
- Factors,Slick-method (Factors), 18
- Factors<- (Factors), 18
- Factors<- ,OMs-method (Factors), 18
- Factors<- ,Slick-method (Factors), 18
- FilterSlick, 19
- get_casestudies, 20
- Institution (Slick-class), 66
- Institution(), 69
- Institution<- (Slick-class), 66
- Introduction (Slick-class), 66
- Introduction(), 69
- Introduction<- (Slick-class), 66
- Kobe, 21
- Kobe(), 16, 23, 26, 28, 45, 66, 69, 76, 77, 86
- Kobe, character-method (Kobe), 21
- Kobe, list-method (Kobe), 21
- Kobe, missing-method (Kobe), 21
- Kobe, Slick-method (Kobe), 21
- Kobe-class, 25
- Kobe<- (Kobe), 21
- Kobe<- ,Slick-method (Kobe), 21
- Label (Code), 10
- Label(), 5, 6, 8, 15, 24, 26, 34–36, 61, 63, 71, 72, 74, 80, 83, 88, 89
- Label, Boxplot-method (Code), 10
- Label, Kobe-method (Code), 10
- Label, MPs-method (Code), 10
- Label, Quilt-method (Code), 10
- Label, Spider-method (Code), 10
- Label, Timeseries-method (Code), 10
- Label, Tradeoff-method (Code), 10
- Label<- (Code), 10
- Label<- ,Boxplot-method (Code), 10
- Label<- ,Kobe-method (Code), 10
- Label<- ,MPs-method (Code), 10
- Label<- ,Quilt-method (Code), 10
- Label<- ,Spider-method (Code), 10
- Label<- ,Timeseries-method (Code), 10
- Label<- ,Tradeoff-method (Code), 10
- Limit, 27
- Limit(), 24
- Limit, Kobe-method (Limit), 27
- Limit, Timeseries-method (Limit), 27
- Limit<- (Limit), 27
- Limit<- ,Kobe-method (Limit), 27
- Limit<- ,Timeseries-method (Limit), 27
- Make_Slick, 29
- MaxValue (MinValue), 33
- MaxValue(), 61
- MaxValue<- (MinValue), 33
- Metadata, 31
- Metadata(), 6, 8, 35, 61, 72, 80, 88
- Metadata, Boxplot-method (Metadata), 31
- Metadata, Kobe-method (Metadata), 31
- Metadata, MPs-method (Metadata), 31
- Metadata, Quilt-method (Metadata), 31
- Metadata, Slick-method (Metadata), 31
- Metadata, Spider-method (Metadata), 31
- Metadata, Timeseries-method (Metadata), 31
- Metadata, Tradeoff-method (Metadata), 31
- Metadata<- (Metadata), 31
- Metadata<- ,Boxplot-method (Metadata), 31
- Metadata<- ,Kobe-method (Metadata), 31
- Metadata<- ,MPs-method (Metadata), 31
- Metadata<- ,Quilt-method (Metadata), 31
- Metadata<- ,Spider-method (Metadata), 31
- Metadata<- ,Timeseries-method (Metadata), 31
- Metadata<- ,Tradeoff-method (Metadata), 31
- methods::show(), 65
- MinValue, 33
- MinValue(), 61

- MinValue<- (MinValue), 33
- MPs, 34
- MPs(), 36, 66, 69
- MPs,character_list-method (MPs), 34
- MPs,missing-method (MPs), 34
- MPs,Slick-method (MPs), 34
- MPs-class, 36
- MPs<- (MPs), 34
- MPs<- ,Slick-method (MPs), 34
- NewSlick, 37
- OMs, 38
- OMs(), 40, 41, 66, 69
- OMs,dataframe_list-method (OMs), 38
- OMs,missing-method (OMs), 38
- OMs,Slick-method (OMs), 38
- OMs-class, 40
- OMs<- (OMs), 38
- OMs<- ,Slick-method (OMs), 38
- plotBoxplot, 42
- plotBoxplot(), 5, 6
- plotKobe, 44
- plotQuilt, 46
- plotSpider, 48
- plotTimeseries, 51
- plotTimeseries(), 80
- plotTradeoff, 55
- PMnorm, 56
- Preset, 57
- Preset(), 5, 6, 8, 24, 26, 34–36, 39, 41, 61, 63, 71, 72, 74, 80, 83, 88, 89
- Preset,Boxplot-method (Preset), 57
- Preset,Kobe-method (Preset), 57
- Preset,MPs-method (Preset), 57
- Preset,OMs-method (Preset), 57
- Preset,Quilt-method (Preset), 57
- Preset,Spider-method (Preset), 57
- Preset,Timeseries-method (Preset), 57
- Preset,Tradeoff-method (Preset), 57
- Preset<- (Preset), 57
- Preset<- ,Boxplot-method (Preset), 57
- Preset<- ,Kobe-method (Preset), 57
- Preset<- ,MPs-method (Preset), 57
- Preset<- ,OMs-method (Preset), 57
- Preset<- ,Quilt-method (Preset), 57
- Preset<- ,Spider-method (Preset), 57
- Preset<- ,Timeseries-method (Preset), 57
- Preset<- ,Tradeoff-method (Preset), 57
- Quilt, 59
- Quilt(), 33, 47, 62, 63, 66, 69
- Quilt,character_list-method (Quilt), 59
- Quilt,missing-method (Quilt), 59
- Quilt,Slick-method (Quilt), 59
- Quilt-class, 62
- Quilt<- (Quilt), 59
- Quilt<- ,Slick-method (Quilt), 59
- RefPoints, 64
- RefPoints,Timeseries-method (RefPoints), 64
- RefPoints<- (RefPoints), 64
- RefPoints<- ,Timeseries-method (RefPoints), 64
- show, 65
- show,Boxplot-method (show), 65
- show,CheckList-method (show), 65
- show,Kobe-method (show), 65
- show,MPs-method (show), 65
- show,OMs-method (show), 65
- show,Quilt-method (show), 65
- show,Slick-method (show), 65
- show,Spider-method (show), 65
- show,Timeseries-method (show), 65
- show,Tradeoff-method (show), 65
- Slick, 30, 38, 57
- Slick (Slick-class), 66
- Slick(), 32, 35, 39, 40
- Slick-class, 66
- Spider, 70, 73, 74
- Spider(), 66, 69
- Spider,character-method (Spider), 70
- Spider,list-method (Spider), 70
- Spider,missing-method (Spider), 70
- Spider,Slick-method (Spider), 70
- Spider-class, 73
- Spider<- (Spider), 70
- Spider<- ,Slick-method (Spider), 70
- Subtitle (Slick-class), 66
- Subtitle(), 69
- Subtitle<- (Slick-class), 66
- Target (Limit), 27
- Target(), 24
- Target,Kobe-method (Limit), 27

- Target, Timeseries-method (Limit), 27
- Target<- (Limit), 27
- Target<-, Kobe-method (Limit), 27
- Target<-, Timeseries-method (Limit), 27
- Time, 75
- Time(), 24
- Time, Kobe-method (Time), 75
- Time, Timeseries-method (Time), 75
- Time<- (Time), 75
- Time<-, Kobe-method (Time), 75
- Time<-, Timeseries-method (Time), 75
- TimeLab, 76
- TimeLab, Kobe-method (TimeLab), 76
- TimeLab, Timeseries-method (TimeLab), 76
- TimeLab<- (TimeLab), 76
- TimeLab<-, Kobe-method (TimeLab), 76
- TimeLab<-, Timeseries-method (TimeLab), 76
- TimeNow, 77
- TimeNow<- (TimeNow), 77
- Timeseries, 76, 78
- Timeseries(), 28, 53, 64, 66, 69, 75–77, 82, 83
- Timeseries, character-method (Timeseries), 78
- Timeseries, list-method (Timeseries), 78
- Timeseries, missing-method (Timeseries), 78
- Timeseries, Slick-method (Timeseries), 78
- Timeseries-class, 82
- Timeseries-class(), 77
- Timeseries<- (Timeseries), 78
- Timeseries<-, Slick-method (Timeseries), 78
- TimeTerminal, 85
- TimeTerminal, Kobe-method (TimeTerminal), 85
- TimeTerminal<- (TimeTerminal), 85
- TimeTerminal<-, Kobe-method (TimeTerminal), 85
- Title (Slick-class), 66
- Title(), 69
- Title<- (Slick-class), 66
- Tradeoff, 86
- Tradeoff(), 66, 69, 89
- Tradeoff, character-method (Tradeoff), 86
- Tradeoff, list-method (Tradeoff), 86
- Tradeoff, missing-method (Tradeoff), 86
- Tradeoff, Slick-method (Tradeoff), 86
- Tradeoff-class, 89
- Tradeoff<- (Tradeoff), 86
- Tradeoff<-, Slick-method (Tradeoff), 86
- Update, 90
- Value, 91
- Value(), 5, 6, 8, 24, 26, 61, 63, 71, 72, 74, 80, 83, 88, 89
- Value, Boxplot-method (Value), 91
- Value, Kobe-method (Value), 91
- Value, Quilt-method (Value), 91
- Value, Spider-method (Value), 91
- Value, Timeseries-method (Value), 91
- Value, Tradeoff-method (Value), 91
- Value<- (Value), 91
- Value<-, Boxplot-method (Value), 91
- Value<-, Kobe-method (Value), 91
- Value<-, Quilt-method (Value), 91
- Value<-, Spider-method (Value), 91
- Value<-, Timeseries-method (Value), 91
- Value<-, Tradeoff-method (Value), 91