

Package ‘spacesXYZ’

February 10, 2025

Type Package

Title CIE XYZ and some of Its Derived Color Spaces

Version 1.5-1

Encoding UTF-8

Date 2025-02-09

Maintainer Glenn Davis <gdavis@gluonics.com>

Description Functions for converting among CIE XYZ, xyY, Lab, and Luv.

Calculate Correlated Color Temperature (CCT) and the Planckian and daylight loci.

The XYZs of some standard illuminants and some standard linear chromatic adaptation transforms (CATs) are included.

Three standard color difference metrics are included, plus the forward direction of the 'CIECAM02' color appearance model.

License GPL (>= 3)

LazyLoad yes

LazyData yes

Depends R (>= 4.0.0)

Imports logger

Suggests knitr, rmarkdown, microbenchmark

Enhances colorSpec

Repository CRAN

VignetteBuilder knitr

BuildVignettes yes

NeedsCompilation no

Author Glenn Davis [aut, cre]

Date/Publication 2025-02-10 00:00:02 UTC

Contents

spacesXYZ-package	2
adapt	3
adaptation	5
CIECAM02fromXYZ	8
Correlated Color Temperature	9
daylight	13
DeltaE	14
DeltaE_CAM02	15
fromPolar	16
fromXYZ	17
Planckian Loci	18
standardXYZ	20
toPolar	22
toXYZ	23
uvfrom	24
Index	26

spacesXYZ-package *CIE XYZ and some of Its Derived Color Spaces*

Description

This package covers the basic CIE 1931 space, and derived spaces CIE xyY, Lab, and Luv. The equations are taken from Bruce Lindbloom's *CIE Color Calculator*. Color areas that are *not* covered are:

- spectral color data
- device color spaces, e.g. RGB and CMYK
- color order systems, e.g. Munsell, DIN, NCS, Ostwald, ...

The API

The API is small. There are functions to

- convert between CIE XYZ and other CIE spaces
- create and perform some standard chromatic adaptation transforms (CATs)
- compute 3 standard color difference ΔE metrics
- retrieve XYZ and xy of some standard illuminants

Other Packages

Package **colorscience** is a superset of this one.

Packages **colorspace** and **farver** have similar functionality, and are faster because they are in compiled C/C++.

Package **grDevices** also has similar functionality (in the function `convertColor()`), but is missing chromaticities xy, uv, and u'v'.

Logging

Logging is performed using the package **logger**. This is a powerful package that allows a separate configuration for logging from within **spacesXYZ**, and that is what I have done. When **spacesXYZ** is loaded, the logging threshold is changed from INFO to WARN. To change it back again, one can execute:

```
logger::log_threshold( logger::INFO, namespace="spacesXYZ" ) # preferred
or
library( logger )
log_threshold( INFO, namespace="spacesXYZ" ) # not preferred
```

The layout callback function is customized; it adds the name of the calling function to the message. To change it back again, one can execute:

```
log_layout( layout_simple, namespace="spacesXYZ" )
or to install ones own layout function, one can execute:
log_layout( <your function>, namespace="spacesXYZ" ).
```

The appender callback functions is also customized; it comes to an immediate stop if the log event level is FATAL or ERROR. To continue execution after such a log event, one can execute:

```
log_appender( appender_console, namespace="spacesXYZ" )
```

The formatter callback function is initialized to be `formatter_sprintf()`; this should not be changed.

Author(s)

Glenn Davis <gdavis@gluonics.com>

References

Lindbloom, Bruce. **CIE Color Calculator**. <http://brucelindbloom.com/index.html?ColorCalculator.html>

Lindbloom, Bruce. **Color Difference Calculator**. <http://brucelindbloom.com/index.html?ColorDifferenceCalc.html>

adapt

Chromatic Adaptation Functions

Description

Adapt XYZ, xyY, Lab, or Luv from a source viewing environment with a given illuminant, to a target viewing environment with a different illuminant.

Usage

```
## S3 method for class 'CAT'
adaptXYZ( x, XYZ.src )

## S3 method for class 'CAT'
```

```

adaptxyY( x, xyY.src )
## S3 method for class 'CAT'
adaptLab( x, Lab.src )
## S3 method for class 'CAT'
adaptLuv( x, Luv.src )

```

Arguments

<code>x</code>	a CAT object as returned from <code>CAT()</code>
<code>XYZ.src</code>	an Nx3 matrix, or a vector that can be converted to such a matrix, by rows. Each row has an XYZ in the source viewing environment.
<code>xyY.src</code>	an Nx3 matrix, or a vector that can be converted to such a matrix, by rows. Each row has an xyY in the source viewing environment.
<code>Lab.src</code>	an Nx3 matrix, or a vector that can be converted to such a matrix, by rows. Each row has an Lab in the source viewing environment.
<code>Luv.src</code>	an Nx3 matrix, or a vector that can be converted to such a matrix, by rows. Each row has an Luv in the source viewing environment.

Details

`adaptXYZ()` is the most fundamental of the group; it simply multiplies each of the input XYZs by `x$M`.

`adaptxyY()` converts `xyY.src` to XYZ, calls `adaptXYZ()`, and then converts back to `xyY.tgt`. And it does an additional check: if the xy of `xyY.src` is equal to the xy of `x$source.xyY`, then the xy of the returned `xyY.tgt` is set to be the xy of `x$target.xyY`.

`adaptLab()` and `adaptLuv()` work in a similar way. When `Lab.src` is transformed to XYZ, the whitepoint is set to `x$source.XYZ`. And when the adapted XYZ is transformed to adapted Lab, the whitepoint is set to `target.XYZ`.

Value

`adaptXYZ()` returns an Nx3 matrix with adapted XYZ. Each row has an XYZ in the target viewing environment.

`adaptxyY()` returns an Nx3 matrix with adapted xyY. Each row has an xyY in the target viewing environment.

`adaptLab()` and `adaptLuv()` return adapted Lab and Luv respectively.

References

Hunt, R. W. G. **The Reproduction of Colour**. 6th Edition. John Wiley & Sons. 2004.

International Color Consortium. ICC.1:2001-04. File Format for Color Profiles. 2001.

Lindbloom, Bruce. Chromatic Adaptation. http://brucelindbloom.com/Eqn_ChromAdapt.html

Wikipedia. CIECAM02. <https://en.wikipedia.org/wiki/CIECAM02>

See Also

`CAT()`, `standardXYZ()`

Examples

```

# try the Bradford method
bCAT = CAT( 'D50', 'D65', method='bradford' )

adaptXYZ( bCAT, c(1,1,0.5) )
##           X           Y           Z
## [1,] 0.9641191 0.9921559 0.6567701

adaptLab( bCAT, c(50,20,-10) )
##           L           a           b
## [1,] 49.97396 20.84287 -10.19661 # as expected, there is a change

adaptLab( bCAT, c(40,0,0) )
##           L a b
## [1,] 40 0 0 # but adaptLab() always preserves neutrals

adaptLuv( bCAT, c(40,0,0) )
##           L u v
## [1,] 40 0 0 # and adaptLuv() also preserves neutrals

# try the scaling method - now XYZ are scaled independently
sCAT = CAT( 'D50', 'D65', method='scaling' )

adaptLab( sCAT, c(50,20,-10) )
##           L a b
## [1,] 50 20 -10 with sCAT, adaptLab() is now the identity for *all* colors

adaptLuv( sCAT, c(50,-20,10) )
##           L           u           v
## [1,] 50 -18.32244 11.29946 but adaptLuv() is NOT the identity for all colors

```

adaptation

Chromatic Adaptation Transforms (CATs)

Description

Construct transforms from a source viewing environment with a given illuminant, to a target viewing environment with a different illuminant. Some standard linear von-Kries-based CAT methods are available.

Usage

```
CAT( source.XYZ, target.XYZ, method="Bradford" )
```

Arguments

source.XYZ	the XYZ of the illuminant in the source viewing environment. source.XYZ can also be a string with the name of a standard illuminant as in the function standardXYZ().
target.XYZ	the XYZ of the illuminant in the target viewing environment. target.XYZ can also be a string with the name of a standard illuminant as in the function standardXYZ().
method	the method used for the chromatic adaptation. Available methods are: "Bradford", "VonKries", "MCAT02", "Bianco+Schettini", and "scaling"; see References . Partial matching is enabled, and matching is case-insensitive. method can also be a 3x3 matrix, which is the cone response matrix used to construct a von-Kries-based CAT. The matrix must be invertible and map both source.XYZ and target.XYZ to the positive octant.

Value

CAT() returns an object with S3 class **CAT**, which can be passed to [adaptXYZ\(\)](#), [adaptxyY\(\)](#), [adaptLab\(\)](#), or [adaptLuv\(\)](#).

An object with S3 class **CAT** is a list with the following items:

method full name of the adaptation method, as in **Arguments**. If argument method is a 3x3 matrix, then this method is NA.

Ma 3x3 cone response matrix M_A for the method, as defined in *Lindbloom*

source.XYZ XYZ of the illuminant in the source viewing environment

source.xyY xyY of the illuminant in the source viewing environment

target.XYZ XYZ of the illuminant in the target viewing environment

target.xyY xyY of the illuminant in the target viewing environment

M 3x3 matrix defining the CAT. The matrix is written on the left and the source XYZ is written as a column vector on the right. This matrix depends continuously on source.XYZ and target.XYZ, and when these are equal, M is the identity. Therefore, when source.XYZ and target.XYZ are close, M is close to the identity. Compare with *Lindbloom*.

Note

Chromatic adaptation can be viewed as an Aristotelian Analogy of Proportions. For more about this, see the vignette **Chromatic Adaptation**.

References

- Bianco, Simone and Raimondo Schettini. **Two new von Kries based chromatic adaptation transforms found by numerical optimization**. Color Research & Application. v. 35. i. 3. Jan 2010.
- Hunt, R. W. G. **The Reproduction of Colour**. 6th Edition. John Wiley & Sons. 2004.
- International Color Consortium. ICC.1:2001-04. File Format for Color Profiles. 2001.
- Lindbloom, Bruce. Chromatic Adaptation. http://bruceindbloom.com/Eqn_ChromAdapt.html

Pascale, Danny. A Review of RGB Color Spaces ...from xyY to R'G'B'. https://babelcolor.com/index_htm_files/A%20review%20of%20RGB%20color%20spaces.pdf 2003.

Wikipedia. CIECAM02. <https://en.wikipedia.org/wiki/CIECAM02>

See Also

[standardXYZ\(\)](#), [adaptXYZ\(\)](#), [adaptxyY\(\)](#), [adaptLab\(\)](#), [adaptLuv\(\)](#)

Examples

```
D65toC = CAT( 'D65', 'C' )
D65toC

## $method
## [1] "Bradford"
##
## $Ma
##      X      Y      Z
## L  0.8951  0.2664 -0.1614
## M -0.7502  1.7135  0.0367
## S  0.0389 -0.0685  1.0296
##
## $source.XYZ
##      X Y      Z
## D65 0.95047 1 1.08883
##
## $source.xyY
##      x      y Y
## D65 0.3127266 0.3290231 1
##
## $target.XYZ
##      X Y      Z
## C 0.98074 1 1.18232
##
## $target.xyY
##      x      y Y
## C 0.3100605 0.3161496 1
##
## $M
##      X      Y      Z
## X 1.009778519 0.007041913 0.012797129
## Y 0.012311347 0.984709398 0.003296232
## Z 0.003828375 -0.007233061 1.089163878
##
## attr("class")
## [1] "CAT" "list"

adaptXYZ( D65toC, c(1,1,0.5) )
##      X      Y      Z
## [1,] 1.023219 0.9986689 0.5411773
```

CIECAM02fromXYZ

*Compute CIECAM02 Quantities from XYZ***Description**

CIECAM02 is a widely used Color Appearance Model. This function computes many of the quantities in this model from XYZ.

Usage

```
CIECAM02fromXYZ( XYZ, XYZ_w, L_A=100, Y_b=20, surround='Average', discount=TRUE )
```

Arguments

XYZ	a numeric Nx3 matrix with XYZ values in the rows. It can also be a vector that can be converted to such a matrix, by row.
XYZ_w	XYZ of the adapting white point. It should be scaled so that $Y_w=100$. All values must be positive. XYZ_w can also be a character string with the name of a standard illuminant, which is passed to <code>standardXYZ()</code> to get the XYZ.
L_A	absolute luminance of the adapting field.
Y_b	luminous factor of background.
surround	surround conditions, valid values are 'Average', 'Dim', 'Dark'. Matching is partial and caseless.
discount	whether or not observers are discounting the illuminant (color constancy is in effect).

Value

a data.frame with N rows and these columns:

XYZ	the input Nx3 matrix
h	hue angle, in degrees
J	correlate of Lightness
Q	correlate of Brightness
C	correlate of Chroma
M	correlate of Colorfulness
Jp	Lightness J' in CAM02-UCS space
abp	rectangular coordinates (a', b') in CAM02-UCS space

The rownames are set to those of XYZ. The other function arguments (XYZ_w, ...) are attached to the data.frame as attributes.

Author(s)

Glenn Davis

References

Fairchild, Mark D. CIECAM02. in **Color Appearance Models** (3rd ed.). pp. 287-302. John Wiley & Sons. 2013.

See Also

[DeltaE_CAM02\(\)](#)

Examples

```
CIECAM02fromXYZ( c(19.01,20,21.78), c(95.05,100,108.88), L_A=318.31 )

# XYZ.1 XYZ.2 XYZ.3      h      J      Q      C      M      Jp      abp.1      abp.2
# 19.01 20.00 21.78 219.0484 41.73109 195.3713 0.1047078 0.1088422 54.90433 -0.03666471 -0.02974185
```

Correlated Color Temperature

Compute Correlated Color Temperature (CCT) and Points on the Planckian Locus

Description

Compute the CCT in Kelvin, of XYZ, xy, and uv, by multiple methods. And compute points on the Planckian locus.

The *reference* Planckian locus is defined spectrally - from the famous equation for the Planckian radiator (with $c_2 = 1.4388 \times 10^{-2}$) and from the tabulated CIE 1931 standard observer color matching functions, from 360 to 830nm in 1nm steps. The reference locus is a C^∞ curve, parameterized by temperature, in a 2D chromaticity space, usually either xy (1931) or uv (1960). Computing uv values (and derivatives) is lengthy because there are 471 wavelengths. An approximation to the reference locus is desirable.

The default locus approximation is a cubic spline (using `stats::splinefun()` with `method="fmm"`) through the 31 uv locus points in *Robertson* and *Wyszecki & Stiles*. This spline does not appear in *Robertson*, but I think he would approve of it. It has C^2 continuity and good agreement with the reference locus. The maximum RMS error in the uv-plane is about 7.3×10^{-6} over the valid temperature interval $[1667, \infty]$ K. A similar piecewise-linear interpolating path has a maximum RMS error about 10 times larger. The 31 uv values in the table are accurate to the given 5 decimal places (but see **Note**), and the rounding to 5 places is a big limitation in accuracy. The locus is parameterized directly by reciprocal color temperature ($10^6/T$), and therefore indirectly by T . We call either of these the *native parameterization* of the locus. See [Planckian Loci](#). The lines that are perpendicular to the locus are called the *native isotherms*.

The second available locus is a quintic spline through 65 points (knots), that were computed offline and saved with full precision. The maximum RMS error in the uv-plane is about 7.2×10^{-12} over the valid temperature interval $[1000, \infty]$ K. For this one the 1st and 2nd derivatives were also computed, so the normal vectors at the knots are accurate, and the curve is also C^2 . See [Planckian Loci](#). The lines that are perpendicular to the locus are called the *native isotherms* for the locus.

Since there are 2 available loci, technically there are 2 distinct native isotherms, but they are very similar.

Two more families of isotherms are available. The *Robertson* isotherms are tabulated just like the points on the locus, and a special linear interpolation is used for intermediate temperatures. The *McCamy* isotherms are defined by a single cubic rational function in xy , and no interpolation is necessary. Each isotherm family *induces* a slightly different parameterization of the locus - the temperature at a locus point is the temperature of the isotherm passing through that point.

The Robertson parameterization is only continuous of class C^0 , but the *geometric continuity* class is G^2 . The McCamy parameterization is as smooth as the locus itself, which is C^2 .

For the Robertson parameterization the valid temperature interval is $[1667, \infty]$ K. For the McCamy parameterization the valid temperature interval is at most $[1621, 34530]$ K, and may be smaller depending on the locus.

Usage

```
CCTfromXYZ( XYZ, isotherms='robertson', locus='robertson', strict=FALSE )
CCTfromxy( xy, isotherms='robertson', locus='robertson', strict=FALSE )
CCTfromuv( uv, isotherms='robertson', locus='robertson', strict=FALSE )

planckLocus( temperature, locus='robertson', param='robertson', Duv=0, space=1960 )
```

Arguments

XYZ	a numeric Mx3 matrix with XYZ tristimulus values (CIE 1931) in the rows, or a numeric vector that can be converted to such a matrix, by row.
xy	a numeric Mx2 matrix with xy chromaticity values (CIE 1931) in the rows, or a numeric vector that can be converted to such a matrix, by row.
uv	a numeric Mx2 matrix with uv chromaticity values (CIE UCS 1960) in the rows, or a numeric vector that can be converted to such a matrix, by row.
isotherms	A character vector whose elements match one of the available isotherm families: 'robertson', 'mccamy', and 'native'. Matching is partial and case-insensitive. When more than one family is given, a matrix is returned, see Value . When isotherms='native' the isotherms are defined implicitly as lines perpendicular to the locus given by the next argument, see Details .
locus	valid values are 'robertson' and 'precision', see above. Matching is partial and case-insensitive.
strict	The CIE considers the CCT of a chromaticity uv to be meaningful only if the distance from uv to the Planckian locus is less than or equal to 0.05 [in CIE UCS 1960]. If strict=FALSE, then this condition is ignored. Otherwise, the distance is computed along the corresponding isotherm, and if it exceeds 0.05 the returned CCT is set to NA.
temperature	a M-vector of temperatures (in K) at which to compute points on the Planckian locus, either for uv, u'v', or xy; see space.
param	the desired parameterization of the locus. It can be either 'native', or a parameterization induced by the 'robertson' or 'mccamy' isotherms.

Duv	a vector of offset distances in uv (CIE UCS 1960), along the corresponding isotherms, from the locus. Positive offsets are above the locus (greener), and negative offsets are below (purpler). Duv can have length M or 1, where M is the length of temperature. If Duv has length 1, that value is replicated to length M.
space	the year of the chromaticity space to return. Valid values are 1960 (the default uv), 1976 (u'v'), and 1931 (xy).

Details

Each of the isotherm families correspond to a parameterization of the locus. All this is designed so a round trip: temperature \rightarrow uv \rightarrow CCT (with the same choice of isotherm/parameterization) has negligible error.

When `isotherms='native'` the tangent line at a point on the locus is computed using the `deriv=1` argument to `stats::splinefun()` and the normal line - the isotherm at the point - is then easily computed from the tangent line.

When `isotherms='robertson'` or `isotherms='mccamy'` the locus curve has no effect on the computed CCT. The locus is only used when computing the distance from the given uv point to the locus (along the corresponding isotherm), and therefore only affects the decision whether the CCT is meaningful when `strict=TRUE`.

Value

`CCTfromXYZ()`, `CCTfromxy()`, and `CCTfromuv()` return a numeric vector of length M, or an MxN matrix. It returns a matrix iff `length(isotherms) = N \geq 2`. The column names are set to the isotherm family names. The names or rownames are set to the rownames of the input. In case of error, the element of the vector or matrix is set to `NA_real_`. In case there is an error in the arguments, the functions return NULL. In these functions, the locus is not used unless `isotherms='native'` or `strict=TRUE`.

A matrix of Duv values, with the same dimensions as the returned array of CCT values, is attached as attribute "Duv".

`planckLocus()` returns an Mx2 matrix with chromaticities in the rows. The column names are set appropriately for the value of space. The row names are set from temperature. In case of a single error, both entries in the row are set to `NA_real_`. In case there is an error in the arguments, the functions return NULL.

Note

The lookup table on page 228 in *Wyszecki & Stiles* contains an error at 325 mired, which was corrected by Bruce Lindbloom (see [Source](#)).

Source

http://www.brucelindbloom.com/index.html?Eqn_XYZ_to_T.html

References

McCamy, C. S. *Correlated color temperature as an explicit function of chromaticity coordinates*. Color Research & Application. Volume 17. Issue 2. pages 142-144. April 1992.

Robertson, A. R. Computation of correlated color temperature and distribution temperature. *Journal of the Optical Society of America*. 58. pp. 1528-1535 (1968).

Wyszecki, Günther and W. S. Stiles. **Color Science: Concepts and Methods, Quantitative Data and Formulae, Second Edition**. John Wiley & Sons, 1982. Table 1(3.11). pp. 227-228.

See Also

[stats::splinefun\(\)](#), [colorSpec::computeCCT\(\)](#), [RobertsonLocus](#), [PrecisionLocus](#), the vignette [Correlated Color Temperature Isotherms](#)

Examples

```
# do a round trip and then compare
temperature = c(5003,6504)
uv = planckLocus( temperature, Duv=0.05 )
CCTfromuv( uv ) - temperature
##          5003K          6504K
## -5.395038e-05 -1.984926e-04

# find some points on the daylight locus, and then their CCT
temperature = seq( 2000, 10000, by=1000 )
xy = daylightLocus( temperature )
cbind( xy, CCT=CCTfromxy(xy,iso='mccamy') )
##          x          y          CCT
## D2000          NA          NA          NA
## D3000          NA          NA          NA
## D4000  0.3823436  0.3837663  4005.717
## D5000  0.3457410  0.3586662  4999.998
## D6000  0.3216915  0.3377984  5999.437
## D7000  0.3053570  0.3216459  6997.542
## D8000  0.2937719  0.3092195  7985.318
## D9000  0.2852645  0.2995816  8948.809
## D10000 0.2787996  0.2919672  9881.115

# compare all 3 different isotherms
CCTfromxy( xy, isotherms=c('robertson','native','mccamy') )
##          Robertson  native  McCamy
## D2000          NA          NA          NA
## D3000          NA          NA          NA
## D4000  4000.096  4000.062  4005.717
## D5000  4999.749  4999.608  4999.998
## D6000  5998.015  5999.242  5999.437
## D7000  6997.858  6998.258  6997.542
## D8000  7997.599  7996.985  7985.318
## D9000  8999.301  8993.811  8948.809
## D10000 9991.920  9992.672  9881.115

cbind( default=CCTfromxy(xy), prec.native=CCTfromxy(xy,locus='prec',iso='native') )
##          default  prec.native
## 2000K          NA          NA
## 3000K          NA          NA
## 4000K  4000.096   4000.052
```

```
## 5000K 4999.749 4999.767
## 6000K 5998.015 5999.097
## 7000K 6997.858 6997.857
## 8000K 7997.599 7997.951
## 9000K 8999.301 8995.835
## 10000K 9991.920 9992.839
```

daylight *Compute Points on the Daylight Locus, in multiple Chromaticity Spaces*

Description

Compute points on the daylight locus, in multiple chromaticity spaces

Usage

```
daylightLocus( temperature, space=1931 )
```

Arguments

temperature	an M-vector of temperatures (in K) at which to compute points on the daylight locus. The valid temperatures range is 4000K to 25000K; outside this range the output is set to NA.
space	the year of the output chromaticity space desired - valid values are 1931, 1976 and 1960. The 1931 is the original and denoted by xy; the others are derived from it. The 1960 coordinates are usually denoted by uv, and the 1976 coordinates by u'v'. The only difference is that $v' = (3/2)v$.

Value

a numeric Mx2 matrix with xy, uv, or u'v' coordinates in the rows. The colnames of the output are set appropriately.

The names of the temperature are copied to the rownames of the output, unless these names are NULL when the temperatures followed by 'K' are used.

If the input is invalid, the function returns NULL.

References

Wyszecki, Günther and W. S. Stiles. **Color Science: Concepts and Methods, Quantitative Data and Formulae, Second Edition**. John Wiley & Sons, 1982. pp. 145-146.

See Also

[uvfromxy\(\)](#)

Examples

```
# find some points on the daylight locus, and then their CCT
temp = seq( 2000, 10000, by=1000 )
xy = daylightLocus( temp )
cbind( xy, CCT=CCTfromxy(xy) )
##           x           y       CCT
## D2000      NA          NA        NA
## D3000      NA          NA        NA
## D4000  0.3823436 0.3837663 4000.096
## D5000  0.3457410 0.3586662 4999.749
## D6000  0.3216915 0.3377984 5998.015
## D7000  0.3053570 0.3216459 6997.858
## D8000  0.2937719 0.3092195 7997.599
## D9000  0.2852645 0.2995816 8999.301
## D10000 0.2787996 0.2919672 9991.920
```

DeltaE

*Calculate the Color Difference between Two Colors***Description**

Calculate Standard CIE Color Differences between two Colors

Usage

```
DeltaE( Lab1, Lab2, metric=1976 )
```

Arguments

Lab1	a numeric Nx3 matrix with Lab values in the rows, or a vector that can be converted to such a matrix, by row. Lab1 can also be a numeric 3-vector with a single Lab, and it is then replicated to match the size of Lab2.
Lab2	a numeric Nx3 matrix with Lab values in the rows, or a vector that can be converted to such a matrix, by row. Lab2 can also be a numeric 3-vector with a single Lab, and it is then replicated to match the size of Lab1.
metric	a vector of color metric specifiers. Valid values are '1976', '1994', and '2000', which refer to the year the metric was recommended by the CIE. They can also be given as integers, as shown. These metrics are often denoted ΔE_{1976} , ΔE_{1994} , and ΔE_{2000} . When more than one metric is given, a matrix is returned, see Value .

Value

DeltaE() returns a numeric vector of length N, or an NxM matrix. It returns a matrix iff `length(metric) = M ≥ 2`; the column names are set to the metric names. The elements of the output are the pairwise differences, i.e. between row i of Lab1 and row i of Lab2. The names or rownames are set to the rownames of one of the input matrices.

For metric=1976 the distance is simply the Euclidean distance between the two points in Lab, see *Hunt* p. 111.

For metric=1994 the symmetric variant is used, see *Hunt* p. 670. There is an asymmetric variant which is not available in this package. The weighting coefficients are for **graphic arts** (not for **textiles**).

For metric=2000 the distance is insanely complicated, see *Hunt* p. 671.

All these metrics are *symmetric*, which means that swapping Lab1 and Lab2 does not change the result.

References

Hunt, R. W. G. **The Reproduction of Colour**. 6th Edition. John Wiley & Sons. 2004.

Examples

```
DeltaE( c(50,0,0), c(51,2,2, 52,10,11, 46,-13,16) )
## [1] 3 15 21

path = system.file( "extdata/ciede2000testdata.txt", package='spacesXYZ' )
df = read.table( path, sep='\t', quote='', head=TRUE )
Lab1 = as.matrix( df[ , 1:3 ] )
Lab2 = as.matrix( df[ , 4:6 ] )
cbind( Lab1, Lab2, DeltaE( Lab1, Lab2, metric=c(1976,2000) ) )[ 1:10, ]

##      LAB_L_REF LAB_A_REF LAB_B_REF LAB_L_SAM LAB_A_SAM LAB_B_SAM DeltaE.1976 DeltaE.2000
## [1,] 50.0000  2.6772 -79.7751  50.0000  0.0000 -82.7485  4.0010633  2.0424597
## [2,] 50.0000  3.1571 -77.2803  50.0000  0.0000 -82.7485  6.3141501  2.8615102
## [3,] 50.0000  2.8361 -74.0200  50.0000  0.0000 -82.7485  9.1776999  3.4411906
## [4,] 50.0000 -1.3802 -84.2814  50.0000  0.0000 -82.7485  2.0627008  0.9999989
## [5,] 50.0000 -1.1848 -84.8006  50.0000  0.0000 -82.7485  2.3695707  1.0000047
## [6,] 50.0000 -0.9009 -85.5211  50.0000  0.0000 -82.7485  2.9152927  1.0000130
## [7,] 50.0000  0.0000  0.0000  50.0000 -1.0000  2.0000  2.2360680  2.3668588
## [8,] 50.0000 -1.0000  2.0000  50.0000  0.0000  0.0000  2.2360680  2.3668588
## [9,] 50.0000  2.4900 -0.0010  50.0000 -2.4900  0.0009  4.9800004  7.1791720
## [10,] 50.0000  2.4900 -0.0010  50.0000 -2.4900  0.0010  4.9800004  7.1791626
```

DeltaE_CAM02

Calculate the Color Difference in CAM02-UCS between Two Colors

Description

Calculate Standard CIE Color Differences between two colors in uniform color space CAM02-UCS

Usage

```
DeltaE_CAM02( CAM_1, CAM_2 )
```

Arguments

CAM_1 a data.frame returned from `CIECAM02fromXYZ()`, with 1 or N rows.

CAM_2 a data.frame returned from `CIECAM02fromXYZ()`, with 1 or N rows.

These 2 data.frames must have an equal number of rows, *or* one of them can have a single row which is then replicated to match the number of rows in the other one. The ΔE is then computed between corresponding rows.

Value

`DeltaE_CAM02()` returns a numeric vector of length N, containing the computed ΔE in uniform color space CAM02-UCS, between corresponding rows of CAM_1 and CAM_2.

References

Fairchild, Mark D. CIECAM02. in **Color Appearance Models** (3rd ed.). pp. 287-302. John Wiley & Sons. 2013.

See Also

[CIECAM02fromXYZ\(\)](#)

Examples

```
CAM = CIECAM02fromXYZ( c(19.01,20,21.78, 25,20,15), c(95.05,100,108.88), L_A=100 )
CAM
## XYZ.1 XYZ.2 XYZ.3      h      J      Q      C      M      Jp      abp.1      abp.2
## 19.01 20.00 21.78 211.58993 41.57911 153.4480 0.80776 0.7624239 54.74946 -0.2796279 -0.1719605
## 25.00 20.00 15.00 22.98284 43.12872 156.2812 33.08790 31.2308204 56.31674 9.4290922 3.9990801

DeltaE_CAM02( CAM[1, ], CAM[2, ] )

## [1] 10.68238
```

fromPolar

Convert CIE Lab and Luv from Polar Form to Rectangular Form

Description

Convert the Polar Form of CIE Lab and Luv to Rectangular Form

Usage

`LabfromLCHab(LCHab)`

`LuvfromLCHuv(LCHuv)`

Arguments

LCHab	a numeric Nx3 matrix with CIE LCHab coordinates in the rows, or a vector that can be converted to such a matrix, by row. The hue angle H must be in degrees.
LCHuv	a numeric Nx3 matrix with CIE LCHuv coordinates in the rows, or a vector that can be converted to such a matrix, by row. The hue angle H must be in degrees.

Value

LabfromLCHab() returns a numeric Nx3 matrix with CIE Lab coordinates in the rows.

LuvfromLCHuv() returns a numeric Nx3 matrix with CIE Luv coordinates in the rows.

In both cases, the rownames are copied from input to output. If the input is invalid, the functions return NULL.

References

Wikipedia. CIE 1931 color space. https://en.wikipedia.org/wiki/CIE_1931_color_space

See Also

[LCHabfromLab\(\)](#), [LCHuvfromLuv\(\)](#)

Examples

```
LabfromLCHab( c(50,10,45) )
##      L      a      b
## [1,] 50 7.071068 7.071068 # on line with slope 1
```

fromXYZ

Convert from XYZ to other Color Spaces

Description

Convert from XYZ to other Color Spaces

Usage

```
xyYfromXYZ( XYZ )
LabfromXYZ( XYZ, white )
LuvfromXYZ( XYZ, white )
```

Arguments

XYZ	a numeric Nx3 matrix with CIE XYZ coordinates in the rows, or a vector that can be converted to such a matrix, by row.
white	a numeric 3-vector giving the XYZ of reference white; all 3 numbers must be positive. white can also be a character string with the name of a standard illuminant, which is passed to standardXYZ() to get the XYZ.

Value

`xyYfromXYZ()` returns a numeric Nx3 matrix with CIE xyY coordinates in the rows. If the sum $X+Y+Z=0$, xy are set to NA.

`LabfromXYZ()` returns a numeric Nx3 matrix with CIE Lab coordinates in the rows

`LuvfromXYZ()` returns a numeric Nx3 matrix with CIE Luv coordinates in the rows

In all cases, the rownames are copied from input to output. If the input is invalid, the functions return NULL.

References

Wikipedia. CIE 1931 color space. https://en.wikipedia.org/wiki/CIE_1931_color_space

See Also

[standardXYZ\(\)](#)

Examples

```
D65 = standardXYZ( 'D65' )

xyYfromXYZ( D65 )
##           x           y Y
## D65 0.3127266 0.3290231 1    # probably not familiar

round( xyYfromXYZ(D65), 4 )
##           x           y Y
## D65 0.3127 0.329 1    # probably more familiar

LabfromXYZ( 0.18*D65, D65 ) # 18% gray card
##           L a b
## D65 49.49611 0 0    # exactly neutral, and L is about 50

D50 = standardXYZ( 'D50' )

LabfromXYZ( D50, D65 )
##           L           a           b
## D50 100 2.399554 17.65321 # D50 is far from neutral (yellowish) in D65 viewing environment
```

Description

RobertsonLocus	the table from Robertson, with 31 points from 0 to 600 mired
PrecisionLocus	a precomputed table, with 65 points from 0 to 1000 mired

Format

Both objects are `data.frames` with these columns

mired	the reciprocal temperature $10^6/T$
u	the u chromaticity, in 1960 CIE
v	the v chromaticity, in 1960 CIE

The PrecisionLocus `data.frame` has these additional columns:

up	the 1st derivative of u with respect to mired
vp	the 1st derivative of v with respect to mired
upp	the 2nd derivative of u with respect to mired
vpp	the 2nd derivative of v with respect to mired

Details

For RobertsonLocus, the values are taken from *Wyszecki & Stiles*. The lookup table on page 228 contains an error at 325 mired, which was corrected by Bruce Lindbloom (see **Source**).

For PrecisionLocus, the chromaticity values u and v are computed from first principles, from the famous equation for the Planckian radiator (with $c_2 = 1.4388 \times 10^{-2}$) and from the tabulated CIE 1931 standard observer color matching functions, by summing from 360 to 830nm. Let β denote the reciprocal temperature $10^6/T$. We think of u as a function $u(\beta)$. The column up is $u'(\beta)$, and upp is $u''(\beta)$. And similarly for v. The derivatives are computed from first principles, by summing the derivatives of the Planckian formula from 360 to 830nm. This includes the limiting case $\beta = 0$.

When this package is loaded (during `.onLoad()`), cubic splines are computed from RobertsonLocus, using `stats::splinefun()` with `method="fmm"`). And quintic splines are computed from PrecisionLocus. Both splines are C^2 continuous.

Source

http://www.brucelindbloom.com/index.html?Eqn_XYZ_to_T.html

References

Robertson, A. R. Computation of correlated color temperature and distribution temperature. *Journal of the Optical Society of America*. 58. pp. 1528-1535. 1968.

Wyszecki, Günther and W. S. Stiles. **Color Science: Concepts and Methods, Quantitative Data and Formulae, Second Edition**. John Wiley & Sons, 1982. Table 1(3.11). pp. 227-228.

See Also

[CCTfromuv\(\)](#), [planckLocus\(\)](#)

Examples

```
RobertsonLocus[ 1:10, ]
##   mired      u      v
## 1      0 0.18006 0.26352
## 2     10 0.18066 0.26589
## 3     20 0.18133 0.26846
## 4     30 0.18208 0.27119
## 5     40 0.18293 0.27407
## 6     50 0.18388 0.27709
## 7     60 0.18494 0.28021
## 8     70 0.18611 0.28342
## 9     80 0.18740 0.28668
## 10    90 0.18880 0.28997
```

```
PrecisionLocus[ 1:10, ]
##   mired      u      v      up      vp      upp      vpp
## 1      0 0.1800644 0.2635212 5.540710e-05 0.0002276279 7.115677e-07 1.977793e-06
## 2     10 0.1806553 0.2658948 6.291429e-05 0.0002469232 7.900243e-07 1.873208e-06
## 3     20 0.1813253 0.2684554 7.120586e-05 0.0002649377 8.679532e-07 1.722425e-06
## 4     30 0.1820820 0.2711879 8.026143e-05 0.0002812384 9.423039e-07 1.531723e-06
## 5     40 0.1829329 0.2740733 9.002982e-05 0.0002954676 1.010028e-06 1.309700e-06
## 6     50 0.1838847 0.2770894 1.004307e-04 0.0003073613 1.068393e-06 1.066350e-06
## 7     60 0.1849432 0.2802122 1.113592e-04 0.0003167582 1.115240e-06 8.120582e-07
## 8     70 0.1861132 0.2834161 1.226923e-04 0.0003235990 1.149155e-06 5.566812e-07
## 9     80 0.1873980 0.2866757 1.342971e-04 0.0003279171 1.169532e-06 3.088345e-07
## 10    90 0.1887996 0.2899664 1.460383e-04 0.0003298241 1.176525e-06 7.543963e-08
```

standardXYZ

Query the Standardized XYZ and xy values of Standard Illuminants and Whitepoints

Description

In careful calculations with standard illuminants and whitepoints, it is often helpful to have the 'official' values of XYZ and xy, i.e. with the right number of decimal places.

Usage

standardXYZ(name)

standardxy(name)

Arguments

name a subvector of `c('A', 'B', 'C', 'C.NBS', 'C.NTSC', 'C.JOSA', 'D50', 'D50.ICC', 'D55', 'D60', 'D65', 'D75', 'E', 'F2', 'F7', 'F11', 'ACES', 'DCI')`, which are the names of some standard illuminants and white points. Matching is partial and case-insensitive.
name can also be `NULL` or `'*'` which means to return *all* available data.

Details

All XYZ values are taken from the ASTM publication in **References**, except B which is taken from *Wyszecki & Stiles* and D50.ICC which is taken from ICC publications.

xy values were taken from *CIE, BT.709, SMPTE EG 432-1*, and *TB-2018-001*. For D65 the values in *CIE* and *BT.709* disagree; the former has 5 digits and the latter has 4. We have selected the value in *BT.709* (page 3) since is far more commonly used. Three of the Illuminant C variants are rarely used and obsolete.

Value

`standardXYZ()` returns an Mx3 matrix where M is the length of **name**. But if **name** is `NULL` or `'*'`, M is the number of records available. Each row filled with the official XYZ, but if the illuminant name is not recognized or if there is no data, the row is all NAs. The output XYZ is normalized so that Y=1. The matrix rownames are set to the full illuminant names, and colnames to `c('X', 'Y', 'Z')`. Similarly, `standardxy()` returns an Mx2 matrix with colnames set to `c('x', 'y')`.

Warning

The returned XYZs are normalized so that Y=1. In other color domains, it is common to normalize so that Y=100; in these cases be sure to multiply by 100.

Some illuminants have no standard XYZ available and some have no standard xy. In these cases, the rows are filled with NAs.

References

- ASTME 308 - 01. Standard Practice for Computing the Colors of Objects by Using the CIE System. 2001.
- BT.709. Parameter values for the HDTV standards for production and international programme exchange. June 2015.
- CIE 015:2004 - Colorimetry, 3rd edition. International Commission on Illumination (CIE). Vienna Austria. Technical Report. 2004.
- Günther Wyszecki and W. S. Stiles. Color Science: Concepts and Methods, Quantitative Data and Formulae, Second Edition. John Wiley & Sons, 1982. Table I(3.3.8) p. 769.
- TB-2018-001. **Derivation of the ACES White Point CIE Chromaticity Coordinates**. The Academy of Motion Picture Arts and Sciences. Science and Technology Council. Academy Color Encoding System (ACES) Project. June 15, 2018.
- SMPTE RP 431-2. **D-Cinema Quality - Reference Projector and Environment for the Display of DCDM in Review Rooms and Theaters**. 2011.

Examples

```

standardXYZ( c('a', 'd50', 'D50.ICC', 'D65') )
#           X Y      Z
# A      1.0985000 1 0.3558500
# D50     0.9642200 1 0.8252100
# D50.ICC 0.9642029 1 0.8249054
# D65     0.9504700 1 1.0888300

standardxy( c('a', 'D65', 'D60', 'D60.ACES', 'E', 'F2') )
#           x      y
# A      0.44758 0.40745
# D65     0.31270 0.32900
# D60     0.32163 0.33774
# D60.ACES 0.32168 0.33767
# E      0.33333 0.33333
# F2           NA      NA

```

toPolar*Convert CIE Lab and Luv to Polar Form*

Description

Convert the Rectangular Form of CIE Lab and Luv to Polar Form

Usage

```

LCHabfromLab( Lab )
LCHuvfromLuv( Luv )

```

Arguments

Lab a numeric Nx3 matrix with CIE Lab coordinates in the rows, or a vector that can be converted to such a matrix, by row.

Luv a numeric Nx3 matrix with CIE Luv coordinates in the rows, or a vector that can be converted to such a matrix, by row.

Value

a numeric Nx3 matrix with LCH coordinates in the rows. The lightness L is simply copied from input to output. The chroma C corresponds to radius in polar coordinates, and the hue H corresponds to theta. H is in degrees, not radians. The rownames are copied from input to output.

References

Wikipedia. CIE 1931 color space. https://en.wikipedia.org/wiki/CIE_1931_color_space

See Also

[LabfromLCHab\(\)](#), [LuvfromLCHuv\(\)](#)

Examples

```

LCHabfromLab( c(50,0,0) ) # a neutral gray
##      L Cab Hab
## [1,] 50  0  0      # Hue is undefined, but set to 0

LCHabfromLab( c(50,0,20) )
##      L Cab Hab
## [1,] 50  20  90    # 90 degrees, on yellow axis

LCHabfromLab( c(50,0,-20) )
##      L Cab Hab
## [1,] 50  20  270   # 270 degrees, on blue axis

```

toXYZ

Convert other Color Spaces to XYZ

Description

Convert other Color Spaces to XYZ

Usage

```

XYZfromxyY( xyY )
XYZfromLab( Lab, white )
XYZfromLuv( Luv, white )

```

Arguments

xyY	a numeric Nx3 matrix with CIE xyY coordinates in the rows, or a vector that can be converted to such a matrix, by row.
Lab	a numeric Nx3 matrix with CIE Lab coordinates in the rows, or a vector that can be converted to such a matrix, by row.
Luv	a numeric Nx3 matrix with CIE Luv coordinates in the rows, or a vector that can be converted to such a matrix, by row.
white	a numeric 3-vector giving the XYZ of reference white. white can also be a character string with the name of a standard illuminant, which is passed to standardXYZ() to get the XYZ.

Value

a numeric Nx3 matrix with XYZ coordinates in the rows. The rownames are copied from input to output.
 In XYZfromxyY() if y==0 then X and Z are set to NA. Exception: Y==0 is treated as a special case (pure black); x and y are ignored, and XYZ are all set to 0.

References

Wikipedia. CIE 1931 color space. https://en.wikipedia.org/wiki/CIE_1931_color_space

See Also

[standardXYZ\(\)](#)

Examples

```
XYZfromxyY(c(0.310897, 0.306510, 74.613450))
##           X           Y           Z
## [1,] 75.68137 74.61345 93.13427
```

```
XYZfromLab( c(50,2,-3), 'D50' )
##           X           Y           Z
## [1,] 0.1813684 0.1841865 0.1643335
```

uvfrom

Convert from XYZ or xy to Uniform Chromaticity Spaces

Description

Convert from XYZ or xy to Uniform Chromaticity Spaces

Usage

```
uvfromXYZ( XYZ, space=1976 )
```

```
uvfromxy( xy, space=1976 )
```

Arguments

XYZ	a numeric Nx3 matrix with CIE XYZ coordinates in the rows, or a vector that can be converted to such a matrix, by row.
xy	a numeric Nx2 matrix with CIE xy coordinates in the rows, or a vector that can be converted to such a matrix, by row.
space	the year of the space of output uv desired - valid spaces are 1976 and 1960. The default space=1976 has largely superseded space=1960, but the latter is still used for computing Correlated Color Temperature; see CCTfromuv() . The 1976 space is used in the function LuvfromXYZ() . The 1960 coordinates are usually denoted by uv, and the 1976 coordinates by u'v'. The only difference is that $v' = (3/2)v$.

Value

a numeric Nx2 matrix with u'v' (or uv) coordinates in the rows.

For uvfromXYZ(), if $X + 15Y + 3Z \leq 0$, uv are set to NA.

For uvfromxy(), if $-2x + 12y + 3 \leq 0$, uv are set to NA.

The rownames are copied from input to output. If the input is invalid, the function returns NULL.

References

Wikipedia. CIE 1931 color space. https://en.wikipedia.org/wiki/CIE_1931_color_space

Wikipedia. CIE 1960 color space. https://en.wikipedia.org/wiki/CIE_1960_color_space

See Also

[LuvfromXYZ\(\)](#), [standardXYZ\(\)](#)

Examples

```
# locate some standard illuminants on the 1976 UCS diagram
uvfromXYZ( standardXYZ( c('C','D50','D65','E') ) )
```

```
##           u'           v'
## C  0.2008921 0.4608838
## D50 0.2091601 0.4880734
## D65 0.1978398 0.4683363
## E   0.2105263 0.4736842
```

Index

- * **ISCC-NBS**
 - CIECAM02fromXYZ, 8
- * **XYZ**
 - daylight, 13
 - fromPolar, 16
 - fromXYZ, 17
 - toPolar, 22
 - toXYZ, 23
 - uvfrom, 24
- * **adaptation**
 - adapt, 3
 - adaptation, 5
- * **datasets**
 - Planckian Loci, 18
- * **package**
 - spacesXYZ-package, 2

adapt, 3
adaptation, 5
adaptLab, 6, 7
adaptLab (adapt), 3
adaptLuv, 6, 7
adaptLuv (adapt), 3
adaptxyY, 6, 7
adaptxyY (adapt), 3
adaptXYZ, 6, 7
adaptXYZ (adapt), 3

CAT, 4
CAT (adaptation), 5
CCTfromuv, 20, 24
CCTfromuv (Correlated Color Temperature), 9
CCTfromxy (Correlated Color Temperature), 9
CCTfromXYZ (Correlated Color Temperature), 9
CIECAM02fromXYZ, 8, 16
colorSpec::computeCCT, 12
convertColor, 2

Correlated Color Temperature, 9

daylight, 13
daylightLocus (daylight), 13
DeltaE, 14
DeltaE_CAM02, 9, 15

fromPolar, 16
fromXYZ, 17

LabfromLCHab, 22
LabfromLCHab (fromPolar), 16
LabfromXYZ (fromXYZ), 17
LCHabfromLab, 17
LCHabfromLab (toPolar), 22
LCHuvfromLuv, 17
LCHuvfromLuv (toPolar), 22
LuvfromLCHuv, 22
LuvfromLCHuv (fromPolar), 16
LuvfromXYZ, 24, 25
LuvfromXYZ (fromXYZ), 17

Planckian Loci, 9, 18
planckLocus, 20
planckLocus (Correlated Color Temperature), 9
PrecisionLocus, 12
PrecisionLocus (Planckian Loci), 18

RobertsonLocus, 12
RobertsonLocus (Planckian Loci), 18

spacesXYZ-package, 2
standardxy (standardXYZ), 20
standardXYZ, 4, 7, 8, 17, 18, 20, 23–25
stats::splinefun, 9, 11, 12, 19

toPolar, 22
toXYZ, 23

uvfrom, 24

[uvfromxy](#), 13

[uvfromxy \(uvfrom\)](#), 24

[uvfromXYZ \(uvfrom\)](#), 24

[xyYfromXYZ \(fromXYZ\)](#), 17

[XYZfromLab \(toXYZ\)](#), 23

[XYZfromLuv \(toXYZ\)](#), 23

[XYZfromxyY \(toXYZ\)](#), 23